

---

Stream: Internet Engineering Task Force (IETF)

RFC: [9983](#)

Category: Standards Track

Published: May 2026

ISSN: 2070-1721

Authors:

R. Chen

D. Zhao

P. Psenak

K. Talaulikar

C. Lin

*ZTE Corporation*

*ZTE Corporation*

*Cisco Systems*

*Cisco Systems*

*New H3C Technologies*

# RFC 9983

## OSPFv2 Anycast Property Advertisement

---

### Abstract

An IP prefix may be configured as anycast and, as such, the same value can be advertised by multiple routers. It is useful for other routers to know that the advertisement is for an anycast prefix.

This document defines a new flag in the OSPFv2 Extended Prefix TLV Flags to advertise the anycast property. The document also specifies a companion YANG module for managing this function.

### Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in Section 2 of RFC 7841.

Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <https://www.rfc-editor.org/info/rfc9983>.

### Copyright Notice

Copyright (c) 2026 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions

with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

## Table of Contents

1. Introduction	2
1.1. Requirements Language	3
2. OSPFv2 Anycast Property Advertisement	3
3. BGP-LS Advertisement	4
4. YANG Data Model	4
4.1. Tree for the YANG Data Model	4
4.2. YANG Data Model for OSPFv2 Anycast Property Advertisement	4
5. IANA Considerations	6
5.1. OSPFv2 Extended Prefix TLV Flags Registry	7
5.2. OSPFv2 Anycast Flag YANG Module Registration	7
6. Security Considerations	7
6.1. Protocol Security Considerations	7
6.2. YANG Security Considerations	7
7. References	8
7.1. Normative References	8
7.2. Informative References	9
Acknowledgements	10
Contributors	10
Authors' Addresses	10

## 1. Introduction

An IP prefix may be configured as anycast and, as such, the same value can be advertised by multiple routers. It is useful for other routers to know that the advertisement is for an anycast prefix.

[RFC7684] defines OSPFv2 Opaque Link State Advertisements (LSAs) based on Type-Length-Value (TLV) tuples that can be used to associate additional attributes with prefixes or links. The OSPFv2 Extended Prefix TLV that is contained in the OSPFv2 Extended Prefix Opaque LSA is used to advertise additional attributes associated with a prefix.

Extensions related to the anycast property of prefixes have been specified for IS-IS [RFC9352] and OSPFv3 [RFC9513], even though those documents are related to Segment Routing over IPv6, the anycast property applies to any IP prefix advertisement. This document defines a flag to advertise the anycast property for a prefix advertisement in OSPFv2 in the Flags field of the OSPFv2 Extended Prefix TLV Flags (Section 2.1 of [RFC7684]). The document also specifies a companion YANG module for managing this function.

## 1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

## 2. OSPFv2 Anycast Property Advertisement

An IP prefix may be configured as anycast; it is useful for other routers to know that the advertisement is for an anycast prefix.

In the context of the flags defined in this document, the term "set" means the bit is set to 1; "clear" means the bit is set to 0.

A flag is introduced in the "OSPFv2 Extended Prefix TLV Flags" IANA registry (see [RFC7684]) to advertise the anycast property:

Value: 0x10

Description: Anycast Flag (AC-Flag)

The only meaning of the AC-Flag is that the prefix is intended to be advertised by multiple nodes.

When a prefix is configured as anycast, the AC-Flag **MUST** be set. Otherwise, this flag **MUST** be clear.

The AC-Flag and the N-flag (Section 2.1 of [RFC7684]) **MUST NOT** both be set. The reception of an advertisement with both the N-flag and AC-Flag set **MUST** be considered a configuration anomaly, and the N-flag **MUST** be ignored. Additionally, the detection of such a conflicting advertisement **SHOULD** be logged as an operational error (subject to rate-limiting).

The AC-Flag **MUST** be preserved when the OSPFv2 Extended Prefix Opaque LSA is re-advertised into other areas.

The same prefix can be advertised by multiple routers, and, if at least one of them sets the AC-Flag in its advertisement, the prefix is considered to be anycast.

A prefix that is advertised by a single node and without an AC-Flag is considered to be a node-specific prefix.

Anycast prefixes **SHOULD** be consistently managed throughout the network. Since an AC-Flag set takes precedence in identifying the anycast property, stale configurations should be strictly monitored.

### 3. BGP-LS Advertisement

[RFC9085] defines the Prefix Attribute Flags TLV for Border Gateway Protocol - Link State (BGP-LS) that carries prefix attribute flags information. The Flags field of this TLV is interpreted according to OSPFv2 [RFC7684]. Thus, the Flags field of the BGP-LS Prefix Attribute Flags TLV also conveys the anycast property introduced by this document.

### 4. YANG Data Model

YANG [RFC7950] is a data definition language used to define the contents of a conceptual data store that allows networked devices to be managed using Network Configuration Protocol (NETCONF) [RFC6241] or RESTCONF [RFC8040].

This section defines a YANG data model that can be used to manage the usage of the OSPFv2 Anycast Property as defined in this document, which augments the OSPF YANG data model [RFC9129] and the YANG Data Model for Routing Management [RFC8349].

#### 4.1. Tree for the YANG Data Model

This document uses the graphical representation of data models per [RFC8340].

The following shows the tree diagram of the module:

```
module: ietf-ospf-anycast-flag
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
    /ospf:interfaces/ospf:interface:
      +--rw anycast-flag?  boolean
```

#### 4.2. YANG Data Model for OSPFv2 Anycast Property Advertisement

The "ietf-ospf-anycast-flag" module defined in this document imports typedefs from [RFC8349] and [RFC9129].

```
<CODE BEGINS> file "ietf-ospf-anycast-flag@2026-05-19.yang"
```

```
module ietf-ospf-anycast-flag {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-ospf-anycast-flag";
  prefix ospf-anycast-flag;

  import ietf-routing {
    prefix rt;
    reference
      "RFC 8349: A YANG Data Model for Routing
      Management (NMDA Version)";
  }
  import ietf-ospf {
    prefix ospf;
    reference
      "RFC 9129: YANG Data Model for the OSPF Protocol";
  }

  organization
    "IETF LSR - Link State Routing Working Group";
  contact
    "WG Web: <https://datatracker.ietf.org/wg/lsr/>
    WG List: <mailto:lsr@ietf.org>

    Author: Ran Chen
            <mailto:chen.ran@zte.com.cn>
    Author: Detao Zhao
            <mailto:zhao.detao@zte.com.cn>
    Author: Peter Psenak
            <mailto:ppsenak@cisco.com>
    Author: Ketan Talaulikar
            <mailto:ketant.ietf@gmail.com>
    Author: Changwang Lin
            <mailto:linchangwang.04414@h3c.com>";

  description
    "This YANG module adds the support of managing an OSPFv2
    prefix as anycast.

    The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
    NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
    'MAY', and 'OPTIONAL' in this document are to be interpreted as
    described in BCP 14 (RFC 2119) (RFC 8174) when, and only when,
    they appear in all capitals, as shown here.

    Copyright (c) 2026 IETF Trust and the persons identified as
    authors of the code. All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject to
    the license terms contained in, the Revised BSD License set
    forth in Section 4.c of the IETF Trust's Legal Provisions
    Relating to IETF Documents
    (https://trustee.ietf.org/license-info).

    All revisions of IETF and IANA published modules can
    be found at the YANG Parameters registry group
    (https://www.iana.org/assignments/yang-parameters);
```



## 5.1. OSPFv2 Extended Prefix TLV Flags Registry

IANA has allocated the following value in the "OSPFv2 Extended Prefix TLV Flags" registry:

0x10: AC-Flag (Anycast Flag)

## 5.2. OSPFv2 Anycast Flag YANG Module Registration

IANA has registered the following URI in the "ns" registry within the "IETF XML Registry" registry group (see [\[RFC3688\]](#)):

ID: yang:ietf-ospf-anycast-flag

URI: urn:ietf:params:xml:ns:yang:ietf-ospf-anycast-flag

Registrant Contact: The IESG

XML: N/A; the requested URI is an XML namespace

IANA has registered the following YANG module in the "YANG Module Names" registry ([\[RFC6020\]](#)) within the "YANG Parameters" registry group.

Name: ietf-ospf-anycast-flag

Maintained by IANA? N

Namespace: urn:ietf:params:xml:ns:yang:ietf-ospf-anycast-flag

Prefix: ospf-anycast-flag

Reference: RFC 9983

# 6. Security Considerations

## 6.1. Protocol Security Considerations

Procedures and protocol extensions defined in this document do not affect the OSPFv2 security model. See the "Security Considerations" section of [\[RFC7684\]](#) for a discussion of OSPFv2 security.

The newly introduced AC-Flag, which **MUST** be either set or clear, introduces operational dependencies that impact the semantic validity of the advertised prefix. The correct semantic interpretation of the AC-Flag relies on both router implementation support for the flag and accurate operator configuration of the anycast route. Consequently, receivers **MUST** consider the possibility of misconfiguration or inconsistent implementation when relying on the AC-Flag for forwarding or security decisions.

## 6.2. YANG Security Considerations

This section is modeled after the template described in [Section 3.7](#) of [\[RFC9907\]](#).

The "ietf-ospf-anycast-flag" YANG module defines a data model that is designed to be accessed via YANG-based management protocols, such as Network Configuration Protocol (NETCONF) [RFC6241] and RESTCONF [RFC8040]. These YANG-based management protocols (1) have to use a secure transport layer (e.g., SSH [RFC4252], TLS [RFC8446], and QUIC [RFC9000]) and (2) have to use mutual authentication.

The Network Configuration Access Control Model (NACM) [RFC8341] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There is a data node defined in this YANG module that is writable/creatable/deletable (i.e., config true, which is the default). This data node can be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) and delete operations to this data node without proper protection or authentication can have a negative effect on network operations. Specifically, the following subtree and data node have particular sensitivities/vulnerabilities:

```
/ospf:ospf/ospf:areas/ospf:area/ospf:interfaces/ospf:interface/ospf-anycast-flag:anycast-flag
```

As specified in Section 2, the AC-Flag and the N-flag **MUST NOT** both be set to 1. This rule is enforced by a "must" constraint in the YANG module to prevent configuration anomalies. The handling of such anomalies is defined in Section 2. Modifications to this data node without proper protection could prevent interpreting the IPv4 prefix as anycast or node-specific.

The readable data node in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to this data node. Specifically, the following subtree and data node have particular sensitivities/vulnerabilities:

```
/ospf:ospf/ospf:areas/ospf:area/ospf:interfaces/ospf:interface/ospf-anycast-flag:anycast-flag
```

Unauthorized access to the data node of this subtree can disclose specific anycast property information for OSPF prefixes on a device.

There are no particularly sensitive RPC or action operations.

## 7. References

### 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

- 
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", RFC 6020, DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
  - [RFC7684] Psenak, P., Gredler, H., Shakir, R., Henderickx, W., Tantsura, J., and A. Lindem, "OSPFv2 Prefix/Link Attribute Advertisement", RFC 7684, DOI 10.17487/RFC7684, November 2015, <<https://www.rfc-editor.org/info/rfc7684>>.
  - [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", RFC 7950, DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
  - [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
  - [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, RFC 8341, DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
  - [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", RFC 8349, DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
  - [RFC9085] Previdi, S., Talaulikar, K., Ed., Filsfils, C., Gredler, H., and M. Chen, "Border Gateway Protocol - Link State (BGP-LS) Extensions for Segment Routing", RFC 9085, DOI 10.17487/RFC9085, August 2021, <<https://www.rfc-editor.org/info/rfc9085>>.
  - [RFC9129] Yeung, D., Qu, Y., Zhang, Z., Chen, I., and A. Lindem, "YANG Data Model for the OSPF Protocol", RFC 9129, DOI 10.17487/RFC9129, October 2022, <<https://www.rfc-editor.org/info/rfc9129>>.

## 7.2. Informative References

- [RFC4252] Ylonen, T. and C. Lonvick, Ed., "The Secure Shell (SSH) Authentication Protocol", RFC 4252, DOI 10.17487/RFC4252, January 2006, <<https://www.rfc-editor.org/info/rfc4252>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", RFC 6241, DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", RFC 8040, DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", BCP 215, RFC 8340, DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", RFC 8446, DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

- [RFC9000] Iyengar, J., Ed. and M. Thomson, Ed., "QUIC: A UDP-Based Multiplexed and Secure Transport", RFC 9000, DOI 10.17487/RFC9000, May 2021, <<https://www.rfc-editor.org/info/rfc9000>>.
- [RFC9352] Psenak, P., Ed., Filsfils, C., Bashandy, A., Decraene, B., and Z. Hu, "IS-IS Extensions to Support Segment Routing over the IPv6 Data Plane", RFC 9352, DOI 10.17487/RFC9352, February 2023, <<https://www.rfc-editor.org/info/rfc9352>>.
- [RFC9513] Li, Z., Hu, Z., Talaulikar, K., Ed., and P. Psenak, "OSPFv3 Extensions for Segment Routing over IPv6 (SRv6)", RFC 9513, DOI 10.17487/RFC9513, December 2023, <<https://www.rfc-editor.org/info/rfc9513>>.
- [RFC9907] Bierman, A., Boucadair, M., Ed., and Q. Wu, "Guidelines for Authors and Reviewers of Documents Containing YANG Data Models", BCP 216, RFC 9907, DOI 10.17487/RFC9907, March 2026, <<https://www.rfc-editor.org/info/rfc9907>>.

## Acknowledgements

The authors would like to thank Acee Lindem for aligning the terminology with existing OSPF documents and for editorial improvements.

## Contributors

This document has the following contributor:

### Yingzhen Qu

Futurewei Technologies

Email: [yingzhen.ietf@gmail.com](mailto:yingzhen.ietf@gmail.com)

## Authors' Addresses

### Ran Chen

ZTE Corporation

Nanjing

China

Email: [chen.ran@zte.com.cn](mailto:chen.ran@zte.com.cn)

### Detao Zhao

ZTE Corporation

Nanjing

China

Email: [zhao.detao@zte.com.cn](mailto:zhao.detao@zte.com.cn)

### Peter Psenak

Cisco Systems

Email: [ppsenak@cisco.com](mailto:ppsenak@cisco.com)

**Ketan Talaulikar**

Cisco Systems

Email: [ketant.ietf@gmail.com](mailto:ketant.ietf@gmail.com)**Changwang Lin**

New H3C Technologies

Beijing

China

Email: [linchangwang.04414@h3c.com](mailto:linchangwang.04414@h3c.com)