

The **mandi** Bundle

Paul J. Heafner*

Printed February 27, 2024

mandi version v3.2.2 dated 2024-02-27
mandistudent version v3.2.2 dated 2024-02-27
mandiexp version v3.2.2 dated 2024-02-27

*Email: heafnerj@gmail.com

Contents

Acknowledgements	3
Change History	4
List of Web VPython Programs	5
List of VPython Programs	5
List of Figures	5
1 Introduction	6
2 Getting Help	6
3 Code Availability	6
4 Compatibility with Other Packages and Classes	6
5 Student/Instructor Quick Guide	7
6 The <code>mandi</code> Package	8
6.1 Package Options	8
6.2 The <code>mandisetup</code> Command	8
6.3 Lua ^{La} T _E X is Required	8
6.4 Physical Quantities	9
6.4.1 Typesetting Physical Quantities	9
6.4.2 Checking Physical Quantities	10
6.4.3 Predefined Physical Quantities	10
6.4.4 Defining and Redefining Physical Quantities	22
6.4.5 Changing Units	22
6.5 Physical Constants	23
6.5.1 Typesetting Physical Constants	23
6.5.2 Checking Physical Constants	24
6.5.3 Predefined Physical Constants	24
6.5.4 Defining and Redefining Physical Constants	30
6.5.5 Changing Precision	31
6.6 Predefined Units and Constructs	31
6.7 <code>mandi</code> Source Code	35
7 The <code>mandistudent</code> Package	52
7.1 Traditional Vector Notation	52
7.2 Problems and Annotated Problem Solutions	56
7.3 Coordinate-Free and Index Notation	60
7.4 Web VPython and VPython Program Listings	62
7.5 The <code>webpythonblock</code> Environment	62
7.6 The <code>vpythonfile</code> Command	68
7.7 The <code>webpythoninline</code> and <code>vpythoninline</code> Commands	70
7.8 <code>mandistudent</code> Source Code	71
8 The <code>mandiexp</code> Package	83
8.1 The Fundamental Principles	83
8.2 Other Symbols	85
8.3 <code>mandiexp</code> Source Code	88
Index	95

Acknowledgements

To all of the students who have learned $\text{\LaTeX} 2_{\varepsilon}$ in my introductory physics courses over the years, I say a heartfelt thank you. You have contributed directly to the state of this software and to its use in introductory physics courses and to innovating how physics is taught.

I also acknowledge the $\text{\LaTeX} 2_{\varepsilon}$ developers who inhabit the [TeX StackExchange](#) site. Entering a new culture is daunting for anyone, especially for newcomers; the $\text{\LaTeX} 2_{\varepsilon}$ development culture is no exception. We all share a passion for creating beautiful documents and I learned much over the summers of 2020 and 2021 that improved my ability to do just that. There are too many of you to list individually, and I would surely accidentally omit some were I to try. Collectively, I thank you all for your patience and advice.

Change History

v3.0.0 – 2021-08-22		
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52} <code>mandiexp</code> ^{P.83}		
Initial release	6	
v3.0.1 – 2021-08-24		
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52}		
<code>mandiexp</code> ^{P.83} Minor doc changes	6	
v3.1.0 – 2022-01-27		
<code>mandi</code> ^{P.8} Added GitHub links to code	6	
<code>mandi</code> ^{P.8} Added <code>\hbar</code> ^{P.33}	46	
<code>mandi</code> ^{P.8} Added <code>\lorentzfactor</code> ^{P.16}	43	
<code>mandi</code> ^{P.8} Added a negative space to <code>\lightspeed</code> ^{P.32}	37	
<code>mandi</code> ^{P.8} Constants' values now use only <code>\times</code>	46	
<code>mandi</code> ^{P.8} Improved <code>\CheckConstant</code> ^{P.24}	50	
<code>mandi</code> ^{P.8} Improved <code>\CheckQuantity</code> ^{P.10}	50	
<code>mandi</code> ^{P.8} Unknown package options handled safely	36	
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52} L ^T E _X 3 code now conforms to formatting standards	6	
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52} <code>mandiexp</code> ^{P.83}		
Code formatted for better readability	6	
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52} <code>mandiexp</code> ^{P.83}		
<code>xparse</code> is loaded for older formats	6	
<code>mandi</code> ^{P.8} <code>\mivector</code> ^{P.34} now requires more than one component	50	
<code>mandistudent</code> ^{P.52} All instances of <code>GlowScript</code> have been changed to Web VPython	62	
<code>mandistudent</code> ^{P.52} Default URL for <code>\vpythonfile</code> ^{P.68} is now vpython.org	81	
<code>mandistudent</code> ^{P.52} Slightly modified <code>\image</code> ^{P.59}	77	
<code>mandistudent</code> ^{P.52} URLs fixed in <code>\vpythonfile</code> ^{P.68}	81	
<code>mandistudent</code> ^{P.52} URLs fixed in <code>webvpythonblock</code> ^{P.62}	80	
<code>mandistudent</code> ^{P.52} Version number works	71	
<code>mandistudent</code> ^{P.52} <code>\diff</code> renamed to <code>\df</code> ^{P.62}		
for compatibility with the <code>numerica</code> package	62	
<code>mandistudent</code> ^{P.52} <code>\vec</code> ^{P.52} and <code>\dirvec</code> ^{P.52}		
no longer add <code>\scriptspace</code> when no sub/superscript is given	74	
<code>mandistudent</code> ^{P.52} <code>webvpythonblock*</code> ^{P.62} is a variant of <code>webvpythonblock</code> ^{P.62} that omits the QR code	81	
<code>mandistudent</code> ^{P.52} <code>webvpythonblock</code> ^{P.62} now automatically generates QR codes for program listings	80	
<code>mandiexp</code> ^{P.83} Version number works	88	
v3.2.0 – 2023-08-01		
<code>mandi</code> ^{P.8} Changed <code>\unit</code> to <code>\units</code>	37	
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52} <code>mandiexp</code> ^{P.83}		
Source updated	6	
<code>mandistudent</code> ^{P.52} Added statement about BEAMER compatibility	6	
<code>mandistudent</code> ^{P.52} <code>\hilite</code> ^{P.58} is not defined if BEAMER is loaded	77	
<code>mandistudent</code> ^{P.52} <code>\vpythonfile</code> ^{P.68} now shows URL in header	81	
<code>mandistudent</code> ^{P.52} <code>physicsproblem</code> ^{P.56} and <code>physicsproblem*</code> ^{P.56} are not defined if BEAMER is loaded	76	
<code>mandistudent</code> ^{P.52} <code>webvpythonblock</code> ^{P.62} and <code>webvpythonblock*</code> ^{P.62} now show URL in header	80	
<code>mandiexp</code> ^{P.83} <code>mandistudent</code> is loaded for <code>\vec*</code>	88	
v3.2.1 – 2023-11-22		
<code>mandi</code> ^{P.8} Minor changes to <code>mandi.ins</code> inside <code>mandi.dtx</code>	6	
<code>mandi</code> ^{P.8} <code>mandistudent</code> ^{P.52} <code>mandiexp</code> ^{P.83}		
Source updated and bumped version for new CTAN upload	6	
Improved <code>README.md</code> at request of CTAN maintainer	6	
v3.2.2 – 2024-02-27		
<code>mandi</code> ^{P.8} Ensured all subscripts and superscripts are braced	6	
<code>mandi</code> ^{P.8} Removed unnecessary <code>\ExplSyntaxOn</code> and <code>\ExplSyntaxOff</code> pairs	6	

List of Web VPython Programs

1	Example With QR Code	64
2	Example Without QR Code	67

List of VPython Programs

1	A VPython Program	69
---	-----------------------------	----

List of Figures

1	Image shown 20 percent actual size.	60
2	Image shown 20 percent actual size and rotated.	60

1 Introduction

The `mandi`¹ bundle consists of three packages: `mandi`, `mandistudent`, and `mandiexp`. Package `mandi`^{→ P.8} provides the core functionality, namely correctly typesetting physical quantities and constants with their correct SI units as either scalars or vectors, depending on which is appropriate. Package `mandistudent`^{→ P.52} provides other typesetting capability appropriate for written problem solutions. Finally, package `mandiexp`^{→ P.83} provides commands for typesetting expressions from *Matter & Interactions*².

So many changes have been made that I think the best approach for all users is to treat this as a brand new experience. I think the most important thing to keep in mind is that I assume all users will have a relatively recent TeX distribution (like TeX Live) that includes an updated kernel. If users report that this is a major problem, I can provide some degree of backwards compatibility. However, I use a fully updated TeX Live distribution.

2 Getting Help

If you have a question about `mandi`, first please read this documentation to make sure your question is not addressed here. Then if you wish, email me. As a user, you deserve courteous and timely help if you need it. You will never get a response from me saying that because this software is free you are not entitled to help using it. It is sad that some developers take that attitude. Using free software does not absolve the developer of helping users unless the license specifically says so.

3 Code Availability

The `mandi` source repository's `main` branch is at <https://github.com/heafnerj/mandi>. This code will usually coincide with that found on CTAN. The very latest build can be found on the `dev` branch found at <https://github.com/heafnerj/mandi/tree/dev>. Students and other academic academic users should probably get the `dev` branch code since it is stable and may contain improvements over the `main` branch code.

4 Compatibility with Other Packages and Classes

When using BEAMER, certain commands in the `mandistudent` package are not defined. Because BEAMER uses the `enumitem` package, the `physicsproblem`^{→ P.56} and `physicsproblem*`^{→ P.56} environments are not defined. The `\hilite`^{→ P.58} command is also not defined because it does not work and I do not currently know why.

¹The bundle name can be pronounced either with two syllables, to rhyme with *candy*, or with three syllables, as *M and I*.

²See *Matter & Interactions* and <https://matterandinteractions.org/> for details.

5 Student/Instructor Quick Guide

Use `\vecP.52` to typeset the symbol for a vector. Use `\magnitudeP.55` to typeset the symbol for a vector's magnitude. Use `\dirvecP.52` to typeset the symbol for a vector's direction. Use `\changeinP.53` to typeset the symbol for the change in a vector or scalar. Use `\zerovecP.53` to typeset the zero vector. Use `\timestentoP.34` to typeset scientific notation.

<code>\(\vec{p} \) or \(\vec*{p} \)</code>	p or \vec{p}
<code>\(\vec{p}_{\text{final}} \) or \(\vec*{p}_{\text{final}} \)</code>	p_{final} or \vec{p}_{final}
<code>\(\magnitude{\vec{p}} \) or \(\magnitude*{\vec{p}} \)</code>	$\ p\ $ or $\ p_{\text{final}}\ $
<code>\(\dirvec{p} \) or \(\dirvec*{p} \)</code>	\hat{p} or \hat{p}
<code>\(\changein{\vec{p}} \) or \(\changein*{p} \)</code>	Δp or Δt
<code>\(\zerovec \) or \(\zerovec* \)</code>	$\mathbf{0}$ or $\vec{0}$
<code>\(6.02\timestento{-19} \)</code>	6.02×10^{-19}

Use a `physical quantity'sP.9` name to typeset a magnitude and that quantity's units. If the quantity is a vector, you can add `vector` either to the beginning or the end of the quantity's name. For example, if you want momentum, use `\momentumP.9` and its variants.

<code>\(\momentum{7.071} \)</code>	$7.071 \text{ kg} \cdot \text{m/s}$
<code>\(\vector{\momentum}{3,-4,5} \)</code>	$\langle 3, -4, 5 \rangle \text{ kg} \cdot \text{m/s}$
<code>\(\momentum{\vector{3,-4,5}} \)</code>	$\langle 3, -4, 5 \rangle \text{ kg} \cdot \text{m/s}$

Use a `physical constant'sP.23` name to typeset its numerical value and units. Append `mathsymbol` to the constant's name to get its mathematical symbol. For example, if you want to typeset the vacuum permittivity, use `\vacuumpermittivityP.30` and its variant.

<code>\(\vacuumpermittivitymathsymbol = \vacuumpermittivity \)</code>	$\epsilon_0 = 9 \times 10^{-12} \text{ C}^2/\text{N} \cdot \text{m}^2$
--	--

Use `\mivectorP.34` to typeset symbolic vectors with components. Use the alias `\directionP.13` to typeset a direction or unit vector.

<code>\(\mivector{\slot,\slot,\slot} \) or \(\mivector{p_x,p_y,p_z} \)</code>	$\langle \frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}} \rangle$ or $\langle p_x, p_y, p_z \rangle$
	$\langle \frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}}, \frac{1}{\sqrt{3}} \rangle$ or $\langle p_x, p_y, p_z \rangle$

Use `\physicsproblemP.56` and `\partsP.56` and `\problempartP.56` for problems. For step-by-step mathematical solutions use `\physicssolutionP.57`. Use `\webpythonblockP.62` to typeset Web VPython programs. Use `\vpythonfileP.68` to typeset VPython program files.

6 The `mandi` Package

Load `mandi` as you would any package in your preamble.

```
\usepackage[options]{mandi}
```

`\mandiversion`

Typesets the current version and build date.

```
The version is \mandiversion{} and is a stable build.
```

```
The version is v3.2.2 dated 2024-02-27 and is a stable build.
```

6.1 Package Options

N 2021-01-30
N 2021-01-30

`units`=*type of unit* (initially unspecified, set to `alternate`)
`preciseconstants`=*boolean* (initially unspecified, set to `false`)

Now `mandi` uses a key-value interface for options. The `units` key can be set to `base`, `derived`, or `alternate`. The `preciseconstants` key is always either `true` or `false`.

6.2 The `mandisetup` Command

N 2021-02-17

```
\mandisetup{(options)}
```

Command to set package options on the fly after loadtime. This can be done in the preamble or inside the `\begin{document}... \end{document}` environment.

```
\mandisetup{units=base}
```

```
\mandisetup{preciseconstants}
```

```
\mandisetup{preciseconstants = false}
```

6.3 Lua^LA_TE_X is Required

In order to make use of better fonts and Unicode features, `mandi` now requires the Lua^LA_TE_X engine for processing documents. It will not work with other engines.

6.4 Physical Quantities

6.4.1 Typesetting Physical Quantities

Typesetting physical quantities and constants using semantically appropriate names, along with the correct [SI units](#), is the core function of `mandi`. Take momentum as the prototypical physical quantity in an introductory physics course.

```
\momentum{\langle magnitude \rangle}
\momentumvector{\langle c_1, \dots, c_n \rangle}
\vectormomentum{\langle c_1, \dots, c_n \rangle}
```

Command for momentum and its vector variants. The default units will depend on the options passed to `mandi` at load time. Alternate units are the default. Other units can be forced as demonstrated. The vector variants can take more than three components. Note the other variants for the quantity's value and units.

Commands that include the name of a physical quantity typeset units, so they shouldn't be used for algebraic or symbolic values of components. Don't use `\vectormomentum{mv_{x},mv_{y},mv_{z}}` but instead the generic `\mivector{mv_{x},mv_{y},mv_{z}}` instead.

6.4.2 Checking Physical Quantities

U 2022-01-27

`\CheckQuantity{<name>}`

Command to check and typeset the command, base units, derived units, and alternate units of a defined physical quantity.

6.4.3 Predefined Physical Quantities

Every other defined physical quantity can be treated similarly. Just replace `momentum` with the quantity's name. Obviously, the variants that begin with `\vector` will not be defined for scalar quantities. Here are all the physical quantities, with all their units, defined in `mandi`. Remember that units are not present with symbolic (algebraic) quantities, so do not use the `\vector` variants of these commands for symbolic components. Use `\mivector`^{P.34} instead.

N 2021-02-24

```
\acceleration{<magnitude>}
\accelerationvector{<c1, ..., cn>}
\vectoracceleration{<c1, ..., cn>}
```

command	<code>\acceleration</code>	
base	<code>derived</code>	<code>alternate</code>
$m \cdot s^{-2}$	N/kg	m/s^2

`\amount{<magnitude>}`

command	<code>\amount</code>	
base	<code>derived</code>	<code>alternate</code>
mol	mol	mol

N 2021-02-24

```
\angularacceleration{<magnitude>}
\angularaccelerationvector{<c1, ..., cn>}
\vectorangularacceleration{<c1, ..., cn>}
```

command	<code>\angularacceleration</code>	
base	<code>derived</code>	<code>alternate</code>
$rad \cdot s^{-2}$	rad/s^2	rad/s^2

`\angularfrequency{<magnitude>}`

command	<code>\angularfrequency</code>	
base	<code>derived</code>	<code>alternate</code>
$rad \cdot s^{-1}$	rad/s	rad/s

N 2021-02-24

```
\angularimpulse{<magnitude>}
\angularimpulsevector{<c1, ..., cn>}
\vectorangularimpulse{<c1, ..., cn>}
```

command	<code>\angularimpulse</code>	
base	<code>derived</code>	<code>alternate</code>
$kg \cdot m^2 \cdot s^{-1}$	$kg \cdot m^2/s$	$kg \cdot m^2/s$

N 2021-02-24

```
\angularmomentum{\(magnitude)}
\angularmomentumvector{\(c_1, \dots, c_n)}
\vectorangularmomentum{\(c_1, \dots, c_n)}
```

command	<code>\angularmomentum</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-1}$	$\text{kg} \cdot \text{m}^2/\text{s}$	$\text{kg} \cdot \text{m}^2/\text{s}$

N 2021-02-24

```
\angularvelocity{\(magnitude)}
\angularvelocityvector{\(c_1, \dots, c_n)}
\vectorangularvelocity{\(c_1, \dots, c_n)}
```

command	<code>\angularvelocity</code>	
base	<code>derived</code>	alternate
$\text{rad} \cdot \text{s}^{-1}$	rad/s	rad/s

```
\area{\(magnitude)}
```

command	<code>\area</code>	
base	<code>derived</code>	alternate
m^2	m^2	m^2

```
\areachargedensity{\(magnitude)}
```

command	<code>\areachargedensity</code>	
base	<code>derived</code>	alternate
$\text{A} \cdot \text{s} \cdot \text{m}^{-2}$	C/m^2	C/m^2

```
\areamassdensity{\(magnitude)}
```

command	<code>\areamassdensity</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^{-2}$	kg/m^2	kg/m^2

```
\capacitance{\(magnitude)}
```

command	<code>\capacitance</code>	
base	<code>derived</code>	alternate
$\text{A}^2 \cdot \text{s}^4 \cdot \text{kg}^{-1} \cdot \text{m}^{-2}$	F	C/V

```
\charge{\(magnitude)}
```

command	<code>\charge</code>	
base	<code>derived</code>	alternate
$\text{A} \cdot \text{s}$	C	C

N 2021-02-24

```
\cmagneticfield{\(magnitude)}
\cmagneticfieldvector{\(c_1, \dots, c_n\)}
\vectorcmagneticfield{\(c_1, \dots, c_n\)}
```

command	\cmagneticfield	
base	derived	alternate
$\text{kg} \cdot \text{m} \cdot \text{A}^{-1} \cdot \text{s}^{-3}$	N/C	N/C

```
\conductance{\(magnitude)}
```

command	\conductance	
base	derived	alternate
$\text{A}^2 \cdot \text{s}^3 \cdot \text{kg}^{-1} \cdot \text{m}^{-2}$	S	A/V

```
\conductivity{\(magnitude)}
```

command	\conductivity	
base	derived	alternate
$\text{A}^2 \cdot \text{s}^3 \cdot \text{kg}^{-1} \cdot \text{m}^{-3}$	S/m	A/V · m

```
\conventionalcurrent{\(magnitude)}
```

command	\conventionalcurrent	
base	derived	alternate
A	C/s	A

```
\current{\(magnitude)}
```

command	\current	
base	derived	alternate
A	A	A

```
\currentdensity{\(magnitude)}
```

```
\currentdensityvector{\(c_1, \dots, c_n\)}
\vectorcurrentdensity{\(c_1, \dots, c_n\)}
```

command	\currentdensity	
base	derived	alternate
$\text{A} \cdot \text{m}^{-2}$	$\text{C/s} \cdot \text{m}^2$	A/m^2

```
\dielectricconstant{\(magnitude)}
```

command	\dielectricconstant	
base	derived	alternate

N 2021-02-24

```
\direction{\langle magnitude \rangle}
\directionvector{\langle c_1, \dots, c_n \rangle}
\vector{direction}{\langle c_1, \dots, c_n \rangle}
```

command base	\direction derived	alternate
-----------------	-----------------------	-----------

N 2021-02-24

```
\displacement{\langle magnitude \rangle}
\displacementvector{\langle c_1, \dots, c_n \rangle}
\vector{displacement}{\langle c_1, \dots, c_n \rangle}
```

command base	\displacement derived	alternate
m	m	m

```
\duration{\langle magnitude \rangle}
```

command base	\duration derived	alternate
s	s	s

N 2021-02-24

```
\electricdipolemoment{\langle magnitude \rangle}
\electricdipolemomentvector{\langle c_1, \dots, c_n \rangle}
\vector{electricdipolemoment}{\langle c_1, \dots, c_n \rangle}
```

command base	\electricdipolemoment derived	alternate
A · s · m	C · m	C · m

N 2021-02-24

```
\electricfield{\langle magnitude \rangle}
\electricfieldvector{\langle c_1, \dots, c_n \rangle}
\vector{electricfield}{\langle c_1, \dots, c_n \rangle}
```

command base	\electricfield derived	alternate
kg · m · A ⁻¹ · s ⁻³	V/m	N/C

```
\electricflux{\langle magnitude \rangle}
```

command base	\electricflux derived	alternate
kg · m ³ · A ⁻¹ · s ⁻³	V · m	N · m ² /C

```
\electricpotential{\langle magnitude \rangle}
```

command	\electricpotential	
base	derived	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{A}^{-1} \cdot \text{s}^{-3}$	V	V

N 2021-05-01

\electricpotentialdifference{\langle magnitude\rangle}

command	\electricpotentialdifference	
base	derived	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{A}^{-1} \cdot \text{s}^{-3}$	V	V

\electroncurrent{\langle magnitude\rangle}

command	\electroncurrent	
base	derived	alternate
s^{-1}	e/s	e/s

\emf{\langle magnitude\rangle}

command	\emf	
base	derived	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{A}^{-1} \cdot \text{s}^{-3}$	V	V

\energy{\langle magnitude\rangle}

command	\energy	
base	derived	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2}$	J	J

N 2021-04-15

\energyinev{\langle magnitude\rangle}

command	\energyinev	
base	derived	alternate
eV	eV	eV

N 2021-04-15

\energyinkev{\langle magnitude\rangle}

command	\energyinkev	
base	derived	alternate
keV	keV	keV

N 2021-04-15

\energyinmev{\langle magnitude\rangle}

command	\energyinmev	
base	derived	alternate
MeV	MeV	MeV

\energydensity{\langle magnitude\rangle}

command	<code>\energydensity</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$	J/m^3	J/m^3

N 2021-02-24

```
\energyflux{\(magnitude)}
\energyfluxvector{\(c_1, \dots, c_n\)}
\vectorenergyflux{\(c_1, \dots, c_n\)}
```

command	<code>\energyflux</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{s}^{-3}$	W/m^2	W/m^2

```
\entropy{\(magnitude)}
```

command	<code>\entropy</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$	J/K	J/K

N 2021-02-24

```
\force{\(magnitude)}
\forcevector{\(c_1, \dots, c_n\)}
\vectorforce{\(c_1, \dots, c_n\)}
```

command	<code>\force</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m} \cdot \text{s}^{-2}$	N	N

```
\frequency{\(magnitude)}
```

command	<code>\frequency</code>	
base	<code>derived</code>	alternate
s^{-1}	Hz	Hz

N 2021-02-24

```
\gravitationalfield{\(magnitude)}
\gravitationalfieldvector{\(c_1, \dots, c_n\)}
\vectorgravitationalfield{\(c_1, \dots, c_n\)}
```

command	<code>\gravitationalfield</code>	
base	<code>derived</code>	alternate
$\text{m} \cdot \text{s}^{-2}$	N/kg	N/kg

```
\gravitationalpotential{\(magnitude)}
```

command	<code>\gravitationalpotential</code>	
base	<code>derived</code>	alternate
$\text{m}^2 \cdot \text{s}^{-2}$	J/kg	J/kg

N 2021-05-01

```
\gravitationalpotentialdifference{\(magnitude)}
```

command	<code>\gravitationalpotentialdifference</code>	
base	<code>derived</code>	alternate
$\text{m}^2 \cdot \text{s}^{-2}$	J/kg	J/kg

N 2021-02-24

```
\impulse{\langle magnitude\rangle}
\impulsevector{\langle c_1, \dots, c_n \rangle}
\vectorimpulse{\langle c_1, \dots, c_n \rangle}
```

command	<code>\impulse</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m} \cdot \text{s}^{-1}$	$\text{N} \cdot \text{s}$	$\text{N} \cdot \text{s}$

```
\indexofrefraction{\langle magnitude\rangle}
```

command	<code>\indexofrefraction</code>	
base	<code>derived</code>	alternate

```
\inductance{\langle magnitude\rangle}
```

command	<code>\inductance</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{A}^{-2} \cdot \text{s}^{-2}$	H	$\text{V} \cdot \text{s}/\text{A}$

```
\linearchargedensity{\langle magnitude\rangle}
```

command	<code>\linearchargedensity</code>	
base	<code>derived</code>	alternate
$\text{A} \cdot \text{s} \cdot \text{m}^{-1}$	C/m	C/m

```
\linearmassdensity{\langle magnitude\rangle}
```

command	<code>\linearmassdensity</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^{-1}$	kg/m	kg/m

N 2022-01-27

```
\lorentzfactor{\langle magnitude\rangle}
```

command	<code>\lorentzfactor</code>	
base	<code>derived</code>	alternate

U 2021-05-02

```
\luminousintensity{\langle magnitude\rangle}
```

command	<code>\luminousintensity</code>	
base	<code>derived</code>	alternate
cd	cd	cd

`\magneticcharge{magnitude}`

command	<code>\magneticcharge</code>	
base	<code>derived</code>	<code>alternate</code>
$A \cdot m$	$A \cdot m$	$A \cdot m$

`\magneticdipolemoment{magnitude}`

`\magneticdipolemomentvector{c1, ..., cn}`
`\vectormagneticdipolemoment{c1, ..., cn}`

command	<code>\magneticdipolemoment</code>	
base	<code>derived</code>	<code>alternate</code>
$A \cdot m^2$	$A \cdot m^2$	J/T

`\magneticfield{magnitude}`

`\magneticfieldvector{c1, ..., cn}`
`\vectormagneticfield{c1, ..., cn}`

command	<code>\magneticfield</code>	
base	<code>derived</code>	<code>alternate</code>
$kg \cdot A^{-1} \cdot s^{-2}$	$N/A \cdot m$	T

`\magneticflux{magnitude}`

command	<code>\magneticflux</code>	
base	<code>derived</code>	<code>alternate</code>
$kg \cdot m^2 \cdot A^{-1} \cdot s^{-2}$	$T \cdot m^2$	$V \cdot s$

`\mass{magnitude}`

command	<code>\mass</code>	
base	<code>derived</code>	<code>alternate</code>
kg	kg	kg

`\mobility{magnitude}`

command	<code>\mobility</code>	
base	<code>derived</code>	<code>alternate</code>
$kg \cdot m^2 \cdot A^{-1} \cdot s^{-4}$	$m^2/V \cdot s$	$C \cdot m/N \cdot s$

`\momentofinertia{magnitude}`

command	<code>\momentofinertia</code>	
base	<code>derived</code>	<code>alternate</code>
$kg \cdot m^2$	$J \cdot s^2$	$kg \cdot m^2$

N 2021-02-24

```
\momentum{\langle magnitude\rangle}
\momentumvector{\langle c_1, \dots, c_n \rangle}
\vectormomentum{\langle c_1, \dots, c_n \rangle}
```

command	<code>\momentum</code>	
base	<code>\derived</code>	
$\text{kg} \cdot \text{m} \cdot \text{s}^{-1}$	$\text{kg} \cdot \text{m/s}$	

N 2021-02-24

```
\momentumflux{\langle magnitude\rangle}
\momentumfluxvector{\langle c_1, \dots, c_n \rangle}
\vectormomentumflux{\langle c_1, \dots, c_n \rangle}
```

command	<code>\momentumflux</code>	
base	<code>\derived</code>	
$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$	N/m^2	

```
\numberdensity{\langle magnitude\rangle}
```

command	<code>\numberdensity</code>	
base	<code>\derived</code>	
m^{-3}	/m^3	

```
\permeability{\langle magnitude\rangle}
```

command	<code>\permeability</code>	
base	<code>\derived</code>	
$\text{kg} \cdot \text{m} \cdot \text{A}^{-2} \cdot \text{s}^{-2}$	H/m	

```
\permittivity{\langle magnitude\rangle}
```

command	<code>\permittivity</code>	
base	<code>\derived</code>	
$\text{A}^2 \cdot \text{s}^4 \cdot \text{kg}^{-1} \cdot \text{m}^{-3}$	F/m	

```
\planeangle{\langle magnitude\rangle}
```

command	<code>\planeangle</code>	
base	<code>\derived</code>	
$\text{m} \cdot \text{m}^{-1}$	rad	

```
\polarizability{\langle magnitude\rangle}
```

command	<code>\polarizability</code>	
base	<code>\derived</code>	
$\text{A}^2 \cdot \text{s}^4 \cdot \text{kg}^{-1}$	$\text{C} \cdot \text{m}^2/\text{V}$	

```
\power{\langle magnitude\rangle}
```

command	<code>\power</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-3}$	<code>W</code>	J/s

N 2021-02-24

```
\poynting{\langle magnitude \rangle}
\poyntingvector{\langle c_1, \dots, c_n \rangle}
\vectorpoynting{\langle c_1, \dots, c_n \rangle}
```

command	<code>\poynting</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{s}^{-3}$	<code>W/m^2</code>	W/m^2

```
\pressure{\langle magnitude \rangle}
```

command	<code>\pressure</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$	<code>Pa</code>	N/m^2

```
\relativepermeability{\langle magnitude \rangle}
```

command	<code>\relativepermeability</code>	
base	<code>derived</code>	alternate

```
\relativepermittivity{\langle magnitude \rangle}
```

command	<code>\relativepermittivity</code>	
base	<code>derived</code>	alternate

```
\resistance{\langle magnitude \rangle}
```

command	<code>\resistance</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{A}^{-2} \cdot \text{s}^{-3}$	Ω	Ω

```
\resistivity{\langle magnitude \rangle}
```

command	<code>\resistivity</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^3 \cdot \text{A}^{-2} \cdot \text{s}^{-3}$	$\Omega \cdot \text{m}$	$\text{V} \cdot \text{m/A}$

```
\solidangle{\langle magnitude \rangle}
```

command	<code>\solidangle</code>	
base	<code>derived</code>	alternate
$\text{m}^2 \cdot \text{m}^{-2}$	<code>sr</code>	sr

`\specificheatcapacity{magnitude}`

command	<code>\specificheatcapacity</code>	
base	<code>derived</code>	<code>alternate</code>
$\text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$	$\text{J/K} \cdot \text{kg}$	$\text{J/K} \cdot \text{kg}$

`\springstiffness{magnitude}`

command	<code>\springstiffness</code>	
base	<code>derived</code>	<code>alternate</code>
$\text{kg} \cdot \text{s}^{-2}$	N/m	N/m

`\springstretch{magnitude}`

command	<code>\springstretch</code>	
base	<code>derived</code>	<code>alternate</code>
m	m	m

`\stress{magnitude}`

command	<code>\stress</code>	
base	<code>derived</code>	<code>alternate</code>
$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$	Pa	N/m^2

`\strain{magnitude}`

command	<code>\strain</code>	
base	<code>derived</code>	<code>alternate</code>

`\temperature{magnitude}`

command	<code>\temperature</code>	
base	<code>derived</code>	<code>alternate</code>
K	K	K

`\torque{magnitude}`

`\torquevector{ c_1, \dots, c_n }`

`\vectortorque{ c_1, \dots, c_n }`

command	<code>\torque</code>	
base	<code>derived</code>	<code>alternate</code>
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2}$	$\text{N} \cdot \text{m}$	$\text{N} \cdot \text{m}$

`\velocity{magnitude}`

`\velocityvector{ c_1, \dots, c_n }`

`\vectorvelocity{ c_1, \dots, c_n }`

command	<code>\velocity</code>	
base	<code>derived</code>	alternate
$m \cdot s^{-1}$	m/s	m/s

`\velocityc{<magnitude>}`
`\velocityvector{<c1, ..., cn>}`
`\vectorvelocityc{<c1, ..., cn>}`

command	<code>\velocityc</code>	
base	<code>derived</code>	alternate
c	c	c

`\volume{<magnitude>}`

command	<code>\volume</code>	
base	<code>derived</code>	alternate
m^3	m^3	m^3

`\volumechargedensity{<magnitude>}`

command	<code>\volumechargedensity</code>	
base	<code>derived</code>	alternate
$A \cdot s/m^3$	C/m^3	C/m^3

`\volumemassdensity{<magnitude>}`

command	<code>\volumemassdensity</code>	
base	<code>derived</code>	alternate
$kg \cdot m^{-3}$	kg/m^3	kg/m^3

`\wavelength{<magnitude>}`

command	<code>\wavelength</code>	
base	<code>derived</code>	alternate
m	m	m

`\wavenumber{<magnitude>}`
`\wavenumbervector{<c1, ..., cn>}`
`\vectorwavenumber{<c1, ..., cn>}`

command	<code>\wavenumber</code>	
base	<code>derived</code>	alternate
m^{-1}	$/m$	$/m$

`\work{<magnitude>}`

N 2021-02-24

command	<code>\work</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-2}$	J	J

```
\youngsmodulus{\(magnitude)}
```

command	<code>\youngsmodulus</code>	
base	<code>derived</code>	alternate
$\text{kg} \cdot \text{m}^{-1} \cdot \text{s}^{-2}$	Pa	N/m^2

6.4.4 Defining and Redefining Physical Quantities

N 2021-02-16
N 2021-02-21

```
\NewScalarQuantity{\(name)}{\(base units)}[\(derived units)][\(alternate units)]
\RenewScalarQuantity{\(name)}{\(base units)}[\(derived units)][\(alternate units)]
```

Command to (re)define a new/existing scalar quantity. If the derived or alternate units are omitted, they are defined to be the same as the base units. Do not use both this command and `\NewVectorQuantity` or `\RenewVectorQuantity` to (re)define a quantity.

N 2021-02-16
N 2021-02-21

```
\NewVectorQuantity{\(name)}{\(base units)}[\(derived units)][\(alternate units)]
\RenewVectorQuantity{\(name)}{\(base units)}[\(derived units)][\(alternate units)]
```

Command to (re)define a new/existing vector quantity. If the derived or alternate units are omitted, they are defined to be the same as the base units. Do not use both this command and `\NewScalarQuantity` or `\RenewScalarQuantity` to (re)define a quantity.

6.4.5 Changing Units

Units are set when `mandi` is loaded, but the default setting can be easily overridden in four ways: command variants that are defined when a [physical quantity](#) ^{P.9} or [physical constant](#) ^{P.23} is defined, a global modal command (switch), a command that sets units for a single instance, and an environment that sets units for its duration. All of these methods work for both physical quantities and physical constants.

U 2021-02-26
U 2021-02-26
U 2021-02-26

```
\alwaysusebaseunits
\alwaysusederivedunits
\alwaysusealternateunits
```

Modal commands (switches) for setting the default unit form for the entire document. When `mandi` is loaded, one of these three commands is executed depending on whether the optional `units` key is provided. See the section on loading the package for details. Alternate units are the default because they are the most likely ones to be seen in introductory physics textbooks.

U 2021-02-26
U 2021-02-26
U 2021-02-26

```
\hereusebaseunits{\(content)}
\hereusederivedunits{\(content)}
\hereusealternateunits{\(content)}
```

Commands for setting the unit form on the fly for a single instance. The example uses momentum and the Coulomb constant, but they work for any defined quantity and constant.

\(\backslash(\backslashhereusebaseunits\{\momentum{5}\} \backslash)\) \\	$5 \text{ kg} \cdot \text{m} \cdot \text{s}^{-1}$
\(\backslash(\backslashhereusederivedunits\{\momentum{5}\} \backslash)\) \\	$5 \text{ kg} \cdot \text{m/s}$
\(\backslash(\backslashhereusealternateunits\{\momentum{5}\} \backslash)\) \\	$5 \text{ kg} \cdot \text{m/s}$
\(\backslash(\backslashhereusebaseunits\{\oofpez\} \backslash)\) \\	$9 \times 10^9 \text{ kg} \cdot \text{m}^3 \cdot \text{A}^{-2} \cdot \text{s}^{-4}$
\(\backslash(\backslashhereusederivedunits\{\oofpez\} \backslash)\) \\	$9 \times 10^9 \text{ m/F}$
\(\backslash(\backslashhereusealternateunits\{\oofpez\} \backslash)\)	$9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$

U 2021-02-26	\begin{usebaseunits} <i>(environment content)</i> \end{usebaseunits}	(use base units)
U 2021-02-26	\begin{usederivedunits} <i>(environment content)</i> \end{usederivedunits}	(use derived units)
U 2021-02-26	\begin{usealternateunits} <i>(environment content)</i> \end{usealternateunits}	(use alternate units)

Inside these environments units are changed for the duration of the environment regardless of the global default setting.

\(\backslash(\backslashmomentum{5}\) \backslash)\) \\	$5 \text{ kg} \cdot \text{m/s}$
\(\backslash(\backslashoofpez\)\) \\	$9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$
\begin{usebaseunits} \(\backslash(\backslashmomentum{5}\) \backslash)\) \\ \(\backslash(\backslashoofpez\)\) \\	$5 \text{ kg} \cdot \text{m} \cdot \text{s}^{-1}$
\end{usebaseunits}	
\begin{usederivedunits} \(\backslash(\backslashmomentum{5}\) \backslash)\) \\ \(\backslash(\backslashoofpez\)\) \\	$9 \times 10^9 \text{ kg} \cdot \text{m}^3 \cdot \text{A}^{-2} \cdot \text{s}^{-4}$
\end{usederivedunits}	
\begin{usealternateunits} \(\backslash(\backslashmomentum{5}\) \backslash)\) \\ \(\backslash(\backslashoofpez\)\) \\	$5 \text{ kg} \cdot \text{m/s}$
\end{usealternateunits}	

6.5 Physical Constants

6.5.1 Typesetting Physical Constants

Take the quantity $\frac{1}{4\pi\epsilon_0}$, sometimes called the [Coulomb constant](#), as the prototypical [physical constant](#) in an introductory physics course. Here are all the ways to access this quantity in `mandi`. As you can see, these commands are almost identical to the corresponding commands for physical quantities.

\oofpez

Command for the Coulomb constant. The constant's numerical precision and default units will depend on the options passed to `mandi` at load time. Alternate units and approximate numerical values are the defaults. Other units can be forced as demonstrated.

<code>\(\backslash oofpez\)</code>	<code>\backslash oofpez</code>	$9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$
<code>\(\backslash oofpezapproximatevalue\)</code>	<code>\backslash oofpezapproximatevalue</code>	9×10^9
<code>\(\backslash oofpezprecisevalue\)</code>	<code>\backslash oofpezprecisevalue</code>	8.9875517923×10^9
<code>\(\backslash oofpezmathsymbol\)</code>	<code>\backslash oofpezmathsymbol</code>	$\frac{1}{4\pi\epsilon_0}$
<code>\(\backslash oofpezbaseunits\)</code>	<code>\backslash oofpezbaseunits</code>	$9 \times 10^9 \text{ kg} \cdot \text{m}^3 \cdot \text{A}^{-2} \cdot \text{s}^{-4}$
<code>\(\backslash oofpezderivedunits\)</code>	<code>\backslash oofpezderivedunits</code>	$9 \times 10^9 \text{ m/F}$
<code>\(\backslash oofpezelternateunits\)</code>	<code>\backslash oofpezelternateunits</code>	$9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$
<code>\(\backslash oofpezonlybaseunits\)</code>	<code>\backslash oofpezonlybaseunits</code>	$\text{kg} \cdot \text{m}^3 \cdot \text{A}^{-2} \cdot \text{s}^{-4}$
<code>\(\backslash oofpezonlyderivedunits\)</code>	<code>\backslash oofpezonlyderivedunits</code>	m/F
<code>\(\backslash oofpezonlyelternateunits\)</code>	<code>\backslash oofpezonlyelternateunits</code>	$\text{N} \cdot \text{m}^2/\text{C}^2$

6.5.2 Checking Physical Constants

U 2022-01-27

`\CheckConstant{<name>}`

Command to check and typeset the constant's name, mathematical symbol, approximate value, precise value, base units, derived units, and alternate units.

6.5.3 Predefined Physical Constants

Every other defined physical constant can be treated similarly to `\oofpez`^{P.27}. Just replace `\oofpez` with the constant's name. Unfortunately, there is no universal agreement on the names of every constant so don't fret if the names used here vary from other sources. Here are all the physical constants, with all their units, defined in `mandi`. The constants `\coulombconstant`^{P.25} and `\biotsavartconstant` are defined as semantic aliases for, respectively, `\oofpez`^{P.27} and `\mzofp`^{P.27}.

`\avogadro`

(exact)

command	<code>\avogadro</code>	
symbol	<code>\avogadro</code>	precise
N_A	6×10^{23}	$6.02214076 \times 10^{23}$
base	<code>\derived</code>	alternate
mol^{-1}	<code>/mol</code>	<code>/mol</code>

N 2021-02-02

`\biotsavartconstant`

command	<code>\biotsavartconstant</code>	
symbol	<code>\biotsavartconstant</code>	precise
$\frac{\mu_0}{4\pi}$	10^{-7}	10^{-7}
base	<code>\derived</code>	alternate
$\text{kg} \cdot \text{m} \cdot \text{A}^{-2} \cdot \text{s}^{-2}$	<code>H/m</code>	$\text{T} \cdot \text{m/A}$

`\bohrradius`

command
symbol
 a_0
base
m

\bohradius
approximate
 5.3×10^{-11}
derived
m

precise
 $5.29177210903 \times 10^{-11}$
alternate
m

\boltzmann

(exact)

command
symbol
 k_B
base
 $kg \cdot m^2 \cdot s^{-2} \cdot K^{-1}$

\boltzmann
approximate
 1.4×10^{-23}
derived
J/K

precise
 1.380649×10^{-23}
alternate
J/K

N 2021-02-02

\coulombconstant

command
symbol
 $\frac{1}{4\pi\epsilon_0}$
base
 $kg \cdot m^3 \cdot A^{-2} \cdot s^{-4}$

\coulombconstant
approximate
 9×10^9
derived
m/F

precise
 8.9875517923×10^9
alternate
 $N \cdot m^2/C^2$

\earthmass

command
symbol
 M_{Earth}
base
kg

\earthmass
approximate
 6.0×10^{24}
derived
kg

precise
 5.9722×10^{24}
alternate
kg

\earthmoondistance

command
symbol
 d_{EM}
base
m

\earthmoondistance
approximate
 3.8×10^8
derived
m

precise
 3.81550×10^8
alternate
m

\earthradius

command
symbol
 R_{Earth}
base
m

\earthradius
approximate
 6.4×10^6
derived
m

precise
 6.3781×10^6
alternate
m

\earthsundistance

command	<code>\earthsundistance</code>	
symbol	<code>approximate</code>	precise
d_{ES}	1.5×10^{11}	1.496×10^{11}
base	<code>derived</code>	alternate
m	m	m

\electroncharge

command	<code>\electroncharge</code>	
symbol	<code>approximate</code>	precise
q_e	-1.6×10^{-19}	$-1.602176634 \times 10^{-19}$
base	<code>derived</code>	alternate
$A \cdot s$	C	C

\electronCharge

command	<code>\electronCharge</code>	
symbol	<code>approximate</code>	precise
Q_e	-1.6×10^{-19}	$-1.602176634 \times 10^{-19}$
base	<code>derived</code>	alternate
$A \cdot s$	C	C

\electronmass

command	<code>\electronmass</code>	
symbol	<code>approximate</code>	precise
m_e	9.1×10^{-31}	$9.1093837015 \times 10^{-31}$
base	<code>derived</code>	alternate
kg	kg	kg

\elementarycharge

(exact)

command	<code>\elementarycharge</code>	
symbol	<code>approximate</code>	precise
e	1.6×10^{-19}	$1.602176634 \times 10^{-19}$
base	<code>derived</code>	alternate
$A \cdot s$	C	C

\finestructure

command	<code>\finestructure</code>	
symbol	<code>approximate</code>	precise
α	$\frac{1}{137}$	$7.2973525693 \times 10^{-3}$
base	<code>derived</code>	alternate

\hydrogenmass

command	\hydrogenmass	
symbol	approximate	precise
m_H	1.7×10^{-27}	$1.6737236 \times 10^{-27}$
base	derived	alternate
kg	kg	kg

\moonearthdistance

command	\moonearthdistance	
symbol	approximate	precise
d_{ME}	3.8×10^8	3.81550×10^8
base	derived	alternate
m	m	m

\moonmass

command	\moonmass	
symbol	approximate	precise
M_{Moon}	7.3×10^{22}	7.342×10^{22}
base	derived	alternate
kg	kg	kg

\moonradius

command	\moonradius	
symbol	approximate	precise
R_{Moon}	1.7×10^6	1.7371×10^6
base	derived	alternate
m	m	m

\mzofp

command	\mzofp	
symbol	approximate	precise
$\frac{\mu_0}{4\pi}$	10^{-7}	10^{-7}
base	derived	alternate
$\text{kg} \cdot \text{m} \cdot \text{A}^{-2} \cdot \text{s}^{-2}$	H/m	$\text{T} \cdot \text{m/A}$

\neutronmass

command	\neutronmass	
symbol	approximate	precise
m_n	1.7×10^{-27}	$1.67492749804 \times 10^{-27}$
base	derived	alternate
kg	kg	kg

\oofpez

command	\oofpez	
symbol	approximate	precise
$\frac{1}{4\pi\epsilon_0}$	9×10^9	8.9875517923×10^9
base	derived	alternate
$\text{kg} \cdot \text{m}^3 \cdot \text{A}^{-2} \cdot \text{s}^{-4}$	m/F	$\text{N} \cdot \text{m}^2/\text{C}^2$

\oofpezcs

command	\oofpezcs	
symbol	approximate	precise
$\frac{1}{4\pi\epsilon_0 c^2}$	10^{-7}	10^{-7}
base	derived	alternate
$\text{kg} \cdot \text{m} \cdot \text{A}^{-2} \cdot \text{s}^{-2}$	$\text{T} \cdot \text{m}^2$	$\text{N} \cdot \text{s}^2/\text{C}^2$

\planck

(exact)

command	\planck	
symbol	approximate	precise
h	6.6×10^{-34}	$6.62607015 \times 10^{-34}$
base	derived	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-1}$	J · s	J · s

\planckbar

command	\planckbar	
symbol	approximate	precise
\hbar	1.1×10^{-34}	$1.054571817 \times 10^{-34}$
base	derived	alternate
$\text{kg} \cdot \text{m}^2 \cdot \text{s}^{-1}$	J · s	J · s

\planckc

command	\planckc	
symbol	approximate	precise
hc	2.0×10^{-25}	$1.98644586 \times 10^{-25}$
base	derived	alternate
$\text{kg} \cdot \text{m}^3 \cdot \text{s}^{-2}$	J · m	J · m

\protoncharge

command	\protoncharge	
symbol	approximate	precise
q_p	$+1.6 \times 10^{-19}$	$+1.602176634 \times 10^{-19}$
base	derived	alternate
$\text{A} \cdot \text{s}$	C	C

\protonCharge

command	\protonCharge	
symbol	approximate	
Q_p	$+1.6 \times 10^{-19}$	
base	derived	
$A \cdot s$	C	

\protonmass

command	\protonmass	
symbol	approximate	
m_p	1.7×10^{-27}	
base	derived	
kg	kg	

\rydberg

command	\rydberg	
symbol	approximate	
R_∞	1.1×10^7	
base	derived	
m^{-1}	m^{-1}	

\speedoflight

(exact)

command	\speedoflight	
symbol	approximate	
c	3×10^8	
base	derived	
$m \cdot s^{-1}$	m/s	

\stefanboltzmann

command	\stefanboltzmann	
symbol	approximate	
σ	5.7×10^{-8}	
base	derived	
$kg \cdot s^{-3} \cdot K^{-4}$	$W/m^2 \cdot K^4$	

\sunearthdistance

command	\sunearthdistance	
symbol	approximate	
d_{SE}	1.5×10^{11}	
base	derived	
m	m	

\sunradius

command	\sunradius	
symbol	approximate	precise
R_{Sun}	7.0×10^8	6.957×10^8
base	derived	alternate
m	m	m

\surfacegravfield

command	\surfacegravfield	
symbol	approximate	precise
g	9.8	9.807
base	derived	alternate
$\text{m} \cdot \text{s}^{-2}$	N/kg	N/kg

\universalgrav

command	\universalgrav	
symbol	approximate	precise
G	6.7×10^{-11}	6.67430×10^{-11}
base	derived	alternate
$\text{m}^3 \cdot \text{kg}^{-1} \cdot \text{s}^{-2}$	$\text{N} \cdot \text{m}^2/\text{kg}^2$	$\text{N} \cdot \text{m}^2/\text{kg}^2$

\vacuumpermeability

command	\vacuumpermeability	
symbol	approximate	precise
μ_0	$4\pi \times 10^{-7}$	$4\pi \times 10^{-7}$
base	derived	alternate
$\text{kg} \cdot \text{m} \cdot \text{A}^{-2} \cdot \text{s}^{-2}$	H/m	T · m/A

\vacuumpermittivity

command	\vacuumpermittivity	
symbol	approximate	precise
ϵ_0	9×10^{-12}	$8.854187817 \times 10^{-12}$
base	derived	alternate
$\text{A}^2 \cdot \text{s}^4 \cdot \text{kg}^{-1} \cdot \text{m}^{-3}$	F/m	$\text{C}^2/\text{N} \cdot \text{m}^2$

6.5.4 Defining and Redefining Physical Constants

N 2021-02-16

```
\NewPhysicalConstant {[<name>]}{[<symbol>]}{[<approximate value>]}{[<precise value>]}{[<base units>]}
[<derived units>] [<alternate units>]
```

N 2021-02-21

```
\RenewPhysicalConstant {[<name>]}{[<symbol>]}{[<approximate value>]}{[<precise value>]}{[<base units>]}
[<derived units>] [<alternate units>]
```

Command to define/redefine a new/existing physical constant. If the derived or alternate units are omitted, they are defined to be the same as the base units.

6.5.5 Changing Precision

[Changing units](#) ^{P.22} works for physical constants just as it does for physical quantities. A similar mechanism is provided for changing the precision of physical constants' numerical values.

N 2021-02-16 `\alwaysuseapproximateconstants`
N 2021-02-16 `\alwaysusepreciseconstants`

Modal commands (switches) for setting the default precision for the entire document. The default when the package is loaded is set by the presence or absence of the [preciseconstants](#) ^{P.8} key.

N 2021-02-16 `\hereuseapproximateconstants{<content>}`
N 2021-02-16 `\hereusepreciseconstants{<content>}`

Commands for setting the precision on the fly for a single instance.

<code>\(\hereuseapproximateconstants{\oofpez} \) \\</code> <code>\(\hereusepreciseconstants{\oofpez} \)</code>	$9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$ $8.9875517923 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$
---	---

N 2021-02-16 `\begin{useapproximateconstants}{<environment content>}` (use approximate constants)
`\end{useapproximateconstants}`
N 2021-02-16 `\begin{usepreciseconstants}{<environment content>}` (use precise constants)
`\end{usepreciseconstants}`

Inside these environments precision is changed for the duration of the environment regardless of the global default setting.

<code>\(\oofpez \) \\</code> <code>\begin{useapproximateconstants}{<environment content>}</code> <code>\(\oofpez \) \\</code> <code>\end{useapproximateconstants}</code> <code>\begin{usepreciseconstants}{<environment content>}</code> <code>\(\oofpez \) \\</code> <code>\end{usepreciseconstants}</code> <code>\(\oofpez \)</code>	$9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$ $9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$ $8.9875517923 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$ $9 \times 10^9 \text{ N} \cdot \text{m}^2/\text{C}^2$
---	---

6.6 Predefined Units and Constructs

These commands should be used only in defining or redefining physical quantities or physical constants. One exception is `\emptyunit`, which may be used for explanatory purposes.

U 2023-08-01 `\per`
`\usk`
`\units{<magnitude>}{<unit>}`
`\emptyunit`
`\ampere`
`\atomicmassunit`
`\candela`

N 2021-04-15	\coulomb \degree \electronvolt \ev \farad \henry \hertz \joule \kelvin \kev	(not SI but common in introductory physics) (alias)
N 2021-04-15	\kilolectronvolt \kilogram \lightspeed	(not SI but common in introductory physics)
N 2021-04-15	\megaelectronvolt \meter \metre \mev \mole \newton \ohm \pascal \radian \second \siemens \steradian \tesla \volt \watt \weber \tothetwo \tothethree \tothefour \inverse \totheinversetwo \totheinversethree \totheinversefour	(not SI but common relativity) (not SI but common in introductory physics) (alias) (alias)
N 2021-04-15		

\(\per \)	\(\frac{1}{\text{m}} \)
\(\usk \)	\(\text{m} \)
\(\units{3}{\meter\per\second} \)	\(\text{m}^3 \text{s}^{-3} \)
\(\emptyunit \)	\(\text{m}^0 \)
\(\ampere \)	\(\text{A} \)
\(\atomicmassunit \)	\(\text{u} \)
\(\candela \)	\(\text{cd} \)
\(\coulomb \)	\(\text{C} \)
\(\degree \)	\({}^\circ \)
\(\electronvolt \)	\(\text{eV} \)
\(\farad \)	\(\text{F} \)
\(\henry \)	\(\text{H} \)
\(\hertz \)	\(\text{Hz} \)
\(\joule \)	\(\text{J} \)
\(\kelvin \)	\(\text{K} \)
\(\kev \)	\(\text{keV} \)
\(\kilogram \)	\(\text{kg} \)
\(\lightspeed \)	\(\text{c} \)
\(\meter \)	\(\text{m} \)
\(\metre \)	\(\text{m} \)
\(\mev \)	\(\text{MeV} \)
\(\mole \)	\(\text{mol} \)
\(\newton \)	\(\text{N} \)
\(\ohm \)	\(\Omega \)
\(\pascal \)	\(\text{Pa} \)
\(\radian \)	\(\text{rad} \)
\(\second \)	\(\text{s} \)
\(\siemens \)	\(\text{S} \)
\(\steradian \)	\(\text{sr} \)
\(\tesla \)	\(\text{T} \)
\(\volt \)	\(\text{V} \)
\(\watt \)	\(\text{W} \)
\(\weber \)	\(\text{Wb} \)
\(\emptyunit{\tothetwo} \)	\(\text{□}^2 \)
\(\emptyunit{\tothethree} \)	\(\text{□}^3 \)
\(\emptyunit{\tothefour} \)	\(\text{□}^4 \)
\(\emptyunit{\inverse} \)	\(\text{□}^{-1} \)
\(\emptyunit{\totheinversetwo} \)	\(\text{□}^{-2} \)
\(\emptyunit{\totheinversethree} \)	\(\text{□}^{-3} \)
\(\emptyunit{\totheinversefour} \)	\(\text{□}^{-4} \)

N 2022-01-27

\hbar

A better glyph for Planck's constant over 2π .

```
\(\ \hbar \)
```

\hbar

```
\tent{<number>}  
\timestent{<number>}  
\xtent{<number>}
```

Commands for powers of ten and scientific notation.

```
\( \tent{-4} \) \\  
\( 3\timestent{8} \) \\  
\( 3\xtent{8} \)
```

10^{-4}
 3×10^8
 3×10^8

U 2022-01-27 **\mivector** [*delimiter*] {*c₁, ..., c_n*} [*units*]

Typesets a vector as either numeric or symbolic components with an optional unit (for numerical components only). There must be more than one component, and there can be more than three components. The delimiter used in the list of components can be specified; the default is a comma. The notation mirrors that of *Matter & Interactions*.

<pre>\(\mivector{p_0,p_1,p_2,p_3} \)</pre>	2	$\langle p_0, p_1, p_2, p_3 \rangle$
<pre>\(\mivector{\gamma mc,\gamma mv_x,\gamma mv_y,\gamma mv_z} \)</pre>	2	$\langle \gamma mc, \gamma mv_x, \gamma mv_y, \gamma mv_z \rangle$
<pre>\(\mivector{\frac{Q_1 Q_2}{x^2},0,0} \)</pre>	2	$\left\langle \frac{Q_1 Q_2}{x^2}, 0, 0 \right\rangle$
<pre>\(\mivector{-1,0,0} \)</pre>	2	$\langle -1, 0, 0 \rangle$
<pre>\(\mivector{-1,0,0}[\velocityonlyderivedunits] \)</pre>	2	$\langle -1, 0, 0 \rangle \text{ m/s}$
<pre>\(\mivector{-1,0,0}[\meter\per\second] \)</pre>	2	$\langle -1, 0, 0 \rangle \text{ m/s}$
<pre>\(\velocity{\mivector{-1,0,0}} \)</pre>		

6.7 **mandi** Source Code

Define the package version and date for global use, exploiting the fact that in a .sty file there is now no need for `\makeatletter` and `\makeatother`. This simplifies defining internal commands (with @ in the name) that are not for the user to know about.

```
1 \def\mandi@version{3.2.2}
2 \def\mandi@date{2024-02-27}
3 \NeedsTeXFormat{LaTeX2e}[2020-02-02]
4 \DeclareRelease{v3.2.2}{2024-02-27}{mandi.sty}
5 \DeclareCurrentRelease{v\mandi@version}{\mandi@date}
6 \ProvidesPackage{mandi}
7   [\mandi@date\space v\mandi@version\space Macros for physical quantities]
```

Define a convenient package version command.

```
8 \newcommand*{\mandiversion}{v\mandi@version\space dated \mandi@date}
```

Load third party packages, documenting why each one is needed.

We need pgfplots for a key-value interface.

```
9 \RequirePackage{pgfplots}
```

We need array for \chkquantity and \chkconstant.

```
10 \RequirePackage{array}
```

We need iftex so we can require Lua^AT_EX.

```
11 \RequirePackage{iftex}
```

We need mathtools for intelligent delimiters.

```
12 \RequirePackage{mathtools}
```

We need unicode-math for Unicode support and changing fonts.

```
13 \RequirePackage{unicode-math}
```

Suppress some annoying warnings.

```
14 \unimathsetup{warnings-off={mathtools-colon,mathtools-overbracket}}
```

Load xparse if necessary.

```
15 \IfFormatAtLeastTF{2020-10-01}
```

```
16   {}%
```

```
17   {\RequirePackage{xparse}}%
```

We require the Lua^AT_EX engine.

```
18 \RequireLuaTeX
```

Parts of the unit engine have been rewritten with `xparse` for both clarity and power. Note that `xparse` is now part of the L^AT_EX 2_ε kernel. Other parts have been rewritten in `expl` with a look to the future.

Define some generic internal selectors.

```
19 \newcommand*{\mandi@selectunits}{}%
```

```
20 \newcommand*{\mandi@selectprecision}{}%
```

Define some specific internal selectors. The first two are really just workalikes for `\@firstoftwo` and `\@secondoftwo`. The third, fourth, and fifth are `\@firstofthree`, `\@secondofthree`, and `\@thirdofthree` and apparently do not yet exist.

```
21 \newcommand*{\mandi@selectapproximate}[2]{#1}
```

```
22 \newcommand*{\mandi@selectprecise}[2]{#2}
```

```
23 \newcommand*{\mandi@selectbaseunits}[3]{#1}
```

```
24 \newcommand*{\mandi@selectderivedunits}[3]{#2}
```

```
25 \newcommand*{\mandi@selectalternateunits}[3]{#3}
```

Document level global switches.

```
26 \NewDocumentCommand{\alwaysusebaseunits}{}%
27   {\renewcommand*{\mandi@selectunits}{\mandi@selectbaseunits}}%
28 \NewDocumentCommand{\alwaysusederivedunits}{}%
29   {\renewcommand*{\mandi@selectunits}{\mandi@selectderivedunits}}%
30 \NewDocumentCommand{\alwaysusealternateunits}{}%
31   {\renewcommand*{\mandi@selectunits}{\mandi@selectalternateunits}}%
32 \NewDocumentCommand{\alwaysuseapproximateconstants}{}%
33   {\renewcommand*{\mandi@selectprecision}{\mandi@selectapproximate}}%
34 \NewDocumentCommand{\alwaysusepreciseconstants}{}%
35   {\renewcommand*{\mandi@selectprecision}{\mandi@selectprecise}}%
```

Document level localized variants.

```
36 \NewDocumentCommand{\hereusebaseunits}{ m }{\begingroup\alwaysusebaseunits#1\endgroup}%
37 \NewDocumentCommand{\hereusederivedunits}{ m }{\begingroup\alwaysusederivedunits#1\endgroup}%
38 \NewDocumentCommand{\hereusealternateunits}{ m }{\begingroup\alwaysusealternateunits#1\endgroup}%
39 \NewDocumentCommand{\hereuseapproximateconstants}{ m }{\begingroup\alwaysuseapproximateconstants#1\endgroup}%
40 \NewDocumentCommand{\hereusepreciseconstants}{ m }{\begingroup\alwaysusepreciseconstants#1\endgroup}%
```

Document level environments.

```
41 \NewDocumentEnvironment{usebaseunits}{}{\alwaysusebaseunits}{}%
42 \NewDocumentEnvironment{usederivedunits}{}{\alwaysusederivedunits}{}%
43 \NewDocumentEnvironment{usealternateunits}{}{\alwaysusealternateunits}{}%
44 \NewDocumentEnvironment{useapproximateconstants}{}{\alwaysuseapproximateconstants}{}%
45 \NewDocumentEnvironment{usepreciseconstants}{}{\alwaysusepreciseconstants}{}%
```

mandi now has a key-value interface, implemented with `pgfkeys` and `pgfkeys`. There are two options:

`units`^{→P.8}, with values `base`, `derived`, or `alternate` selects the default form of units
`preciseconstants`^{→P.8}, with values `true` and `false`, selects precise numerical values for constants rather than approximate values.

First, define the keys. The key handlers require certain commands defined by the unit engine.

```
46 \newif\ifusingpreciseconstants
47 \pgfkeys{%
48   /mandi/options/.cd,
49   initial@setup/.style={%
50     /mandi/options/buffered@units/.initial=alternate,%
51   },%
52   initial@setup,%
53   preciseconstants/.is if=usingpreciseconstants,%
54   units/.is choice,%
55   units/.default=derived,%
56   units/alternate/.style={/mandi/options/buffered@units=alternate},%
57   units/base/.style={/mandi/options/buffered@units=base},%
58   units/derived/.style={/mandi/options/buffered@units=derived},%
59   .unknown/.code={%
60     \typeout{}%
61     \typeout{mandi: You used unknown option '\pgfkeyscurrentname'.}%
62   },%
63 }%
```

Process the options.

```
64 \ProcessPgfPackageOptions{/mandi/options}
```

Write a banner to the console showing the options in use.

```
65 \typeout{}%
66 \typeout{mandi: You are using mandi \mandiversion.}%
67 \typeout{mandi: This package requires LuaLaTeX.}%
68 \typeout{mandi: Loadtime options...}
```

Complete the banner by showing currently selected options. The value of the `units`^{P.8} key is used in situ to set the default units.

```
69 \newcommand*{\mandi@do@setup}{%
70   \csname alwaysuse\pgfkeysvalueof{/mandi/options/buffered@units}units\endcsname%
71   \typeout{mandi: You will get \pgfkeysvalueof{/mandi/options/buffered@units}\space units.}%
72   \ifusingpreciseconstants
73     \alwaysusepreciseconstants
74     \typeout{mandi: You will get precise constants.}%
75   \else
76     \alwaysuseapproximateconstants
77     \typeout{mandi: You will get approximate constants.}%
78   \fi
79   \typeout{}%
80 }%
81 \mandi@do@setup
```

Define a setup command that overrides the loadtime options when called with new options. A new banner is written to the console.

```

82 \NewDocumentCommand{\mandisetup}{ m }%
83   {%
84     \IfValueT{#1}{%
85       {%
86         \pgfqkeys{/mandi/options}{#1}%
87         \typeout{}%
88         \typeout{mandi: mandisetup options...}%
89         \mandi@do@setup
90       }%
91     }%

```

Define units and related constructs to be used with the unit engine. All single letter macros are now gone. We basically absorbed and adapted the now outdated `Slunits` package. We make use of `\symp{...}` from the `unicode-math` package.

```

92 \NewDocumentCommand{\per}{\cdot}{\cdot}{/}
93 \NewDocumentCommand{\usk}{\cdot}{\cdot}{\cdotp}
94 \NewDocumentCommand{\units}{m m}%
95 {%
96   \IfValueTF{#2}%
97   {%
98     {#1}\cdot{#2}%
99   }%
100  {%
101    {#1}\cdot{}%
102  }%
103 }%
104 \NewDocumentCommand{\ampere}{}{\symup{A}}%
105 \NewDocumentCommand{\atomicmassunit}{}{\symup{u}}%
106 \NewDocumentCommand{\candela}{}{\symup{cd}}%
107 \NewDocumentCommand{\coulomb}{}{\symup{C}}%
108 \NewDocumentCommand{\degree}{\cdot}{\cdot^{\circ}}%
109 \NewDocumentCommand{\electronvolt}{}{\symup{eV}}%
110 \NewDocumentCommand{\ev}{\cdot}{\cdot}{\electronvolt}%
111 \NewDocumentCommand{\farad}{}{\symup{F}}%
112 \NewDocumentCommand{\henry}{}{\symup{H}}%
113 \NewDocumentCommand{\hertz}{}{\symup{Hz}}%
114 \NewDocumentCommand{\joule}{}{\symup{J}}%
115 \NewDocumentCommand{\kelvin}{}{\symup{K}}%
116 \NewDocumentCommand{\kev}{\cdot}{\cdot}{\kilolectronvolt}%
117 \NewDocumentCommand{\kiloelectronvolt}{}{\symup{keV}}%
118 \NewDocumentCommand{\kilogram}{}{\symup{kg}}%

```

```

119 \NewDocumentCommand{\lightspeed}{}{\!\!`symup{c}}
120 \NewDocumentCommand{\megaelectronvolt}{}{\symup{MeV}}
121 \NewDocumentCommand{\meter}{}{\symup{m}}
122 \NewDocumentCommand{\metre}{}{\meter}
123 \NewDocumentCommand{\mev}{}{\megaelectronvolt}
124 \NewDocumentCommand{\mole}{}{\symup{mol}}
125 \NewDocumentCommand{\newton}{}{\symup{N}}
126 \NewDocumentCommand{\ohm}{}{\symup{\Omega}}
127 \NewDocumentCommand{\pascal}{}{\symup{Pa}}
128 \NewDocumentCommand{\radian}{}{\symup{rad}}
129 \NewDocumentCommand{\second}{}{\symup{s}}
130 \NewDocumentCommand{\siemens}{}{\symup{S}}
131 \NewDocumentCommand{\steradian}{}{\symup{sr}}
132 \NewDocumentCommand{\tesla}{}{\symup{T}}
133 \NewDocumentCommand{\volt}{}{\symup{V}}
134 \NewDocumentCommand{\watt}{}{\symup{W}}
135 \NewDocumentCommand{\weber}{}{\symup{Wb}}
136 \NewDocumentCommand{\tothetwo}{}{\^2}
137 \NewDocumentCommand{\tothethree}{}{\^3}
138 \NewDocumentCommand{\tothefour}{}{\^4}
139 \NewDocumentCommand{\inverse}{}{\^{-1}}
140 \NewDocumentCommand{\totheinversetwo}{}{\^{-2}}
141 \NewDocumentCommand{\totheinversethree}{}{\^{-3}}
142 \NewDocumentCommand{\totheinversefour}{}{\^{-4}}
143 \NewDocumentCommand{\emptyunit}{}{\mdlgwhtsquare}
144 \NewDocumentCommand{\tento}{m}{10^{#1}}
145 \NewDocumentCommand{\timestento}{m}{\times\tento{#1}}
146 \NewDocumentCommand{\xtento}{m}{\times\tento{#1}}

147 \ExplSyntaxOn
148 \cs_new:Npn \__mandi_newscalarquantity:nnnn #1#2#3#4
149 {
150     \cs_new:cpx {#1} ##1 {\units{##1}{\mandi@selectunits{#2}{#3}{#4}}}
151     \cs_new:cpx {#1value} ##1 {##1}
152     \cs_new:cpx {#1baseunits} ##1 {\units{##1}{\mandi@selectbaseunits{#2}{#3}{#4}}}
153     \cs_new:cpx {#1derivedunits} ##1 {\units{##1}{\mandi@selectderivedunits{#2}{#3}{#4}}}
154     \cs_new:cpx {#1alternateunits} ##1 {\units{##1}{\mandi@selectalternateunits{#2}{#3}{#4}}}
155     \cs_new:cpx {#1onlybaseunits} {\mandi@selectbaseunits{#2}{#3}{#4}}
156     \cs_new:cpx {#1onlyderivedunits} {\mandi@selectderivedunits{#2}{#3}{#4}}
157     \cs_new:cpx {#1onlyalternateunits} {\mandi@selectalternateunits{#2}{#3}{#4}}
158 }
159 \NewDocumentCommand{\NewScalarQuantity}{m m O{#2} O{#2} }
160 {
161     \__mandi_newscalarquantity:nnnn { #1 }{ #2 }{ #3 }{ #4 }
162 }

```

Redefining an existing scalar quantity.

```

163 \cs_new:Npn \__mandi_renewsalarquantity:nnnn #1#2#3#4
164 {
165     \cs_set:cpx {#1} ##1 {\units{##1}{\mandi@selectunits{#2}{#3}{#4}}}
166     \cs_set:cpx {#1value} ##1 {##1}
167     \cs_set:cpx {#1baseunits} ##1 {\units{##1}{\mandi@selectbaseunits{#2}{#3}{#4}}}
168     \cs_set:cpx {#1derivedunits} ##1 {\units{##1}{\mandi@selectderivedunits{#2}{#3}{#4}}}
169     \cs_set:cpx {#1alternateunits} ##1 {\units{##1}{\mandi@selectalternateunits{#2}{#3}{#4}}}
170     \cs_set:cpx {#1onlybaseunits} {\mandi@selectbaseunits{#2}{#3}{#4}}
171     \cs_set:cpx {#1onlyderivedunits} {\mandi@selectderivedunits{#2}{#3}{#4}}
172     \cs_set:cpx {#1onlyalternateunits} {\mandi@selectalternateunits{#2}{#3}{#4}}
173 }
174 \NewDocumentCommand{\RenewScalarQuantity}{m m O{#2} O{#2} }
175 {

```

```

176     \__mandi_renewsalarquantity:nnnn { #1 }{ #2 }{ #3 }{ #4 }
177 }

Defining a new vector quantity. Note that a corresponding scalar is also defined.

178 \cs_new:Npn \__mandi_newvectorquantity:nnnn #1#2#3#4
179 {
180     \__mandi_newscalarquantity:nnnn { #1 }{ #2 }{ #3 }{ #4 }
181     \cs_new:cpx {vector#1} ##1 {\units{\mivector{##1}}{\mandi@selectunits{#2}{#3}{#4}}}
182     \cs_new:cpx {#1vector} ##1 {\units{\mivector{##1}}{\mandi@selectunits{#2}{#3}{#4}}}
183     \cs_new:cpx {vector#1value} ##1 {\mivector{##1}}
184     \cs_new:cpx {#1vectorvalue} ##1 {\mivector{##1}}
185     \cs_new:cpx {vector#1baseunits} ##1 {\units{\mivector{##1}}{\mandi@selectbaseunits{#2}{#3}{#4}}}
186     \cs_new:cpx {#1vectorbaseunits} ##1 {\units{\mivector{##1}}{\mandi@selectbaseunits{#2}{#3}{#4}}}
187     \cs_new:cpx {vector#1derivedunits} ##1 {\units{\mivector{##1}}{\mandi@selectderivedunits{#2}{#3}{#4}}}
188     \cs_new:cpx {#1vectorderivedunits} ##1 {\units{\mivector{##1}}{\mandi@selectderivedunits{#2}{#3}{#4}}}
189     \cs_new:cpx {vector#1alternateunits} ##1 {\units{\mivector{##1}}{\mandi@selectalternateunits{#2}{#3}{#4}}}
190     \cs_new:cpx {#1vectoralternateunits} ##1 {\units{\mivector{##1}}{\mandi@selectalternateunits{#2}{#3}{#4}}}
191     \cs_new:cpx {vector#1onlybaseunits} {\mandi@selectbaseunits{#2}{#3}{#4}}
192     \cs_new:cpx {#1vectoronlybaseunits} {\mandi@selectbaseunits{#2}{#3}{#4}}
193     \cs_new:cpx {vector#1onlyderivedunits} {\mandi@selectderivedunits{#2}{#3}{#4}}
194     \cs_new:cpx {#1vectoronlyderivedunits} {\mandi@selectderivedunits{#2}{#3}{#4}}
195     \cs_new:cpx {vector#1onlyalternateunits} {\mandi@selectalternateunits{#2}{#3}{#4}}
196     \cs_new:cpx {#1vectoronlyalternateunits} {\mandi@selectalternateunits{#2}{#3}{#4}}
197 }
198 \NewDocumentCommand{\NewVectorQuantity}{ m m 0{#2} 0{#2} }
199 {
200     \__mandi_newvectorquantity:nnnn { #1 }{ #2 }{ #3 }{ #4 }
201 }

```

Redefining an existing vector quantity. Note that a corresponding scalar is also redefined.

```

202 \cs_new:Npn \__mandi_renewvectorquantity:nnnn #1#2#3#4
203 {
204     \__mandi_renewsalarquantity:nnnn { #1 }{ #2 }{ #3 }{ #4 }
205     \cs_set:cpx {vector#1} ##1 {\units{\mivector{##1}}{\mandi@selectunits{#2}{#3}{#4}}}
206     \cs_set:cpx {#1vector} ##1 {\units{\mivector{##1}}{\mandi@selectunits{#2}{#3}{#4}}}
207     \cs_set:cpx {vector#1value} ##1 {\mivector{##1}}
208     \cs_set:cpx {#1vectorvalue} ##1 {\mivector{##1}}
209     \cs_set:cpx {vector#1baseunits} ##1 {\units{\mivector{##1}}{\mandi@selectbaseunits{#2}{#3}{#4}}}
210     \cs_set:cpx {#1vectorbaseunits} ##1 {\units{\mivector{##1}}{\mandi@selectbaseunits{#2}{#3}{#4}}}
211     \cs_set:cpx {vector#1derivedunits} ##1 {\units{\mivector{##1}}{\mandi@selectderivedunits{#2}{#3}{#4}}}
212     \cs_set:cpx {#1vectorderivedunits} ##1 {\units{\mivector{##1}}{\mandi@selectderivedunits{#2}{#3}{#4}}}
213     \cs_set:cpx {vector#1alternateunits} ##1 {\units{\mivector{##1}}{\mandi@selectalternateunits{#2}{#3}{#4}}}
214     \cs_set:cpx {#1vectoralternateunits} ##1 {\units{\mivector{##1}}{\mandi@selectalternateunits{#2}{#3}{#4}}}
215     \cs_set:cpx {vector#1onlybaseunits} {\mandi@selectbaseunits{#2}{#3}{#4}}
216     \cs_set:cpx {#1vectoronlybaseunits} {\mandi@selectbaseunits{#2}{#3}{#4}}
217     \cs_set:cpx {vector#1onlyderivedunits} {\mandi@selectderivedunits{#2}{#3}{#4}}
218     \cs_set:cpx {#1vectoronlyderivedunits} {\mandi@selectderivedunits{#2}{#3}{#4}}
219     \cs_set:cpx {vector#1onlyalternateunits} {\mandi@selectalternateunits{#2}{#3}{#4}}
220     \cs_set:cpx {#1vectoronlyalternateunits} {\mandi@selectalternateunits{#2}{#3}{#4}}
221 }
222 \NewDocumentCommand{\RenewVectorQuantity}{ m m 0{#2} 0{#2} }
223 {
224     \__mandi_renewvectorquantity:nnnn { #1 }{ #2 }{ #3 }{ #4 }
225 }

```

Defining a new physical constant.

```

226 \cs_new:Npn \__mandi_newphysicalconstant:nnnnnnn #1#2#3#4#5#6#7
227 {
228     \cs_new:cpx {#1} {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectunits{#5}{#6}{#7}}}

```

```

229 \cs_new:cpn {\#1mathsymbol} {#2}
230 \cs_new:cpn {\#1approximatevalue} {#3}
231 \cs_new:cpn {\#1precisevalue} {#4}
232 \cs_new:cpn {\#1baseunits}
233   {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectbaseunits{#5}{#6}{#7}}}
234 \cs_new:cpn {\#1derivedunits}
235   {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectderivedunits{#5}{#6}{#7}}}
236 \cs_new:cpn {\#1alternateunits}
237   {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectalternateunits{#5}{#6}{#7}}}
238 \cs_new:cpn {\#1onlybaseunits} {\mandi@selectbaseunits{#5}{#6}{#7}}
239 \cs_new:cpn {\#1onlyderivedunits} {\mandi@selectderivedunits{#5}{#6}{#7}}
240 \cs_new:cpn {\#1onlyalternateunits} {\mandi@selectalternateunits{#5}{#6}{#7}}
241 }
242 \NewDocumentCommand{\NewPhysicalConstant}{ m m m m m 0{#5} 0{#5} }
243 {
244   \__mandi_newphysicalconstant:nnnnnnn { #1 }{ #2 }{ #3 }{ #4 }{ #5 }{ #6 }{ #7 }
245 }

```

Redefining an existing physical constant.

```

246 \cs_new:Npn \__mandi_renewphysicalconstant:nnnnnnn #1#2#3#4#5#6#7
247 {
248   \cs_set:cpn {\#1} {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectunits{#5}{#6}{#7}}}
249   \cs_set:cpn {\#1mathsymbol} {#2}
250   \cs_set:cpn {\#1approximatevalue} {#3}
251   \cs_set:cpn {\#1precisevalue} {#4}
252   \cs_set:cpn {\#1baseunits}
253     {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectbaseunits{#5}{#6}{#7}}}
254   \cs_set:cpn {\#1derivedunits}
255     {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectderivedunits{#5}{#6}{#7}}}
256   \cs_set:cpn {\#1alternateunits}
257     {\units{\mandi@selectprecision{#3}{#4}}{\mandi@selectalternateunits{#5}{#6}{#7}}}
258   \cs_set:cpn {\#1onlybaseunits} {\mandi@selectbaseunits{#5}{#6}{#7}}
259   \cs_set:cpn {\#1onlyderivedunits} {\mandi@selectderivedunits{#5}{#6}{#7}}
260   \cs_set:cpn {\#1onlyalternateunits} {\mandi@selectalternateunits{#5}{#6}{#7}}
261 }
262 \NewDocumentCommand{\RenewPhysicalConstant}{ m m m m m 0{#5} 0{#5} }
263 {
264   \__mandi_renewphysicalconstant:nnnnnnn { #1 }{ #2 }{ #3 }{ #4 }{ #5 }{ #6 }{ #7 }
265 }
266 \ExplSyntaxOff

```

Define every quantity we need in introductory physics, alphabetically for convenience. This is really the core feature of `mandi` that no other package offers. There are commands for quantities that have no dimensions or units, and these quantities are defined for semantic completeness.

```

267 \NewVectorQuantity{acceleration}%
268   {\meter\usk\second\totheinversetwo}%
269   [\newton\per\kilogram]%
270   [\meter\per\second\tothetwo]%
271 \NewScalarQuantity{amount}%
272   {\mole}%
273 \NewVectorQuantity{angularacceleration}%
274   {\radian\usk\second\totheinversetwo}%
275   [\radian\per\second\tothetwo]%
276   [\radian\per\second\tothetwo]%
277 \NewScalarQuantity{angularfrequency}%
278   {\radian\usk\second\inverse}%
279   [\radian\per\second]%
280   [\radian\per\second]%

```

Angular impulse may also be `\newton\usk\meter\usk\second` or `\joule\usk\second`.

```
281 \NewVectorQuantity{angularimpulse}%
282   {\kilogram\usk\meter\tothetwo\usk\second\inverse}%
283   [\kilogram\usk\meter\tothetwo\per\second]%
284   [\kilogram\usk\meter\tothetwo\per\second]%
```

Angular momentum may also be `\joule\usk\second` or `\newton\usk\meter\usk\second`.

```
285 \NewVectorQuantity{angularmomentum}%
286   {\kilogram\usk\meter\tothetwo\usk\second\inverse}%
287   [\kilogram\usk\meter\tothetwo\per\second]%
288   [\kilogram\usk\meter\tothetwo\per\second]%

289 \NewVectorQuantity{angularvelocity}%
290   {\radian\usk\second\inverse}%
291   [\radian\per\second]%
292   [\radian\per\second]%
293 \NewScalarQuantity{area}%
294   {\meter\tothetwo}%
295 \NewScalarQuantity{areachargedensity}%
296   {\ampere\usk\second\usk\meter\totheinversetwo}%
297   [\coulomb\per\meter\tothetwo]%
298   [\coulomb\per\meter\tothetwo]%
299 \NewScalarQuantity{areamassdensity}%
300   {\kilogram\usk\meter\totheinversetwo}%
301   [\kilogram\per\meter\tothetwo]%
302   [\kilogram\per\meter\tothetwo]%
```

Capacitance may also be `\coulomb\tothetwo\per\newton\usk\meter` or `\second\per\ohm`.

```
303 \NewScalarQuantity{capacitance}%
304   {\ampere\tothetwo\usk\second\tothefour\usk\kilogram\inverse\usk\meter\totheinversetwo}%
305   [\farad]%
306   [\coulomb\per\volt]%
```

Charge may also be `\farad\usk\volt`.

```
307 \NewScalarQuantity{charge}%
308   {\ampere\usk\second}%
309   [\coulomb]%
310   [\coulomb]%
```

Magnetic field times c may also be `\volt\per\meter`.

```
311 \NewVectorQuantity{cmagneticfield}%
312   {\kilogram\usk\meter\usk\ampere\inverse\usk\second\totheinversethree}%
313   [\newton\per\coulomb]%
314   [\newton\per\coulomb]%

315 \NewScalarQuantity{conductance}%
316   {\ampere\tothetwo\usk\second\tothethree\usk\kilogram\inverse\usk\meter\totheinversetwo}%
317   [\siemens]%
318   [\ampere\per\volt]%
319 \NewScalarQuantity{conductivity}%
320   {\ampere\tothetwo\usk\second\tothethree\usk\kilogram\inverse\usk\meter\totheinversethree}%
321   [\siemens\per\meter]%
322   [\ampere\per\volt\usk\meter]%
323 \NewScalarQuantity{conventionalcurrent}%
324   {\ampere}%
325   [\coulomb\per\second]%
326   [\ampere]%
327 \NewScalarQuantity{current}%
328   {\ampere}%
329 \NewScalarQuantity{currentdensity}%

```

```

330  {\ampere\usk\meter\totheinversetwo}%
331  [\coulomb\per\second\usk\meter\tothetwo]%
332  [\ampere\per\meter\tothetwo]%
333 \NewScalarQuantity{dielectricconstant}%
334  {}%
335 \NewVectorQuantity{direction}%
336  {}%
337 \NewVectorQuantity{displacement}%
338  {\meter}%
339 \NewScalarQuantity{duration}%
340  {\second}%
341 \NewVectorQuantity{electricdipolemoment}%
342  {\ampere\usk\second\usk\meter}%
343  [\coulomb\usk\meter]%
344  [\coulomb\usk\meter]%
345 \NewVectorQuantity{electricfield}%
346  {\kilogram\usk\meter\usk\ampere\inverse\usk\second\totheinversethree}%
347  [\volt\per\meter]%
348  [\newton\per\coulomb]%
349 \NewScalarQuantity{electricflux}%
350  {\kilogram\usk\meter\tothethree\usk\ampere\inverse\usk\second\totheinversethree}%
351  [\volt\usk\meter]%
352  [\newton\usk\meter\tothetwo\per\coulomb]%

```

Electric potential, electric potential difference, and emf may also be $\text{joule}\per\text{coulomb}$.

```

353 \NewScalarQuantity{electricpotential}%
354  {\kilogram\usk\meter\tothetwo\usk\ampere\inverse\usk\second\totheinversethree}%
355  [\volt]%
356  [\volt]%
357 \NewScalarQuantity{electricpotentialdifference}%
358  {\kilogram\usk\meter\tothetwo\usk\ampere\inverse\usk\second\totheinversethree}%
359  [\volt]%
360  [\volt]%
361 \NewScalarQuantity{electroncurrent}%
362  {\second\inverse}%
363  [\ensuremath{\text{e}}\per\second]%
364  [\ensuremath{\text{e}}\per\second]%
365 \NewScalarQuantity{emf}%
366  {\kilogram\usk\meter\tothetwo\usk\ampere\inverse\usk\second\totheinversethree}%
367  [\volt]%
368  [\volt]%

```

Energy may also be $\text{newton}\text{usk}\text{meter}$.

```

369 \NewScalarQuantity{energy}%
370  {\kilogram\usk\meter\tothetwo\usk\second\totheinversetwo}%
371  [\joule]%
372  [\joule]%
373 \NewScalarQuantity{energyinev}%
374  {\electronvolt}%
375 \NewScalarQuantity{energyinkev}%
376  {\kilolectronvolt}%
377 \NewScalarQuantity{energyinmev}%
378  {\megaelectronvolt}%
379 \NewScalarQuantity{energydensity}%
380  {\kilogram\usk\meter\inverse\usk\second\totheinversetwo}%
381  [\joule\per\meter\tothethree]%
382  [\joule\per\meter\tothethree]%
383 \NewScalarQuantity{energyflux}%

```

```

384   {\kilogram\usk\second\totheinversethree}%
385   [\watt\per\meter\tothetwo]%
386   [\watt\per\meter\tothetwo]%
387 \NewScalarQuantity{entropy}%
388   {\kilogram\usk\meter\tothetwo\usk\second\totheinversetwo\usk\kelvin\inverse}%
389   [\joule\per\kelvin]%
390   [\joule\per\kelvin]%

```

Force may also be $\text{kilogram}\text{usk}\text{meter}\text{per}\text{second}\text{tothetwo}$.

```

391 \NewVectorQuantity{force}%
392   {\kilogram\usk\meter\usk\second\totheinversetwo}%
393   [\newton]%
394   [\newton]%

395 \NewScalarQuantity{frequency}%
396   {\second\inverse}%
397   [\hertz]%
398   [\hertz]%
399 \NewVectorQuantity{gravitationalfield}%
400   {\meter\usk\second\totheinversetwo}%
401   [\newton\per\kilogram]%
402   [\newton\per\kilogram]%
403 \NewScalarQuantity{gravitationalpotential}%
404   {\meter\tothetwo\usk\second\totheinversetwo}%
405   [\joule\per\kilogram]%
406   [\joule\per\kilogram]%
407 \NewScalarQuantity{gravitationalpotentialdifference}%
408   {\meter\tothetwo\usk\second\totheinversetwo}%
409   [\joule\per\kilogram]%
410   [\joule\per\kilogram]%
411 \NewVectorQuantity{impulse}%
412   {\kilogram\usk\meter\usk\second\inverse}%
413   [\newton\usk\second]%
414   [\newton\usk\second]%
415 \NewScalarQuantity{indexofrefraction}%
416   {}%

```

Inductance may also be $\text{square}\text{meter}\text{usk}\text{kilogram}\text{per}\text{coulomb}\text{tothetwo}$ or $\text{Wb}\text{per}\text{ampere}$.

```

417 \NewScalarQuantity{inductance}%
418   {\kilogram\usk\meter\tothetwo\usk\ampere\totheinversetwo\usk\second\totheinversetwo}%
419   [\henry]%
420   [\volt\usk\second\per\ampere]%

421 \NewScalarQuantity{linearchargedensity}%
422   {\ampere\usk\second\usk\meter\inverse}%
423   [\coulomb\per\meter]%
424   [\coulomb\per\meter]%
425 \NewScalarQuantity{linearmassdensity}%
426   {\kilogram\usk\meter\inverse}%
427   [\kilogram\per\meter]%
428   [\kilogram\per\meter]%

429 \NewScalarQuantity{lorentzfactor}%
430   {}%
431 \NewScalarQuantity{luminousintensity}%
432   {\candela}%

```

There is another convention for magnetic charge, so be careful.

```

433 \NewScalarQuantity{magneticcharge}%
434   {\ampere\usk\meter}%

```

```

435 \NewVectorQuantity{magneticdipolemoment}%
436   {\ampere\usk\meter\tothetwo}%
437   [\ampere\usk\meter\tothetwo]%
438   [\joule\per\tesla]%

Magnetic field may also be \Wb\per\meter\tothetwo.

439 \NewVectorQuantity{magneticfield}%
440   {\kilogram\usk\ampere\inverse\usk\second\totheinversetwo}%
441   [\newton\per\ampere\usk\meter]%
442   [\tesla]%

Magnetic flux may also be \Wb or \joule\per\ampere.

443 \NewScalarQuantity{magneticflux}%
444   {\kilogram\usk\meter\tothetwo\usk\ampere\inverse\usk\second\totheinversetwo}%
445   [\tesla\usk\meter\tothetwo]%
446   [\volt\usk\second]%

447 \NewScalarQuantity{mass}%
448   {\kilogram}%
449 \NewScalarQuantity{mobility}%
450   {\kilogram\usk\meter\tothetwo\usk\ampere\inverse\usk\second\totheinversetwo}%
451   [\meter\tothetwo\per\volt\usk\second]%
452   [\coulomb\usk\meter\per\newton\usk\second]%
453 \NewScalarQuantity{momentofinertia}%
454   {\kilogram\usk\meter\tothetwo}%
455   [\joule\usk\second\tothetwo]%
456   [\kilogram\usk\meter\tothetwo]%
457 \NewVectorQuantity{momentum}%
458   {\kilogram\usk\meter\usk\second\inverse}%
459   [\kilogram\usk\meter\per\second]%
460   [\kilogram\usk\meter\per\second]%
461 \NewVectorQuantity{momentumflux}%
462   {\kilogram\usk\meter\inverse\usk\second\totheinversetwo}%
463   [\newton\per\meter\tothetwo]%
464   [\newton\per\meter\tothetwo]%
465 \NewScalarQuantity{numberdensity}%
466   {\meter\totheinversethree}%
467   [\per\meter\tothethree]%
468   [\per\meter\tothethree]%
469 \NewScalarQuantity{permeability}%
470   {\kilogram\usk\meter\usk\ampere\totheinversetwo\usk\second\totheinversetwo}%
471   [\henry\per\meter]%
472   [\tesla\usk\meter\per\ampere]%
473 \NewScalarQuantity{permittivity}%
474   {\ampere\tothetwo\usk\second\tothefour\usk\kilogram\inverse\usk\meter\totheinversethree}%
475   [\farad\per\meter]%
476   [\coulomb\tothetwo\per\newton\usk\meter\tothetwo]%
477 \NewScalarQuantity{planeangle}%
478   {\meter\usk\meter\inverse}%
479   [\radian]%
480   [\radian]%
481 \NewScalarQuantity{polarizability}%
482   {\ampere\tothetwo\usk\second\tothefour\usk\kilogram\inverse}%
483   [\coulomb\usk\meter\tothetwo\per\volt]%
484   [\coulomb\tothetwo\usk\meter\per\newton]%
485 \NewScalarQuantity{power}%
486   {\kilogram\usk\meter\tothetwo\usk\second\totheinversethree}%
487   [\watt]%
488   [\joule\per\second]%
489 \NewVectorQuantity{poynting}%

```

```

490  {\kilogram\usk\second\totheinversethree}%
491  [\watt\per\meter\tothetwo]%
492  [\watt\per\meter\tothetwo]%
493 \NewScalarQuantity{pressure}%
494  {\kilogram\usk\meter\inverse\usk\second\totheinversetwo}%
495  [\pascal]%
496  [\newton\per\meter\tothetwo]%
497 \NewScalarQuantity{relativepermeability}%
498  {}%
499 \NewScalarQuantity{relativepermittivity}%
500  {}%

```

Resistance may also be $\text{volt}\text{per}\text{ampere}$.

```

501 \NewScalarQuantity{resistance}%
502  {\kilogram\usk\meter\tothetwo\usk\ampere\totheinversetwo\usk\second\totheinversethree}%
503  [\ohm]%
504  [\ohm]%

505 \NewScalarQuantity{resistivity}%
506  {\kilogram\usk\meter\tothethree\usk\ampere\totheinversetwo\usk\second\totheinversethree}%
507  [\ohm\usk\meter]%
508  [\volt\usk\meter\per\ampere]%
509 \NewScalarQuantity{solidangle}%
510  {\meter\tothetwo\usk\meter\totheinversetwo}%
511  [\steradian]%
512  [\steradian]%

513 \NewScalarQuantity{specificheatcapacity}%
514  {\meter\tothetwo\usk\second\totheinversetwo\usk\kelvin\inverse}%
515  [\joule\per\kelvin\usk\kilogram]%
516  [\joule\per\kelvin\usk\kilogram]%
517 \NewScalarQuantity{springstiffness}%
518  {\kilogram\usk\second\totheinversetwo}%
519  [\newton\per\meter]%
520  [\newton\per\meter]%

```

Spring stretch is really just a displacement.

```

521 \NewScalarQuantity{springstretch}%
522  {\meter}%

523 \NewScalarQuantity{stress}%
524  {\kilogram\usk\meter\inverse\usk\second\totheinversetwo}%
525  [\pascal]%
526  [\newton\per\meter\tothetwo]%
527 \NewScalarQuantity{strain}%
528  {}%

529 \NewScalarQuantity{temperature}%
530  {\kelvin}%

531 \NewVectorQuantity{torque}%
532  {\kilogram\usk\meter\tothetwo\usk\second\totheinversetwo}%
533  [\newton\usk\meter]%
534  [\newton\usk\meter]%

535 \NewVectorQuantity{velocity}%
536  {\meter\usk\second\inverse}%
537  [\meter\per\second]%
538  [\meter\per\second]%

539 \NewVectorQuantity{velocityc}%
540  {\lightspeed}%
541  [\lightspeed]%
542  [\lightspeed]%

543 \NewScalarQuantity{volume}%

```

```

544  {\meter\tothethree}%
545 \NewScalarQuantity{volumechargedensity}%
546  {\ampere\usk\second\per\meter\totheinversethree}%
547  [\coulomb\per\meter\tothethree]%
548  [\coulomb\per\meter\tothethree]%
549 \NewScalarQuantity{volumemassdensity}%
550  {\kilogram\usk\meter\totheinversethree}%
551  [\kilogram\per\meter\tothethree]%
552  [\kilogram\per\meter\tothethree]%

```

Wavelength is really just a displacement.

```

553 \NewScalarQuantity{wavelength}%
554  {\meter}%
555 \NewVectorQuantity{wavenumber}%
556  {\meter\inverse}%
557  [\per\meter]%
558  [\per\meter]%

```

Work may also be `\newton\usk\meter` but this is discouraged to avoid confusion with torque.

```

559 \NewScalarQuantity{work}%
560  {\kilogram\usk\meter\tothetwo\usk\second\totheinversetwo}%
561  [\joule]%
562  [\joule]%

```

Young's modulus is really just a stress.

```

563 \NewScalarQuantity{youngsmodulus}%
564  {\kilogram\usk\meter\inverse\usk\second\totheinversetwo}%
565  [\pascal]%
566  [\newton\per\meter\tothetwo]%

```

We need a better glyph for Planck's constant over 2π .

```

567 \AtBeginDocument{%
568   \DeclareRobustCommand{\hbar}{\mathpalette\hbar@\relax\symup{h}}}%
569 }%
570 \newcommand*{\hbar@}[2]{%
571   \makebox[0pt][l]{\raisebox{-0.07\height}{\(\text{\textnormal{m}\textnormal{o}\textnormal{th}\#1\textnormal{m}\textnormal{kern}-2mu\textnormal{A}\textnormal{F}\)}}}}%
572   \makebox[0pt][l]{\raisebox{-0.11\height}{\(\text{\textnormal{m}\textnormal{o}\textnormal{th}\#1\textnormal{m}\textnormal{kern}-2mu\textnormal{A}\textnormal{F}\)}}}}%
573 }%

```

Optional line to make the bar thicker; must use -0.11 in `\raisebox`.

```

572   \makebox[0pt][l]{\raisebox{-0.11\height}{\(\text{\textnormal{m}\textnormal{o}\textnormal{th}\#1\textnormal{m}\textnormal{kern}-2mu\textnormal{A}\textnormal{F}\)}}}}%
573 }%

```

Define physical constants for introductory physics, again alphabetically for convenience.

```

574 \NewPhysicalConstant{avogadro}%
575  {\symup{N_A}}%
576  {6\times10^{23}}{6.02214076\times10^{23}}%
577  {\mole\inverse}%
578  [\per\mole]%
579  [\per\mole]%

```

`\biotsavartconstant` is an alias for `\mzofp`.

```

580 \NewPhysicalConstant{biotsavartconstant}%
581  {\symup{\frac{\mu_0}{4\pi}}}%
582  {10^{-7}}{10^{-7}}%
583  {\kilogram\usk\meter\usk\ampere\totheinversetwo\usk\second\totheinversetwo}%
584  [\henry\per\meter]%
585  [\tesla\usk\meter\per\ampere]%
586 \NewPhysicalConstant{bohradius}%
587  {\symup{a_o}}%
588  {5.3\times10^{-11}}{5.29177210903\times10^{-11}}%

```

```

589  {\meter}%
590 \NewPhysicalConstant{boltzmann}%
591  {\symup{k_{B}}}%  

592  {1.4\times10^{-23}}{1.380649\times10^{-23}}%
593  {\kilogram\usk\meter\tothetwo\usk\second\totheinversetwo\usk\kelvin\inverse}%
594  [\joule\per\kelvin]%
595  [\joule\per\kelvin]%

\coulombconstant is an alias for \oofpez.

596 \NewPhysicalConstant{coulombconstant}%
597  {\symup{\frac{1}{4\pi\epsilon_0}}}%
598  {9\times10^9}{8.9875517923\times10^9}%
599  {\kilogram\usk\meter\tothethree\usk\ampere\totheinversetwo\usk\second\totheinversefour}%
600  [\meter\per\farad]%
601  [\newton\usk\meter\tothetwo\per\coulomb\tothetwo]%
602 \NewPhysicalConstant{earthmass}%
603  {\symup{M_{Earth}}}%  

604  {6.0\times10^{24}}{5.9722\times10^{24}}%
605  {\kilogram}%
606 \NewPhysicalConstant{earthmoondistance}%
607  {\symup{d_{EM}}}%  

608  {3.8\times10^8}{3.81550\times10^8}%
609  {\meter}%

610 \NewPhysicalConstant{earthradius}%
611  {\symup{R_{Earth}}}%  

612  {6.4\times10^6}{6.3781\times10^6}%
613  {\meter}%

614 \NewPhysicalConstant{earthsundistance}%
615  {\symup{d_{ES}}}%  

616  {1.5\times10^{11}}{1.496\times10^{11}}%
617  {\meter}%

618 \NewPhysicalConstant{electroncharge}%
619  {\symup{q_e}}%
620  {-\elementarychargeapproximatevalue}{-\elementarychargeprecisevalue}%
621  {\ampere\usk\second}%
622  [\coulomb]%
623  [\coulomb]%

624 \NewPhysicalConstant{electronCharge}%
625  {\symup{Q_e}}%
626  {-\elementarychargeapproximatevalue}{-\elementarychargeprecisevalue}%
627  {\ampere\usk\second}%
628  [\coulomb]%
629  [\coulomb]%

630 \NewPhysicalConstant{electronmass}%
631  {\symup{m_e}}%
632  {9.1\times10^{-31}}{9.1093837015\times10^{-31}}%
633  {\kilogram}%

634 \NewPhysicalConstant{elementarycharge}%
635  {\symup{e}}%
636  {1.6\times10^{-19}}{1.602176634\times10^{-19}}%
637  {\ampere\usk\second}%
638  [\coulomb]%
639  [\coulomb]%

640 \NewPhysicalConstant{finestructure}%
641  {\symup{\alpha}}%
642  {\frac{1}{137}}{7.2973525693\times10^{-3}}%
643  {}%  

644 \NewPhysicalConstant{hydrogenmass}%
645  {\symup{m_H}}%

```

```

646 {1.7\times10^{-27}}{1.6737236\times10^{-27}}%
647 {\kilogram}%
648 \NewPhysicalConstant{moonearthdistance}%
649 {\symup{d_{ME}}}%
650 {3.8\times10^8}{3.81550\times10^8}%
651 {\meter}%
652 \NewPhysicalConstant{moonmass}%
653 {\symup{M_{Moon}}}%
654 {7.3\times10^{22}}{7.342\times10^{22}}%
655 {\kilogram}%
656 \NewPhysicalConstant{moonradius}%
657 {\symup{R_{Moon}}}%
658 {1.7\times10^6}{1.7371\times10^6}%
659 {\meter}%
660 \NewPhysicalConstant{mzofp}%
661 {\symup{\frac{\mu_0}{4\pi}}}%
662 {10^{-7}}{10^{-7}}%
663 {\kilogram\usk\meter\usk\ampere\totheinversetwo\usk\second\totheinversetwo}%
664 [\henry\per\meter]%
665 [\tesla\usk\meter\per\ampere]%
666 \NewPhysicalConstant{neutronmass}%
667 {\symup{m_n}}%
668 {1.7\times10^{-27}}{1.67492749804\times10^{-27}}%
669 {\kilogram}%
670 \NewPhysicalConstant{oofpez}%
671 {\symup{\frac{1}{4\pi\epsilon_0}}}%
672 {9\times10^9}{8.9875517923\times10^9}%
673 {\kilogram\usk\meter\tothethree\usk\ampere\totheinversetwo\usk\second\totheinversefour}%
674 [\meter\per\farad]%
675 [\newton\usk\meter\tothetwo\per\coulomb\tothetwo]%
676 \NewPhysicalConstant{oofpezcs}%
677 {\symup{\frac{1}{4\pi\epsilon_0 c^2}}}%
678 {10^{-7}}{10^{-7}}%
679 {\kilogram\usk\meter\usk\ampere\totheinversetwo\usk\second\totheinversetwo}%
680 [\tesla\usk\meter\tothetwo]%
681 [\newton\usk\second\tothetwo\per\coulomb\tothetwo]%
682 \NewPhysicalConstant{planck}%
683 {\symup{h}}%
684 {6.6\times10^{-34}}{6.62607015\times10^{-34}}%
685 {\kilogram\usk\meter\tothetwo\usk\second\inverse}%
686 [\joule\usk\second]%
687 [\joule\usk\second]%

```

See <https://tex.stackexchange.com/a/448565/218142>.

```

688 \NewPhysicalConstant{planckbar}%
689 {\hbar}%
690 {1.1\times10^{-34}}{1.054571817\times10^{-34}}%
691 {\kilogram\usk\meter\tothetwo\usk\second\inverse}%
692 [\joule\usk\second]%
693 [\joule\usk\second]%
694 \NewPhysicalConstant{planckc}%
695 {\symup{hc}}%
696 {2.0\times10^{-25}}{1.98644586\times10^{-25}}%
697 {\kilogram\usk\meter\tothethree\usk\second\totheinversetwo}%
698 [\joule\usk\meter]%
699 [\joule\usk\meter]%
700 \NewPhysicalConstant{protoncharge}%
701 {\symup{q_p}}%
702 {+\elementarychargeapproximatevalue}{+\elementarychargeprecisevalue}%

```

```

703  {\ampere\usk\second}%
704  [\coulomb]%
705  [\coulomb]%
706 \NewPhysicalConstant{protonCharge}%
707  {\symup{Q_p}}%
708  {+\elementarychargeapproximatevalue}{+\elementarychargeprecisevalue}%
709  {\ampere\usk\second}%
710  [\coulomb]%
711  [\coulomb]%
712 \NewPhysicalConstant{protonmass}%
713  {\symup{m_p}}%
714  {1.7\times10^{-27}}{1.672621898\times10^{-27}}%
715  [\kilogram]%
716 \NewPhysicalConstant{rydberg}%
717  {\symup{R_infty}}%
718  {1.1\times10^7}{1.0973731568160\times10^7}%
719  [\meter\inverse]%
720 \NewPhysicalConstant{speedoflight}%
721  {\symup{c}}%
722  {3\times10^8}{2.99792458\times10^8}%
723  [\meter\usk\second\inverse]%
724  [\meter\per\second]%
725  [\meter\per\second]%
726 \NewPhysicalConstant{stefanboltzmann}%
727  {\symup{\sigma}}%
728  {5.7\times10^{-8}}{5.670374\times10^{-8}}%
729  [\kilogram\usk\second\tothe{inversethree}\usk\kelvin\tothe{inversefour}]%
730  [\watt\per\meter\tothetwo\usk\kelvin\tothefour]%
731  [\watt\per\meter\tothetwo\usk\kelvin\tothefour]%
732 \NewPhysicalConstant{sunearthdistance}%
733  {\symup{d_SE}}%
734  {1.5\times10^{11}}{1.496\times10^{11}}%
735  [\meter]%
736 \NewPhysicalConstant{sunmass}%
737  {\symup{M_Sun}}%
738  {2.0\times10^{30}}{1.98855\times10^{30}}%
739  [\kilogram]%
740 \NewPhysicalConstant{sunradius}%
741  {\symup{R_Sun}}%
742  {7.0\times10^8}{6.957\times10^8}%
743  [\meter]%
744 \NewPhysicalConstant{surfacegravfield}%
745  {\symup{g}}%
746  {9.8}{9.807}%
747  [\meter\usk\second\tothe{inversetwo}]%
748  [\newton\per\kilogram]%
749  [\newton\per\kilogram]%

```

The gravitational constant may also have units of $\text{joule}\text{usk}\text{meter}\text{per}\text{kilogram}\text{tothetwo}$.

```

750 \NewPhysicalConstant{universalgrav}%
751  {\symup{G}}%
752  {6.7\times10^{-11}}{6.67430\times10^{-11}}%
753  [\meter\tothethree\usk\kilogram\inverse\usk\second\tothe{inversetwo}]%
754  [\newton\usk\meter\tothetwo\per\kilogram\tothetwo]%
755  [\newton\usk\meter\tothetwo\per\kilogram\tothetwo]%

```

As of 2018 the vacuum permeability is no longer defined as $4\pi \times 10^{-7}$.

```

756 \NewPhysicalConstant{vacuumpermeability}%
757  {\symup{\mu_0}}%

```

```

758 {4\pi\times10^{-7}}{4\pi\times10^{-7}}%
759 {\kilogram\usk\meter\usk\ampere\totheinversetwo\usk\second\totheinversetwo}%
760 [\henry\per\meter]%
761 [\tesla\usk\meter\per\ampere]%
762 \NewPhysicalConstant{vacuumpermittivity}%
763 {\symup{\epsilon_0}}%
764 {9\times10^{-12}}{8.854187817\times10^{-12}}%
765 {\ampere\tothetwo\usk\second\tothefour\usk\kilogram\inverse\usk\meter\totheinversethree}%
766 [\farad\per\meter]%
767 [\coulomb\tothetwo\per\newton\usk\meter\tothetwo]%

```

Diagnostic commands to provide sanity checks on commands that represent physical quantities and constants.

```

768 \ExplSyntaxOn
769 \NewDocumentCommand{\aux}{ m }
770 {
771     \use:c { #1 }
772 }
773 \NewDocumentCommand{\auy}{ m }
774 {
775     \normalfont\ttfamily\token_to_str:c { #1 }
776 }
777 \ExplSyntaxOff
778 \newcolumntype{M}{>{\(}p{0.25\linewidth}<{\)}}
```

$$\begin{array}{|c|c|c|c|} \hline \text{command} & \text{base} & \text{derived} & \text{alternate} \\ \hline \text{only base units} & & & \\ \text{only derived units} & & & \\ \text{only alternate units} & & & \\ \hline \end{array}$$

```

779 \NewDocumentCommand{\CheckQuantity}{ m }
780 {%
781     \begin{center}
782         \begin{tabular}{|c|c|c|c|} \hline
783             \text{command} & \multicolumn{3}{|c|}{\auy{#1}} \\ \hline
784             \text{base} & \text{derived} & \text{alternate} & \\ \hline
785             \text{only base units} & \text{only derived units} & \text{only alternate units} & \\ \hline
786         \end{tabular}
787     \end{center}
788 }%
789 \NewDocumentCommand{\CheckConstant}{ m }
790 {%
791     \begin{center}
792         \begin{tabular}{|c|c|c|c|} \hline
793             \text{command} & \multicolumn{3}{|c|}{\auy{#1}} \\ \hline
794             \text{symbol} & \text{approximate} & \text{precise} & \\ \hline
795             \text{mathsymbol} & \text{approximatevalue} & \text{precisevalue} & \\ \hline
796             \text{base} & \text{derived} & \text{alternate} & \\ \hline
797             \text{only base units} & \text{only derived units} & \text{only alternate units} & \\ \hline
798         \end{tabular}
799     \end{center}
800 }%

```

`\mivector`^{P.34} is a workhorse command.

See <https://tex.stackexchange.com/a/39054/218142>.

```

801 \ExplSyntaxOn
802 \NewDocumentCommand{\mivector}{ O{,} m o }
803 {
804     \__mandi_vector:nn { #1 } { #2 }
805     \IfValueT{#3}{\, , #3}
806 }
807 \seq_new:N \l__mandi_list_seq
808 \cs_new_protected:Npn \__mandi_vector:nn #1#2
809 {
810     \seq_set_split:Nnn \l__mandi_list_seq { , } { #2 }
811     \int_compare:nT { \seq_count:N \l__mandi_list_seq = 1 }
```

```

812 {
813   \msg_new:nnnn { mandi } { onecomponent }
814   {
815     More~than~one~component~expected.          \iow_newline:
816     You~provided~one~component~to~a~command \iow_newline:
817     that~expects~a~vector.~Either~you~don't \iow_newline:
818     need~a~vector~here~or~you~didn't~supply \iow_newline:
819     all~the~components.
820   }
821   {
822     Decide~whether~or~not~you~really~need~a~vector~command~here. \iow_newline:
823     \msg_see_documentation_text:n { mandi }
824   }
825   \msg_fatal:nn { mandi } { onecomponent }
826
827 }
828 \left\langle
829   \seq_use:Nnnn \l_mandi_list_seq { #1 } { #1 } { #1 }
830 \right\rangle
831 }
832 \ExplSyntaxOff

```

7 The `mandistudent` Package

mandi comes with an accessory package `mandistudent`, which extends `mandi` with a collection of commands physics students can use for writing problem solutions. This package focuses on the most frequently needed tools. These commands should always be used in math mode. `mandistudent` requires, and loads, `mandi` but `mandi` doesn't require, and doesn't load, `mandistudent`.

Load `mandistudent` as you would any package in your preamble. There are no package options.

```
\usepackage{mandistudent}
```

`\mandistudentversion`

Typesets the current version and build date.

```
The version is \mandistudentversion{} and is a stable build.
```

```
The version is v3.2.2 dated 2024-02-27 and is a stable build.
```

7.1 Traditional Vector Notation

U 2021-09-18

```
\vec{\langle symbol \rangle}[\langle labels \rangle]
```

(use this variant for boldface notation)

U 2021-09-18

```
\vec*{\langle symbol \rangle}[\langle labels \rangle]
```

(use this variant for arrow notation)

Powerful and intelligent command for symbolic vector notation. The mandatory argument is the symbol for the vector quantity. The optional label(s) consists of superscripts and/or subscripts and can be mathematical or textual in nature. If textual, be sure to wrap them in `\symup{...}` for proper typesetting. The starred variant gives arrow notation whereas without the star you get boldface notation. Subscript and superscript labels can be arbitrarily mixed, and order doesn't matter. This command redefines the default L^AT_EX 2 _{ε} `\vec` command.

```
\(\vec{p}\) \\  
\(\vec{p}_2\) \\  
\(\vec{p}^{\text{ball}}\) \\  
\(\vec{p}_{\text{final}}\) \\  
\(\vec{p}_{\text{final}}^{\text{ball}}\) \\  
\(\vec{p}_{\text{final}}^{\text{final}}\) \\  
\(\vec{p}_{\text{ball}}^{\text{final}}\) \\  
\(\vec{p}_{\text{final}}^{\text{ball}}\) \\  
\(\vec{p}_{\text{final}}^{\text{final}}\) \\  
\(\vec{p}_{\text{ball}}^{\text{final}}\)
```

p
 p_2
 p_{ball}
 p_{final}
 $p_{\text{final ball}}$
 $p_{\text{final final}}$
 $p_{\text{ball ball}}$
 \vec{p}
 \vec{p}_2
 \vec{p}_{ball}
 \vec{p}_{final}
 $\vec{p}_{\text{final final}}$
 $\vec{p}_{\text{ball ball}}$

U 2021-09-18

```
\dirvec{\langle symbol \rangle}[\langle labels \rangle]
```

(use this variant for boldface notation)

U 2021-09-18

`\dirvec*`{*symbol*} [*labels*]

(use this variant for arrow notation)

Powerful and intelligent command for typesetting the direction of a vector. The options are the same as those for `\vec`.

<code>\(\dirvec{p}\)</code>	\hat{p}
<code>\(\dirvec{p}_2\)</code>	\hat{p}_2
<code>\(\dirvec{p}^{\text{final}}\)</code>	\hat{p}_{final}
<code>\(\dirvec{p}^{\text{ball}}\)</code>	\hat{p}_{ball}
<code>\(\dirvec{p}^{\text{final}}_{\text{final}}\)</code>	$\hat{p}_{\text{final}}^{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}_{\text{ball}}\)</code>	$\hat{p}_{\text{final}}^{\text{ball}}$
<code>\(\dirvec{p}^{\text{ball}}_{\text{final}}\)</code>	$\hat{p}_{\text{ball}}^{\text{final}}$
<code>\(\dirvec{p}^{\text{ball}}_{\text{ball}}\)</code>	$\hat{p}_{\text{ball}}^{\text{ball}}$
<code>\(\dirvec{p}_2\)</code>	\hat{p}_2
<code>\(\dirvec{p}^{\text{final}}\)_2</code>	\hat{p}^{final}_2
<code>\(\dirvec{p}^{\text{final}}\)^2</code>	\hat{p}^{final}_2
<code>\(\dirvec{p}^{\text{final}}\)^{-1}</code>	$\hat{p}^{-1}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-2}</code>	$\hat{p}^{-2}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-3}</code>	$\hat{p}^{-3}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-4}</code>	$\hat{p}^{-4}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-5}</code>	$\hat{p}^{-5}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-6}</code>	$\hat{p}^{-6}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-7}</code>	$\hat{p}^{-7}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-8}</code>	$\hat{p}^{-8}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-9}</code>	$\hat{p}^{-9}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-10}</code>	$\hat{p}^{-10}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-11}</code>	$\hat{p}^{-11}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-12}</code>	$\hat{p}^{-12}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-13}</code>	$\hat{p}^{-13}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-14}</code>	$\hat{p}^{-14}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-15}</code>	$\hat{p}^{-15}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-16}</code>	$\hat{p}^{-16}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-17}</code>	$\hat{p}^{-17}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-18}</code>	$\hat{p}^{-18}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-19}</code>	$\hat{p}^{-19}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-20}</code>	$\hat{p}^{-20}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-21}</code>	$\hat{p}^{-21}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-22}</code>	$\hat{p}^{-22}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-23}</code>	$\hat{p}^{-23}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-24}</code>	$\hat{p}^{-24}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-25}</code>	$\hat{p}^{-25}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-26}</code>	$\hat{p}^{-26}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-27}</code>	$\hat{p}^{-27}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-28}</code>	$\hat{p}^{-28}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-29}</code>	$\hat{p}^{-29}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-30}</code>	$\hat{p}^{-30}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-31}</code>	$\hat{p}^{-31}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-32}</code>	$\hat{p}^{-32}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-33}</code>	$\hat{p}^{-33}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-34}</code>	$\hat{p}^{-34}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-35}</code>	$\hat{p}^{-35}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-36}</code>	$\hat{p}^{-36}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-37}</code>	$\hat{p}^{-37}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-38}</code>	$\hat{p}^{-38}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-39}</code>	$\hat{p}^{-39}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-40}</code>	$\hat{p}^{-40}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-41}</code>	$\hat{p}^{-41}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-42}</code>	$\hat{p}^{-42}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-43}</code>	$\hat{p}^{-43}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-44}</code>	$\hat{p}^{-44}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-45}</code>	$\hat{p}^{-45}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-46}</code>	$\hat{p}^{-46}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-47}</code>	$\hat{p}^{-47}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-48}</code>	$\hat{p}^{-48}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-49}</code>	$\hat{p}^{-49}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-50}</code>	$\hat{p}^{-50}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-51}</code>	$\hat{p}^{-51}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-52}</code>	$\hat{p}^{-52}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-53}</code>	$\hat{p}^{-53}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-54}</code>	$\hat{p}^{-54}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-55}</code>	$\hat{p}^{-55}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-56}</code>	$\hat{p}^{-56}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-57}</code>	$\hat{p}^{-57}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-58}</code>	$\hat{p}^{-58}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-59}</code>	$\hat{p}^{-59}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-60}</code>	$\hat{p}^{-60}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-61}</code>	$\hat{p}^{-61}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-62}</code>	$\hat{p}^{-62}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-63}</code>	$\hat{p}^{-63}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-64}</code>	$\hat{p}^{-64}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-65}</code>	$\hat{p}^{-65}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-66}</code>	$\hat{p}^{-66}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-67}</code>	$\hat{p}^{-67}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-68}</code>	$\hat{p}^{-68}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-69}</code>	$\hat{p}^{-69}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-70}</code>	$\hat{p}^{-70}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-71}</code>	$\hat{p}^{-71}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-72}</code>	$\hat{p}^{-72}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-73}</code>	$\hat{p}^{-73}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-74}</code>	$\hat{p}^{-74}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-75}</code>	$\hat{p}^{-75}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-76}</code>	$\hat{p}^{-76}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-77}</code>	$\hat{p}^{-77}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-78}</code>	$\hat{p}^{-78}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-79}</code>	$\hat{p}^{-79}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-80}</code>	$\hat{p}^{-80}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-81}</code>	$\hat{p}^{-81}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-82}</code>	$\hat{p}^{-82}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-83}</code>	$\hat{p}^{-83}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-84}</code>	$\hat{p}^{-84}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-85}</code>	$\hat{p}^{-85}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-86}</code>	$\hat{p}^{-86}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-87}</code>	$\hat{p}^{-87}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-88}</code>	$\hat{p}^{-88}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-89}</code>	$\hat{p}^{-89}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-90}</code>	$\hat{p}^{-90}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-91}</code>	$\hat{p}^{-91}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-92}</code>	$\hat{p}^{-92}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-93}</code>	$\hat{p}^{-93}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-94}</code>	$\hat{p}^{-94}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-95}</code>	$\hat{p}^{-95}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-96}</code>	$\hat{p}^{-96}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-97}</code>	$\hat{p}^{-97}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-98}</code>	$\hat{p}^{-98}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-99}</code>	$\hat{p}^{-99}_{\text{final}}$
<code>\(\dirvec{p}^{\text{final}}\)^{-100}</code>	$\hat{p}^{-100}_{\text{final}}$

`\zerovec`

`\zerovec*`

(use this variant for boldface notation)

(use this variant for arrow notation)

Command for typesetting the zero vector. The starred variant gives arrow notation. Without the star you get boldface notation.

<code>\(\zerovec\)</code>	$\mathbf{0}$
<code>\(\zerovec*\)</code>	$\overrightarrow{0}$

`\changein`

Semantic alias for `\Delta`.

<code>\(\changein t\)</code>	Δt
<code>\(\changein \vec{p}\)</code>	$\Delta \vec{p}$

N 2021-02-21

`\doublebars`[*size*]{*quantity*}

(double bars)

`\doublebars*`[*size*]{*quantity*}

(double bars for fractions)

N 2021-02-21

`\singlebars`[*size*]{*quantity*}

(single bars)

N 2021-02-21

`\singlebars*`[*size*]{*quantity*}

(single bars for fractions)

N 2021-02-21

`\anglebrackets`[*size*]{*quantity*}

(angle brackets)

N 2021-02-21

`\anglebrackets*`[*size*]{*quantity*}

(angle brackets for fractions)

N 2021-02-21

`\parentheses`[*size*]{*quantity*}

(parentheses)

N 2021-02-21

`\parentheses*`[*size*]{*quantity*}

(parentheses for fractions)

N 2021-02-21

`\squarebrackets`[*size*]{*quantity*}

(square brackets)

N 2021-02-21

`\squarebrackets*`[*size*]{*quantity*}

(square brackets for fractions)

N 2021-02-21
N 2021-02-21

`\curlybraces[⟨size⟩]{⟨quantity⟩}` (curly braces)
`\curlybraces*[⟨size⟩]{⟨quantity⟩}` (curly braces for fractions)

If no argument is given, a placeholder is provided. Sizers like `\big`, `\Big`, `\bigg`, and `\Bigg` can be optionally specified. Beginners are encouraged not to use them. See the `mathtools` package documentation for details.

```
\[ \doublebars{} \]
\[ \doublebars{\vec{a}} \]
\[ \doublebars*{\frac{\vec{a}}{3}} \]
\[ \doublebars[\Bigg]{\frac{\vec{a}}{3}} \]
```

$$\begin{aligned} & \| \cdot \| \\ & \| a \| \\ & \left\| \frac{a}{3} \right\| \\ & \left\| \frac{a}{3} \right\| \end{aligned}$$

```
\[ \singlebars{} \]
\[ \singlebars{x} \]
\[ \singlebars*{\frac{x}{3}} \]
\[ \singlebars[\Bigg]{\frac{x}{3}} \]
```

$$\begin{aligned} & | \cdot | \\ & | x | \\ & \left| \frac{x}{3} \right| \\ & \left| \frac{x}{3} \right| \end{aligned}$$

```
\[ \anglebrackets{} \]
\[ \anglebrackets{\vec{a}} \]
\[ \anglebrackets*{\frac{\vec{a}}{3}} \]
\[ \anglebrackets[\Bigg]{\frac{\vec{a}}{3}} \]
```

$$\begin{aligned} & \langle \cdot \rangle \\ & \langle a \rangle \\ & \left\langle \frac{a}{3} \right\rangle \\ & \left\langle \frac{a}{3} \right\rangle \end{aligned}$$

```
\[ \parentheses{} \]
\[ \parentheses{x} \]
\[ \parentheses*{\frac{x}{3}} \]
\[ \parentheses[\Bigg]{\frac{x}{3}} \]
```

$$\begin{aligned} & (\cdot) \\ & (x) \\ & \left(\frac{x}{3} \right) \\ & \left(\frac{x}{3} \right) \end{aligned}$$

```
\[ \squarebrackets{} \]
\[ \squarebrackets{x} \]
\[ \squarebrackets*{\frac{x}{3}} \]
\[ \squarebrackets[\Bigg]{\frac{x}{3}} \]
```

$$\begin{bmatrix} \cdot \\ x \\ \frac{x}{3} \\ \frac{x}{3} \end{bmatrix}$$

```
\{ \curlybraces{} \}
\{ \curlybraces{x} \}
\{ \curlybraces*{\frac{x}{3}} \}
\{ \curlybraces[\Bigg]{\frac{x}{3}} \}
```

$$\begin{Bmatrix} \cdot \\ x \\ \frac{x}{3} \\ \frac{x}{3} \end{Bmatrix}$$

N 2021-02-21 `\magnitude[⟨size⟩]{⟨quantity⟩}`
N 2021-02-21 `\magnitude*[⟨size⟩]{⟨quantity⟩}`
N 2021-02-21 `\norm[⟨size⟩]{⟨quantity⟩}`
N 2021-02-21 `\norm*[⟨size⟩]{⟨quantity⟩}`
N 2021-02-21 `\absolutevalue[⟨size⟩]{⟨quantity⟩}`
N 2021-02-21 `\absolutevalue*[⟨size⟩]{⟨quantity⟩}`

(alias for double bars)
(alias for double bars for fractions)
(alias for double bars)
(alias for double bars for fractions)
(alias for single bars)
(alias for single bars for fractions)

Semantic aliases. Use `\magnitude` or `\magnitude*` to typeset the magnitude of a vector.

```
\[ \magnitude{\vec{p}} \]
\[ \magnitude*{\vec{p}} \]
\[ \magnitude*{\vec{p}_{\text{final}}} \]
\[ \magnitude*{\vec{p}_{\text{final}}} \]
```

$$\begin{aligned} \|p\| \\ \|\vec{p}\| \\ \|p_{\text{final}}\| \\ \|\vec{p}_{\text{final}}\| \end{aligned}$$

N 2021-04-06 `\parallelto`
N 2021-04-06 `\perpendicularto`

Commands for geometric relationships, mainly intended for subscripts.

```
\( \vec{F}_{\parallel} \{\parallelto\} + \vec{F}_{\perp} \{\perpendicularto\} \)
```

$$F_{\parallel} + F_{\perp}$$

7.2 Problems and Annotated Problem Solutions

U 2023-08-01

```
\begin{physicsproblem}{\langle title \rangle}
  \langle problem \rangle
\end{physicsproblem}
```

(use this variant for vertical lists)

U 2023-08-01

```
\begin{physicsproblem*}{\langle title \rangle}
  \langle problem \rangle
\end{physicsproblem*}
```

(use this variant for in-line lists)

U 2023-08-01

```
\begin{parts}{\langle title \rangle}
  \langle problem \rangle
\end{parts}
```

(provides problem parts)

Provides an environment for stating physics problems. Each problem will begin on a new page. See the examples for how to handle single and multiple part problems. Due to incompatibilities with BEAMER and the enumitem package, these environments are not defined if BEAMER is loaded.

U 2023-08-01

```
\problempart
```

Denotes a part of a problem within a `parts` environment. This command is not defined if BEAMER is loaded.

```
\begin{physicsproblem}{Problem 1}
  This is a physics problem with no parts.
\end{physicsproblem}
```

Problem 1

This is a physics problem with no parts.

```
\begin{physicsproblem}{Problem 2}
  This is a physics problem with multiple parts.
  The list is vertical.
  \begin{parts}
    \problempart This is the first part.
    \problempart This is the second part.
    \problempart This is the third part.
  \end{parts}
\end{physicsproblem}
```

Problem 2

This is a physics problem with multiple parts. The list is vertical.

- (a) This is the first part.
- (b) This is the second part.
- (c) This is the third part.

```
\begin{physicsproblem*}{Problem 3}
  This is a physics problem with multiple parts.
  The list is in-line.
  \begin{parts}
    \problempart This is the first part.
    \problempart This is the second part.
    \problempart This is the third part.
  \end{parts}
\end{physicsproblem*}
```

Problem 3

This is a physics problem with multiple parts. The list is in-line. (a) This is the first part. (b) This is the second part. (c) This is the third part.

U 2021-02-26

```
\begin{physicssolution}
  \langle solution steps \rangle
\end{physicssolution} (use this variant for numbered steps)
```

U 2021-02-26

```
\begin{physicssolution*}
  \langle solution steps \rangle
\end{physicssolution*} (use this variant for unnumbered steps)
```

This environment is only for mathematical solutions. The starred variant omits numbering of steps. See the examples.

<pre>\begin{physicssolution} x &= y + z \\ z &= x - y \\ y &= x - z \end{physicssolution}</pre>	$x = y + z$ (1) $z = x - y$ (2) $y = x - z$ (3)
<pre>\begin{physicssolution*} x &= y + z \\ z &= x - y \\ y &= x - z \end{physicssolution*}</pre>	$x = y + z$ $z = x - y$ $y = x - z$

U 2021-02-26

\reason{<reason>}

Provides an annotation in a step-by-step solution. Keep reasons short and to the point. Wrap mathematical content in math mode.

```
\begin{physicssolution}
x &= y + z \reason{This is a reason.} \\
z &= x - y \reason{This is a reason too.} \\
y &= x - z \reason{final answer}
\end{physicssolution}
\begin{physicssolution*}
x &= y + z \reason{This is a reason.} \\
z &= x - y \reason{This is a reason too.} \\
y &= x - z \reason{final answer}
\end{physicssolution*}
```

$$x = y + z \quad \text{This is a reason.} \quad (4)$$

$$z = x - y \quad \text{This is a reason too.} \quad (5)$$

$$y = x - z \quad \text{final answer} \quad (6)$$

$$\begin{aligned} x &= y + z && \text{This is a reason.} \\ z &= x - y && \text{This is a reason too.} \\ y &= x - z && \text{final answer} \end{aligned}$$

When writing solutions, remember that the `physicssolution`^{→P.57} environment is *only* for mathematical content, not textual content or explanations.

```
\begin{physicsproblem}{Combined Problem and Solution}
This is an interesting physics problem.
\begin{physicssolution}
The solution goes here.
\end{physicssolution}
\end{physicsproblem}
```

```
\begin{physicsproblem}{Combined Multipart Problem with Solutions}
This is a physics problem with multiple parts.
\begin{parts}
\problempart This is the first part.
\begin{physicssolution}
The solution goes here.
\end{physicssolution}
\problempart This is the second part.
\begin{physicssolution}
The solution goes here.
\end{physicssolution}
\problempart This is the third part.
\begin{physicssolution}
The solution goes here.
\end{physicssolution}
\end{parts}
\end{physicsproblem}
```

`\hilite[<color>]{<target>} [<shape>]`

Hilites the desired target, which can be an entire mathematical expression or a part thereof. The default color is magenta and the default shape is a rectangle. This command is not defined if BEAMER is loaded.

```

\begin{align*}
(\Delta s)^2 &= -(\Delta t)^2 + (\Delta x)^2 + (\Delta y)^2 + \\
&\quad (\Delta z)^2 \\
(\Delta s)^2 &= \text{hilite}{-(\Delta t)^2 + (\Delta x)^2}[\text{rounded rectangle}] + \\
&\quad (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= \text{hilite}{-(\Delta t)^2 + (\Delta x)^2}[\text{rectangle}] + \\
&\quad (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= \text{hilite}{-(\Delta t)^2 + (\Delta x)^2}[\text{ellipse}] + \\
&\quad (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= \text{hilite}{2}[\text{circle}] &= \text{hilite}[green]{-}[\text{circle}] \\
&\quad (\Delta t)^2[\text{cyan}{2}][\text{circle}] + \\
&\quad (\Delta x)^2[\text{orange}{2}][\text{circle}] + \\
&\quad (\Delta y)^2[\text{blue}{50}{2}][\text{circle}] + \\
&\quad (\Delta z)^2[\text{violet}{45}{2}][\text{circle}]
\end{align*}

```

$$\begin{aligned}
(\Delta s)^2 &= -(\Delta t)^2 + (\Delta x)^2 + (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= -(\Delta t)^2 + (\Delta x)^2 + (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= -(\Delta t)^2 + (\Delta x)^2 + (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= -(\Delta t)^2 + (\Delta x)^2 + (\Delta y)^2 + (\Delta z)^2 \\
(\Delta s)^2 &= \text{hilite}{2}[\text{circle}] = \text{hilite}[\text{green}]{-}[\text{circle}] \\
&\quad (\Delta t)^2[\text{cyan}{2}][\text{circle}] + \\
&\quad (\Delta x)^2[\text{orange}{2}][\text{circle}] + \\
&\quad (\Delta y)^2[\text{blue}{50}{2}][\text{circle}] + \\
&\quad (\Delta z)^2[\text{violet}{45}{2}][\text{circle}]
\end{aligned}$$

```

\begin{align*}
\Delta \vec{p} &= \vec{F}_{\text{net}} \Delta t \\
\text{hilite}{\text{orange}}{\Delta \vec{p}} &= \vec{F}_{\text{net}} \Delta t \\
\Delta \vec{p} &= \text{hilite}{\text{yellow}{50}}{\vec{F}_{\text{net}}} \Delta t \\
&\quad [\text{rounded rectangle}] \Delta t \\
\Delta \vec{p} &= \vec{F}_{\text{net}} \Delta t \\
&\quad [\text{rectangle}] \\
\Delta \vec{p} &= \text{hilite}{\text{cyan}{50}}{\vec{F}_{\text{net}}} \Delta t \\
&\quad [\text{ellipse}] \\
\text{hilite}{\Delta \vec{p}} &= \vec{F}_{\text{net}} \Delta t
\end{align*}

```

$$\begin{aligned}
\Delta p &= F_{\text{net}} \Delta t \\
\text{hilite}{\Delta p} &= F_{\text{net}} \Delta t \\
\Delta p &= F_{\text{net}} \Delta t
\end{aligned}$$

`\image[<options>]{<caption>}{<label>}{<image>}`

Simplified interface for importing an image. The images are treated as floats, so they may not appear at the most logically intuitive place.

```
\image[scale=0.20]{example-image-1x1}
{Image shown 20 percent actual size.}{refffig1}
```



Figure 1: Image shown 20 percent actual size.

Figure \ref{refffig1} is nice.
It's captioned \nameref{refffig1} and is on page \pageref{refffig1}.

Figure 1 is nice. It's captioned [Image shown 20 percent actual size](#) and is on page [60](#).

```
\image[scale=0.20,angle=45]{example-image-1x1}
{Image shown 20 percent actual size and rotated.}{refffig1}
```




Figure 2: Image shown 20 percent actual size and rotated.

Figure \ref{refffig2} is nice.
It's captioned \nameref{refffig2} and is on page \pageref{refffig2}.

Figure 2 is nice. It's captioned [Image shown 20 percent actual size and rotated](#) and is on page [60](#).

7.3 Coordinate-Free and Index Notation

Beyond the current level of introductory physics, we need intelligent commands for typesetting vector and tensor symbols and components suitable for both coordinate-free and index notations.

```
\colvec[\langle delimiter\rangle]{\langle c_1, \dots, c_n \rangle}
\rowvec[\langle delimiter\rangle]{\langle c_1, \dots, c_n \rangle}
```

Typesets column vectors and row vectors as numeric or symbolic components. There can be more than three components. The delimiter used in the list of components can be specified; the default is a comma. Units are not supported, so these are mainly for symbolic work.

```
\[ \colvec{1,2,3} \]
\[ \rowvec{1,2,3} \]
\[ \colvec{x^0,x^1,x^2,x^3} \]
\[ \rowvec{x_0,x_1,x_2,x_3} \]
```

$$\begin{pmatrix} 1 \\ 2 \\ 3 \end{pmatrix}$$

(1 2 3)

$$\begin{pmatrix} x^0 \\ x^1 \\ x^2 \\ x^3 \end{pmatrix}$$

($x_0 \ x_1 \ x_2 \ x_3$)

`\veccomp{<symbol>}`
`\veccomp*{<symbol>}`
`\tencomp{<symbol>}`
`\tencomp*{<symbol>}`

(use this variant for coordinate-free vector notation)
 (use this variant for index vector notation)
 (use this variant for coordinate-free tensor notation)
 (use this variant for index tensor notation)

Conforms to ISO 80000-2 notation.

```
\( \veccomp{r} \) \\
\( \veccomp*{r} \) \\
\( \tencomp{r} \) \\
\( \tencomp*{r} \)
```

r
r
r
r

`\valence{<index>}{<index>}`
`\valence*{<index>}{<index>}`

Typesets tensor valence. The starred variant typesets it horizontally.

A vector is a $\valence{1}{0}$ tensor.
 A vector is a $\valence*{1}{0}$ tensor.

A vector is a $\begin{pmatrix} 1 \\ 0 \end{pmatrix}$ tensor.
 A vector is a (1, 0) tensor.

`\contraction{<slot,slot>}`
`\contraction*{<slot,slot>}`

Typesets tensor contraction in coordinate-free notation. There is no standard for this so we assert one here.

```
\( \contraction{1,2} \) \\
\( \contraction*{1,2} \)
```

$C_{1,2}$
 $C_{1,2}$

`\slot[<vector>]`
`\slot*[<vector>]`

An intelligent slot command for coordinate-free vector and tensor notation. The starred variants suppress the underscore.

$\backslash(\backslash(\backslash(slot)\backslash)\backslash\backslash$ $\backslash(\backslash(slot[\backslash vec\{a}\}])\backslash)\backslash\backslash$ $\backslash(\backslash(slot^*)\backslash)\backslash\backslash$ $\backslash(\backslash(slot^*[\backslash vec\{a}\}])\backslash)$	$(\underline{\underline{}})$ $(\underline{\text{a}})$ $(\underline{\underline{\quad}})$ $(\underline{\text{a}})$
---	---

U 2022-01-27

\df

Intelligent differential and exterior derivative operator.

```
\[
  \int x\,dx
\]
\[
  \int x\,\mathrm{d}x
\]
\[
  \int x\,\mathbf{d}x
\]
```

$$\int x\,dx$$

$$\int x\,\mathrm{d}x$$

$$\int x\,\mathbf{d}x$$

7.4 Web VPython and VPython Program Listings

Web VPython³ and VPython⁴ are programming environments (both use Python) frequently used in introductory physics to introduce students for modeling physical systems. mandi makes including code listings very simple for students.

7.5 The `webvpythonblock` Environment

U 2023-08-01

```
\begin{webvpythonblock}[(options)](<link>){<caption>}
  <Web VPython code>
\end{webvpythonblock}
```

(now includes a QR code)

U 2023-08-01

```
\begin{webvpythonblock*}[(options)](<link>){<caption>}
  <Web VPython code>
\end{webvpythonblock*}
```

(use this variant to omit QR code)

Code placed here is nicely formatted and optionally linked to its source on [Web VPython.org](https://WebVPYthon.org), which must be in a public (not private) folder. Clicking anywhere in the code window (between the black horizontal bars) or on the URL will open the link in the default browser. A caption is mandatory, and a label is internally generated. The listing always begins on a new page. A URL shortening utility is recommended to keep the URL from getting unruly especially if it generates an overfull box error. For convenience, <https://> is automatically prepended to the URL and can be omitted. The # character in a URL should not cause problems. The default URL is that of the Web VPython home page.

³On November 9, 2021 GlowScript was renamed to Web VPython. The website was changed to <https://webvpython.org>.

⁴<https://vpython.org>

```

\begin{webpythonblock}
(glowscript.org/#/user/heafnerj/folder/mandidemo/program/mandidemo)
{Example With QR Code}
Web VPython 3.2

scene.width = 400
scene.height = 760
# constants and data
g = 9.8          # m/s^2
mball = 0.03     # kg
Lo = 0.26        # m
ks = 1.8          # N/m
deltat = 0.01    # s

# objects (origin is at ceiling)
ceiling = box(pos=vector(0,0,0), length=0.2, height=0.01,
               width=0.2)
ball = sphere(pos=vector(0,-0.3,0),radius=0.025,
              color=color.orange)
spring = helix(pos=ceiling.pos, axis=ball.pos-ceiling.pos,
               color=color.cyan,thickness=0.003,coils=40,
               radius=0.010)

# initial values
pball = mball * vector(0,0,0)      # kg m/s
Fgrav = mball * g * vector(0,-1,0) # N
t = 0

# improve the display
scene.autoscale = False           # turn off automatic camera zoom
scene.center = vector(0,-Lo,0) # move camera down
scene.waitfor('click')           # wait for a mouse click

# initial calculation loop
# calculation loop
while t < 10:
    rate(100)
    # we need the stretch
    s = mag(ball.pos) - Lo
    # we need the spring force
    Fspring = ks * s * -norm(spring.axis)
    Fnet = Fgrav + Fspring
    pball = pball + Fnet * deltat
    ball.pos = ball.pos + (pball / mball) * deltat
    spring.axis = ball.pos - ceiling.pos
    t = t + deltat
\end{webpythonblock}

```



Web VPython Program 1: Example With QR Code
<https://glowsheet.org/#/user/heafnerj/folder/mandidemo/program/mandidemo>

```
1  Web VPython 3.2
2
3  scene.width = 400
4  scene.height = 760
5  # constants and data
6  g = 9.8          # m/s^2
7  mball = 0.03    # kg
8  Lo = 0.26       # m
9  ks = 1.8        # N/m
10 deltat = 0.01   # s
11
12 # objects (origin is at ceiling)
13 ceiling = box(pos=vector(0,0,0), length=0.2, height=0.01,
14                 width=0.2)
15 ball = sphere(pos=vector(0,-0.3,0), radius=0.025,
16                 color=color.orange)
17 spring = helix(pos=ceiling.pos, axis=ball.pos-ceiling.pos,
18                  color=color.cyan, thickness=0.003, coils=40,
19                  radius=0.010)
20
21 # initial values
22 pball = mball * vector(0,0,0)      # kg m/s
23 Fgrav = mball * g * vector(0,-1,0) # N
24 t = 0
25
26 # improve the display
27 scene.autoscale = False           # turn off automatic camera zoom
28 scene.center = vector(0,-Lo,0)    # move camera down
29 scene.waitfor('click')           # wait for a mouse click
30
31 # initial calculation loop
32 # calculation loop
33 while t < 10:
34     rate(100)
35     # we need the stretch
36     s = mag(ball.pos) - Lo
37     # we need the spring force
38     Fspring = ks * s * -norm(spring.axis)
39     Fnet = Fgrav + Fspring
40     pball = pball + Fnet * deltat
41     ball.pos = ball.pos + (pball / mball) * deltat
42     spring.axis = ball.pos - ceiling.pos
43     t = t + deltat
```

Here is how one would reference this program elsewhere. Notice the references are numbered sequentially within the document.

\WebVPython{} program \ref{gs:1} is nice.
It's called \nameref{gs:1} and is on page \pageref{gs:1}.

Web VPython program 1 is nice. It's called [Example With QR Code](#) and is on page 64.

```

\begin{webpythonblock*}
(glowscript.org/#/user/heafnerj/folder/mandidemo/program/mandidemo)
{Example Without QR Code}
Web VPython 3.2

scene.width = 400
scene.height = 760
# constants and data
g = 9.8          # m/s^2
mball = 0.03     # kg
Lo = 0.26        # m
ks = 1.8         # N/m
deltat = 0.01    # s

# objects (origin is at ceiling)
ceiling = box(pos=vector(0,0,0), length=0.2, height=0.01,
               width=0.2)
ball = sphere(pos=vector(0,-0.3,0),radius=0.025,
              color=color.orange)
spring = helix(pos=ceiling.pos, axis=ball.pos-ceiling.pos,
               color=color.cyan,thickness=0.003,coils=40,
               radius=0.010)

# initial values
pball = mball * vector(0,0,0)      # kg m/s
Fgrav = mball * g * vector(0,-1,0) # N
t = 0

# improve the display
scene.autoscale = False           # turn off automatic camera zoom
scene.center = vector(0,-Lo,0) # move camera down
scene.waitfor('click')           # wait for a mouse click

# initial calculation loop
# calculation loop
while t < 10:
    rate(100)
    # we need the stretch
    s = mag(ball.pos) - Lo
    # we need the spring force
    Fspring = ks * s * -norm(spring.axis)
    Fnet = Fgrav + Fspring
    pball = pball + Fnet * deltat
    ball.pos = ball.pos + (pball / mball) * deltat
    spring.axis = ball.pos - ceiling.pos
    t = t + deltat
\end{webpythonblock*}

```

Web VPython Program 2: Example Without QR Code
<https://glowscrip.org/#/user/heafnerj/folder/mandidemo/program/mandidemo>

```
1  Web VPython 3.2
2
3  scene.width = 400
4  scene.height = 760
5  # constants and data
6  g = 9.8          # m/s^2
7  mball = 0.03    # kg
8  Lo = 0.26       # m
9  ks = 1.8        # N/m
10  deltat = 0.01  # s
11
12  # objects (origin is at ceiling)
13  ceiling = box(pos=vector(0,0,0), length=0.2, height=0.01,
14      width=0.2)
15  ball = sphere(pos=vector(0,-0.3,0), radius=0.025,
16      color=color.orange)
17  spring = helix(pos=ceiling.pos, axis=ball.pos-ceiling.pos,
18      color=color.cyan, thickness=0.003, coils=40,
19      radius=0.010)
20
21  # initial values
22  pball = mball * vector(0,0,0)      # kg m/s
23  Fgrav = mball * g * vector(0,-1,0) # N
24  t = 0
25
26  # improve the display
27  scene.autoscale = False           # turn off automatic camera zoom
28  scene.center = vector(0,-Lo,0)    # move camera down
29  scene.waitfor('click')           # wait for a mouse click
30
31  # initial calculation loop
32  # calculation loop
33  while t < 10:
34      rate(100)
35      # we need the stretch
36      s = mag(ball.pos) - Lo
37      # we need the spring force
38      Fspring = ks * s * -norm(spring.axis)
39      Fnet = Fgrav + Fspring
40      pball = pball + Fnet * deltat
41      ball.pos = ball.pos + (pball / mball) * deltat
42      spring.axis = ball.pos - ceiling.pos
43      t = t + deltat
```

\WebVPython{} program \ref{gs:2} is nice.
It's called \nameref{gs:2} and is on page \pageref{gs:2}.

Web VPython program 2 is nice. It's called [Example Without QR Code](#) and is on page 67.

7.6 The vpythonfile Command

U 2023-08-01

\vpythonfile[*options*] (*link*) {*file*} {*caption*}

Command to load and typeset a VPython program, read from local file {*file*}. Clicking anywhere in the code window (between the black horizontal bars) or on the URL will open the link in the default browser. A caption is mandatory, and a label is internally generated. The listing always begins on a new page. A URL shortening utility is recommended to keep the URL from getting unruly especially if it generates an overfull box error. For convenience, <https://> is automatically prepended to the URL and can be omitted. The default URL is that of the VPython home page.

```
\vpythonfile{vdemo.py}{A VPython{} Program}
```

VPython Program 1: A VPython Program

```
1  from vpython import *
2
3  scene.width = 400
4  scene.height = 760
5  # constants and data
6  g = 9.8      # m/s^2
7  mball = 0.03 # kg
8  Lo = 0.26    # m
9  ks = 1.8     # N/m
10 deltat = 0.01 # s
11
12 # objects (origin is at ceiling)
13 ceiling = box(pos=vector(0,0,0), length=0.2, height=0.01,
14                 width=0.2)
15 ball = sphere(pos=vector(0,-0.3,0), radius=0.025,
16                 color=color.orange)
17 spring = helix(pos=ceiling.pos, axis=ball.pos-ceiling.pos,
18                  color=color.cyan, thickness=0.003, coils=40,
19                  radius=0.010)
20
21 # initial values
22 pball = mball * vector(0,0,0)      # kg m/s
23 Fgrav = mball * g * vector(0,-1,0) # N
24 t = 0
25
26 # improve the display
27 scene.autoscale = False           # turn off automatic camera zoom
28 scene.center = vector(0,-Lo,0)    # move camera down
29 scene.waitfor('click')           # wait for a mouse click
30
31 # initial calculation loop
32 # calculation loop
33 while t < 10:
34     rate(100)
35     # we need the stretch
36     s = mag(ball.pos) - Lo
37     # we need the spring force
38     Fspring = ks * s * -norm(spring.axis)
39     Fnet = Fgrav + Fspring
40     pball = pball + Fnet * deltat
41     ball.pos = ball.pos + (pball / mball) * deltat
42     spring.axis = ball.pos - ceiling.pos
43     t = t + deltat
```

\VPython{} program \ref{vp:1} is nice.
It's called \nameref{vp:1} and is on page \pageref{vp:1}.

VPython program 1 is nice. It's called [A VPython Program](#) and is on page [69](#).

7.7 The `webvpythoninline` and `vpythoninline` Commands

U 2021-02-26

`\webvpythoninline{< Web VPython code>}`

U 2021-02-26

`\vpythoninline{< VPython code>}`

Typesets a small, in-line snippet of code. The snippet should be less than one line long.

`\WebVPython{} programs begin with \webvpythoninline{Web VPython 3.2}.`

Web VPython programs begin with `Web VPython 3.2`.

`\VPython{} programs begin with \vpythoninline{from vpython import *}.`

VPython programs begin with `from vpython import *`.

7.8 **mandistudent** Source Code

Define the package version and date for global use, exploiting the fact that in a .sty file there is now no need for `\makeatletter` and `\makeatother`. This simplifies defining internal commands, with @ in the name, that are not for the user to know about.

```
1 \def\mandistudent@version{3.2.2}
2 \def\mandistudent@date{2024-02-27}
3 \NeedsTeXFormat{LaTeX2e}[2020-02-02]
4 \DeclareRelease{v3.2.2}{2024-02-27}{\mandistudent.sty}
5 \DeclareCurrentRelease{v\mandistudent@version}{\mandistudent@date}
6 \ProvidesPackage{mandistudent}
7   [\mandistudent@date\space v\mandistudent@version\space Macros for introductory physics]
```

Define a convenient package version command.

```
8 \newcommand*{\mandistudentversion}{v\mandistudent@version\space dated \mandistudent@date}
```

Load third party packages, documenting why each one is needed.

AMS goodness. Don't load `amssymb` or `amsfonts`.

```
9 \RequirePackage{amsmath}
```

We need `enumitem` for the `physicsproblem` environment.

`BEAMER` is not compatible with `enumitem` so if `BEAMER` is loaded certain commands are not defined.

```
10 \IfClassLoadedTF{beamer}%
11   {}%
12   {}%
13   \RequirePackage[inline]{enumitem}%
14 }
```

We need `eso-pic` for `\hilite`.

```
15 \RequirePackage{eso-pic}
```

We need `esvect` for nice vector arrows, style g.

```
16 \RequirePackage[g]{esvect}
```

We need `pgfplots` for a key-value interface.

```
17 \RequirePackage{pgfplots}
```

We need `iftex` so we can require `LuaLaTeX`.

```
18 \RequirePackage{iftex}
```

We need `makebox` for consistent `\direct` notation.

```
19 \RequirePackage{makebox}
```

We need `mandi` to load `mathtools` and `unicode-math`.

```
20 \IfPackageLoadedTF{mandi}%
21   {}%
22   {}%
23   \RequirePackage{mandi}%
24 }
```

We need `nicematrix` for column and row vectors.

```
25 \RequirePackage{nicematrix}
```

We need `qrcode` for QR codes in `webpythonblock`.

```
26 \RequirePackage{qrcode}
```

Set the default size for QR codes.

```
27 \qrset{height=1.5cm}
```

We need `tcolorbox` for program listings.

```
28 \RequirePackage[most]{tcolorbox}
```

We need `tensor` for index notation.

```
29 \RequirePackage{tensor}
30 %
31 % We need \pkg{tikz} for \hlite...
32 %
33 \RequirePackage{tikz}
34 \usetikzlibrary{shapes,fit,tikzmark}
```

Load `xparse` if necessary.

```
35 \IfFormatAtLeastTF{2020-10-01}
36   {}%
37   {\RequirePackage{xparse}}%
```

Always load `hyperref` last if possible.

```
38 \RequirePackage{hyperref}
```

We require the `LuaLaTeX` engine.

```
39 \RequireLuaTeX
```

Set up the fonts to be consistent with ISO 80000-2 notation. The `unicode-math` package loads the `fontspec` and `xparse` packages. Note that `xparse` is now part of the $\text{\LaTeX} 2_{\varepsilon}$ kernel. Because `unicode-math` is required, all documents using `mandi` must be compiled with an engine that supports Unicode, and I recommend `LuaLaTeX`.

```
40 \unimathsetup{math-style=ISO}
```

Use normal math letters from Latin Modern Math for familiarity with textbooks. This gives a better J.

```
41 \setmathfont[Scale=MatchLowercase]
42   {Latin Modern Math}
```

Borrow from TeX Gyre DejaVu Math for vectors and tensors to get single-storey lowercase g.

```
43 \setmathfont[Scale=MatchLowercase,range={sfit/{latin},bfsfit/{latin}}]
44   {TeX Gyre DejaVu Math}
```

Borrow from TeX Gyre DejaVu Math to get single-storey lowercase g.

```
45 \setmathfont[Scale=MatchLowercase,range={sfup/{latin},bfsfup/{latin}}]
46   {TeX Gyre DejaVu Math}
```

Borrow `mathscr` and `mathbfscr` from XITS Math.

See <https://tex.stackexchange.com/a/120073/218142>.

```
47 \setmathfont[Scale=MatchLowercase,range={\mathscr,\mathbfscr}]{XITS Math}
```

Get original and bold `mathcal` fonts.

See <https://tex.stackexchange.com/a/21742/218142>.

```
48 \setmathfont[Scale=MatchLowercase,range={\mathcal,\mathbfcal},StylisticSet=1]{XITS Math}
```

Borrow Greek `sfup` and `sfit` letters from STIX Two Math. Since this isn't officially supported in `unicode-math` we have to manually set this up.

```
49 \setmathfont[Scale=MatchLowercase,range={"E17C-"E1F6}]{STIX Two Math}
50 \newfontfamily{\symsfgreek}{STIX Two Math}
```

I don't understand why `\text{...}` is necessary.

```
51 \newcommand{\symsfupalpha}{\text{\symsfgreek{^\wedge e196}}}
52 \newcommand{\symsfupbeta}{\text{\symsfgreek{^\wedge e197}}}
53 \newcommand{\symsfupgamma}{\text{\symsfgreek{^\wedge e198}}}
54 \newcommand{\symsfupdelta}{\text{\symsfgreek{^\wedge e199}}}
55 \newcommand{\symsfupepsilon}{\text{\symsfgreek{^\wedge e1af}}}
56 \newcommand{\symsfupvarepsilon}{\text{\symsfgreek{^\wedge e19a}}}
57 \newcommand{\symsfupzeta}{\text{\symsfgreek{^\wedge e19b}}}
58 \newcommand{\symsfupeta}{\text{\symsfgreek{^\wedge e19c}}}
```

```

59 \newcommand{\symsfuptheta}{\text{\symsfgreek{^~^~e19d}}}
60 \newcommand{\symsfupvartheta}{\text{\symsfgreek{^~^~e1b0}}}
61 \newcommand{\symsfupiota}{\text{\symsfgreek{^~^~e19e}}}
62 \newcommand{\symsfupkappa}{\text{\symsfgreek{^~^~e19f}}}
63 \newcommand{\symsfuplambda}{\text{\symsfgreek{^~^~e1a0}}}
64 \newcommand{\symsfupmu}{\text{\symsfgreek{^~^~e1a1}}}
65 \newcommand{\symsfupnu}{\text{\symsfgreek{^~^~e1a2}}}
66 \newcommand{\symsfupxi}{\text{\symsfgreek{^~^~e1a3}}}
67 \newcommand{\symsfupomicron}{\text{\symsfgreek{^~^~e1a4}}}
68 \newcommand{\symsfuppi}{\text{\symsfgreek{^~^~e1a5}}}
69 \newcommand{\symsfupvarpi}{\text{\symsfgreek{^~^~e1b3}}}
70 \newcommand{\symsfuprho}{\text{\symsfgreek{^~^~e1a6}}}
71 \newcommand{\symsfupvarrho}{\text{\symsfgreek{^~^~e1b2}}}
72 \newcommand{\symsfupsigma}{\text{\symsfgreek{^~^~e1a8}}}
73 \newcommand{\symsfupvarsigma}{\text{\symsfgreek{^~^~e1a7}}}
74 \newcommand{\symsfuptau}{\text{\symsfgreek{^~^~e1a9}}}
75 \newcommand{\symsfupupsilon}{\text{\symsfgreek{^~^~e1aa}}}
76 \newcommand{\symsfupphi}{\text{\symsfgreek{^~^~e1b1}}}
77 \newcommand{\symsfupvarphi}{\text{\symsfgreek{^~^~e1ab}}}
78 \newcommand{\symsfupchi}{\text{\symsfgreek{^~^~e1ac}}}
79 \newcommand{\symsfuppsi}{\text{\symsfgreek{^~^~e1ad}}}
80 \newcommand{\symsfupomega}{\text{\symsfgreek{^~^~e1ae}}}
81 \newcommand{\symsfupDelta}{\text{\symsfgreek{^~^~e180}}}
82 \newcommand{\symsfupGamma}{\text{\symsfgreek{^~^~e17f}}}
83 \newcommand{\symsfupTheta}{\text{\symsfgreek{^~^~e18e}}}
84 \newcommand{\symsfupLambda}{\text{\symsfgreek{^~^~e187}}}
85 \newcommand{\symsfupXi}{\text{\symsfgreek{^~^~e18a}}}
86 \newcommand{\symsfupPi}{\text{\symsfgreek{^~^~e18c}}}
87 \newcommand{\symsfupSigma}{\text{\symsfgreek{^~^~e18f}}}
88 \newcommand{\symsfupUpsilon}{\text{\symsfgreek{^~^~e191}}}
89 \newcommand{\symsfupPhi}{\text{\symsfgreek{^~^~e192}}}
90 \newcommand{\symsfupPsi}{\text{\symsfgreek{^~^~e194}}}
91 \newcommand{\symsfupOmega}{\text{\symsfgreek{^~^~e195}}}
92 \newcommand{\symsfitalpha}{\text{\symsfgreek{^~^~e1d8}}}
93 \newcommand{\symsfitbeta}{\text{\symsfgreek{^~^~e1d9}}}
94 \newcommand{\symsfitgamma}{\text{\symsfgreek{^~^~e1da}}}
95 \newcommand{\symsfitdelta}{\text{\symsfgreek{^~^~e1db}}}
96 \newcommand{\symsfitepsilon}{\text{\symsfgreek{^~^~e1f1}}}
97 \newcommand{\symsfitvarepsilon}{\text{\symsfgreek{^~^~e1dc}}}
98 \newcommand{\symsfitzeta}{\text{\symsfgreek{^~^~e1dd}}}
99 \newcommand{\symsfiteta}{\text{\symsfgreek{^~^~e1de}}}
100 \newcommand{\symsfittheta}{\text{\symsfgreek{^~^~e1df}}}
101 \newcommand{\symsfitvartheta}{\text{\symsfgreek{^~^~e1f2}}}
102 \newcommand{\symsfitiota}{\text{\symsfgreek{^~^~e1e0}}}
103 \newcommand{\symsfitkappa}{\text{\symsfgreek{^~^~e1e1}}}
104 \newcommand{\symsfitlambda}{\text{\symsfgreek{^~^~e1e2}}}
105 \newcommand{\symsfitmu}{\text{\symsfgreek{^~^~e1e3}}}
106 \newcommand{\symsfitnu}{\text{\symsfgreek{^~^~e1e4}}}
107 \newcommand{\symsfitxi}{\text{\symsfgreek{^~^~e1e5}}}
108 \newcommand{\symsfitomicron}{\text{\symsfgreek{^~^~e1e6}}}
109 \newcommand{\symsfitpi}{\text{\symsfgreek{^~^~e1e7}}}
110 \newcommand{\symsfitvarpi}{\text{\symsfgreek{^~^~e1e5}}}
111 \newcommand{\symsfirrho}{\text{\symsfgreek{^~^~e1e8}}}
112 \newcommand{\symsfitvarrho}{\text{\symsfgreek{^~^~e1f4}}}
113 \newcommand{\symsfitsigma}{\text{\symsfgreek{^~^~e1ea}}}
114 \newcommand{\symsfitvarsigma}{\text{\symsfgreek{^~^~e1e9}}}
115 \newcommand{\symsfittau}{\text{\symsfgreek{^~^~e1eb}}}
116 \newcommand{\symsfitupsilon}{\text{\symsfgreek{^~^~e1ec}}}
117 \newcommand{\symsfitphi}{\text{\symsfgreek{^~^~e1f3}}}

```

```

118 \newcommand{\symsfitvarphi}{\text{\symsfgreek{^~^e1ed}}}
119 \newcommand{\symsfitchi}{\text{\symsfgreek{^~^e1ee}}}
120 \newcommand{\symsfitpsi}{\text{\symsfgreek{^~^e1ef}}}
121 \newcommand{\symsfitomega}{\text{\symsfgreek{^~^e1f0}}}
122 \newcommand{\symsfitDelta}{\text{\symsfgreek{^~^e1c2}}}
123 \newcommand{\symsfitGamma}{\text{\symsfgreek{^~^e1c1}}}
124 \newcommand{\symsfitTheta}{\text{\symsfgreek{^~^e1d0}}}
125 \newcommand{\symsfitLambda}{\text{\symsfgreek{^~^e1c9}}}
126 \newcommand{\symsfitXi}{\text{\symsfgreek{^~^e1cc}}}
127 \newcommand{\symsfitPi}{\text{\symsfgreek{^~^e1ce}}}
128 \newcommand{\symsfitSigma}{\text{\symsfgreek{^~^e1d1}}}
129 \newcommand{\symsfitUpsilon}{\text{\symsfgreek{^~^e1d3}}}
130 \newcommand{\symsfitPhi}{\text{\symsfgreek{^~^e1d4}}}
131 \newcommand{\symsfitPsi}{\text{\symsfgreek{^~^e1d6}}}
132 \newcommand{\symsfitOmega}{\text{\symsfgreek{^~^e1d7}}}

```

Tweak the `esvect` package fonts to get the correct font size.

See <https://tex.stackexchange.com/a/566676>.

```

133 \DeclareFontFamily{U}{esvect}{}%
134 \DeclareFontShape{U}{esvect}{m}{n}{%
135   <-5.5> vect5
136   <5.5-6.5> vect6
137   <6.5-7.5> vect7
138   <7.5-8.5> vect8
139   <8.5-9.5> vect9
140   <9.5-> vect10
141 }{}%

```

Write a banner to the console showing the options in use.

```

142 \typeout{}%
143 \typeout{mandistudent: You are using mandistudent \mandistudentversion.}%
144 \typeout{mandistudent: This package requires LuaLaTeX.}%
145 \typeout{mandistudent: This package changes the default math font(s).}%
146 \typeout{mandistudent: This package redefines the \protect\vec\space command.}%
147 \IfClassLoadedTF{beamer}%
148 {%
149   \typeout{mandistudent: BEAMER detected. Certain commands will not be defined.}%
150 }%
151 {}%
152 \typeout{}%

```

A better, intelligent coordinate-free `\vecP.52` command. Note the use of the `e{_~}` type of optional argument. This accounts for much of the flexibility and power of this command. Also note the use of the TeX primitives `\sb{}` and `\sp{}`. Why doesn't it work when I put spaces around #3 or #4? Because outside of `\ExplSyntaxOn... \ExplSyntaxOff`, the `_` character has a different catcode and is treated as a mathematical entity.

See <https://tex.stackexchange.com/q/554706/218142>.

See also <https://tex.stackexchange.com/a/531037/218142>.

```

153 \RenewDocumentCommand{\vec}{ s m e{_~} }%
154 {%
155   \IfBooleanTF{#1}%
156   {%
157     \vv{#2}%
158     \IfValueT{#4}{%
159       \sp{\, ,#4\phantom{\smash[t]{\big|}}}%
160     }%
161   }%
162   \symbfit{#2}%
163   \IfValueT{#4}{%
164     \sp{#4\phantom{\smash[t]{\big|}}}%

```

```

165      }%
166      \IfValueT{#3}{%
167      { \sb{#3\phantom{\smash[b]{}}}}}
168  }%

```

A command for the direction of a vector. We use a slight tweak to get uniform hats that requires the `makebox` package.
See <https://tex.stackexchange.com/a/391204/218142>.

```

169 \NewDocumentCommand{\dirvec}{ s m e{_} }{%
170   {%
171     \widehat{%
172       {%
173         \makebox*{(\w\!)}{%
174           {%
175             \ensuremath{%
176               \IfBooleanTF{#1}{%
177                 {%
178                   \#2%
179                 }%
180                 {%
181                   \symbfit{#2}%
182                 }%
183               }%
184             }%
185           }%
186         \IfValueT{#3}{%
187           { \sb{#3\phantom{\smash[b]{}}}}}
188         \IfValueT{#4}{%
189           { \sp{, #4\phantom{\smash[t]{}}\big|}}}
190       }%
191     }%
192   }%
193   \IfBooleanTF{#1}{%
194     {\vv{0}}%
195     {\symbup{0}}%
196   }%

```

The zero vector.

```

191 \NewDocumentCommand{\zerovec}{ s }{%
192   {%
193     \IfBooleanTF{#1}{%
194       {\vv{0}}%
195       {\symbup{0}}%
196     }%

```

Notation for column and row vectors.

See <https://tex.stackexchange.com/a/39054/218142>.

```

197 \ExplSyntaxOn
198 \NewDocumentCommand{\colvec}{ O{,} m }{%
199   {%
200     \__mandi_vector_main:n{nnnn}{p}{\backslash}{#1}{#2}%
201   }%
202 \NewDocumentCommand{\rowvec}{ O{,} m }{%
203   {%
204     \__mandi_vector_main:n{nnnn}{p}{\&}{#1}{#2}%
205   }%
206 \seq_new:N \l__mandi_vector_arg_seq
207 \cs_new_protected:Npn \__mandi_vector_main:n{nnnn}{#1#2#3#4}{%
208   {%
209     \seq_set_split:Nnn \l__mandi_vector_arg_seq{#3}{#4}%
210     \begin{#1NiceMatrix}[r]%
211       \seq_use:Nnnn \l__mandi_vector_arg_seq{#2}{#2}{#2}%
212     \end{#1NiceMatrix}%
213   }%
214 \ExplSyntaxOff

```

Students always need this symbol.

```
215 \NewDocumentCommand{\changein}{\Delta}
```

Intelligent delimiters provided via the `mathtools` package. Use the starred variants for fractions. You can supply optional sizes. Note that default placeholders are used when the argument is empty.

```
216 \DeclarePairedDelimiterX{\doublebars}[1]{\lVert}{\rVert}{\ifblank{#1}{\cdot}{\cdotp\cdotp\cdotp}{}{#1}}
217 \DeclarePairedDelimiterX{\singlebars}[1]{\lvert}{\rvert}{\ifblank{#1}{\cdot}{\cdotp\cdotp\cdotp}{}{#1}}
218 \DeclarePairedDelimiterX{\anglebrackets}[1]{\langle}{\rangle}{\ifblank{#1}{\cdot}{\cdotp\cdotp\cdotp}{}{#1}}
219 \DeclarePairedDelimiterX{\parentheses}[1]{(}{)}{\ifblank{#1}{\cdot}{\cdotp\cdotp\cdotp}{}{#1}}
220 \DeclarePairedDelimiterX{\squarebrackets}[1]{[}{]}{\ifblank{#1}{\cdot}{\cdotp\cdotp\cdotp}{}{#1}}
221 \DeclarePairedDelimiterX{\curlybraces}[1]{\{}{\}}{\ifblank{#1}{\cdot}{\cdotp\cdotp\cdotp}{}{#1}}
```

Some semantic aliases. Because of the way `\vecP.52` and `\dirvecP.52` are defined, I reluctantly decided not to implement a `\magvec` command. It would require accounting for too many options. So `\magnitudeP.55` is the new solution.

```
222 \NewDocumentCommand{\magnitude}{\doublebars}
223 \NewDocumentCommand{\norm}{\doublebars}
224 \NewDocumentCommand{\absolutevalue}{\singlebars}
```

Commands for two important geometric relationships. These are meant mainly to be subscripts.

```
225 \NewDocumentCommand{\parallelto}{\doublebars}%
226   {%
227     \mkern3mu\vphantom{\perp}\vrule depth 0pt\mkern2mu\vrule depth 0pt\mkern3mu%
228   }%
229 \NewDocumentCommand{\perpendicularto}{\perp}
```

An environment for problem statements. The starred variant gives in-line lists. These are not defined if BEAMER is loaded.

```
230 \IfClassLoadedTF{beamer}%
231   {}%
232   {}%
233   \NewDocumentEnvironment{physicsproblem}{ m }%
234   {%
235     \newpage%
236     \section*{#1}%
237     \newlist{parts}{enumerate}{2}%
238     \setlist[parts]{label=\bfseries(\alph*)}%
239   }%
240   {}%
241 \NewDocumentEnvironment{physicsproblem*}{ m }%
242   {%
243     \newpage%
244     \section*{#1}%
245     \newlist{parts}{enumerate*}{2}%
246     \setlist[parts]{label=\bfseries(\alph*)}%
247   }%
248   {}%
249 \NewDocumentCommand{\problempart}{\item}%
250 }%
```

An environment for problem solutions. Equation numbering is consecutive through the document.

```
251 \NewDocumentEnvironment{physicssolution}{ +b }%
252   {}%
253   \begin{align}
254     #1
255   \end{align}%
256 }%
257 {}%
258 \NewDocumentEnvironment{physicssolution*}{ +b }%
259   {}%
260   \begin{align*}
```

```

261      #1
262      \end{align*}
263  }%
264 {}%

```

See <https://tex.stackexchange.com/q/570223/218142>.

```

265 \NewDocumentCommand{\reason}{ O{4cm} m }%
266   {%
267     &&\begin{minipage}{#1}\raggedright\small #2\end{minipage}%
268   }%

```

Command for highlighting parts of, or entire, mathematical expressions.
This command is not defined if BEAMER is loaded.

See <https://texexample.net/tikz/examples/beamer-arrows/>.

See also <https://tex.stackexchange.com/a/406084/218142>.

See also <https://tex.stackexchange.com/a/570858/218142>.

See also <https://tex.stackexchange.com/a/570789/218142>.

See also <https://tex.stackexchange.com/a/79659/218142>.

See also <https://tex.stackexchange.com/q/375032/218142>.

See also <https://tex.stackexchange.com/a/571744/218142>

```

269 \newcounter{tikzhighlightnode}
270 \NewDocumentCommand{\hilite}{ O{magenta!60} m O{rectangle} }%
271   {%
272     \stepcounter{tikzhighlightnode}%
273     \tikzmarknode[highlighted-node-\number\value{tikzhighlightnode}]{#2}%
274     \edef\temp{%
275       \noexpand\AddToShipoutPictureBG{%
276         \noexpand\begin{tikzpicture}[overlay,remember picture]%
277         \noexpand\iftikzmarkoncurrentpage{highlighted-node-\number\value{tikzhighlightnode}}{%
278           \noexpand\node[inner sep=1.0pt,fill=#1,#3,fit=(highlighted-node-\number\value{tikzhighlightnode})]{};%
279         \noexpand\fi
280         \noexpand\end{tikzpicture}%
281       }%
282     }%
283     \temp%
284   }%

```

A simplified command for importing images.

See <https://tex.stackexchange.com/a/614478/218142>.

```

285 \NewDocumentCommand{\image}{ O{scale=1} m m m }%
286   {%
287     \par
288     \begin{figure}[ht!]
289       \centering%
290       \includegraphics[#1]{#2}%
291       \caption{#3}%
292       \label{#4}%
293     \end{figure}%
294     \par
295   }%

```

Intelligent commands for typesetting vector and tensor symbols and components suitable for use with both coordinate-free and index notations. Use starred form for index notation, unstarred form for coordinate-free.

Consider renaming these to `\vectorsym` and `\tensorsym`.

```

296 \NewDocumentCommand{\veccomp}{ s m }%
297   {%
298     \IfBooleanTF{#1}%
299       {%

```

```

300      \symnormal{#2}%
301  }%
302  {%
303      \symbfit{#2}%
304  }%
305 }%
306 \NewDocumentCommand{\tencomp}{ s m }%
307 {%
308     \IfBooleanTF{#1}%
309     {%
310         \symsfit{#2}%
311     }%
312     {%
313         \symbfsfit{#2}%
314     }%
315 }%

```

Command to typeset tensor valence.

```

316 \NewDocumentCommand{\valence}{ s m m }%
317 {%
318     \IfBooleanTF{#1}%
319     {%
320         (#2,#3)%
321     }%
322     {%
323         \binom{#2}{#3}%
324     }%
325 }%

```

Intelligent notation for contraction on pairs of slots.

```

326 \NewDocumentCommand{\contraction}{ s m }%
327 {%
328     \IfBooleanTF{#1}%
329     {%
330         \mathsf{C}%
331     }%
332     {%
333         \mathbb{C}%
334     }%
335     _{#2}%
336 }%

```

Intelligent slot command for coordinate-free tensor notation. `d[]` must be used because of the way consecutive optional arguments are handled. See `xparse` docs for details.

```

337 \NewDocumentCommand{\slot}{ s d[] }%
338 {%
339     \IfBooleanTF{#1}%
340     {%
341         \IfValueTF{#2}%

```

Insert a vector, but don't show the slot.

```

342     {%
343         \smash{\makebox[1.5em]{\ensuremath{#2}}}%
344     }%

```

No vector, no slot.

```

345     {%
346         \smash{\makebox[1.5em]{\ensuremath{}}}%
347     }%

```

```

348      }%
349      {%
350          \IfValueTF{#2}{%

```

Insert a vector and show the slot.

```

351      {%
352          \underline{\smash{\makebox[1.5em]{\ensuremath{#2}}}}%
353      }%

```

No vector; just show the slot.

```

354      {%
355          \underline{\smash{\makebox[1.5em]{\enspace}}}%
356      }%
357      {%
358  }%

```

Intelligent differential (exterior derivative) operator.

```

359 \NewDocumentCommand{\df}{ s }{%
360     {%
361         \mathop{}!%
362         \IfBooleanTF{#1}{%
363             {%
364                 \symbfsup{d}%
365             }%
366             {%
367                 \symsup{d}%
368             }%
369     }%

```

Here is a clever way to color digits in program listings thanks to Ulrike Fischer.

See <https://tex.stackexchange.com/a/570717/218142>.

```

370 \directlua{%
371     luatfload.add_colorscheme("colordigits",
372     {[["8000FF"]] = {"one", "two", "three", "four", "five", "six", "seven", "eight", "nine", "zero"}})
373 }%
374 \newfontfamily\colordigits{DejaVuSansMono}[RawFeature={color=colordigits}]

```

Set up a color scheme and a new code environment for listings. The new colors are more restful on the eye. All listing commands now use `tcolorbox`.

See <https://tex.stackexchange.com/a/529421/218142>.

We set a new font for listings and some new colors (background gray, gray, green, orange, peach, pearl, and plum).

```

375 \newfontfamily{\gsfontfamily}{DejaVuSansMono}
376 \definecolor{gsbggray}    {rgb}{0.90,0.90,0.90}
377 \definecolor{gsgray}     {rgb}{0.30,0.30,0.30}
378 \definecolor{gsgreen}    {rgb}{0.00,0.60,0.00}
379 \definecolor{gsorange}   {rgb}{0.80,0.45,0.12}
380 \definecolor{gspeach}   {rgb}{1.00,0.90,0.71}
381 \definecolor{gspearl}   {rgb}{0.94,0.92,0.84}
382 \definecolor{gsplum}    {rgb}{0.74,0.46,0.70}
383 \lstdefinestyle{vpython}{%
384     {%
385         backgroundcolor=\color{gsbggray},%           % background color
386         basicstyle=\colordigits\footnotesize,%       % default style
387         breakatwhitespace=true%,                   % break at whitespace
388         breaklines=true,%                        % break long lines
389         captionpos=b,%                         % position caption
390         classoffset=1,%                        % STILL DON'T UNDERSTAND THIS
391         commentstyle=\color{gsgray},%            % font for comments
392         deletekeywords=[print],%                % delete keywords from the given language

```

```

393    emph={self,cls,@classmethod,@property},%          % words to emphasize
394    emphstyle=\color{gsorange}\itshape,%              % font for emphasis
395    escapeinside={(*@}{@*)},%                      % add LaTeX within your code
396    frame=tb,%                                      % frame style
397    framerule=2.0pt,%                             % frame thickness
398    framexleftmargin=5pt,%                         % extra frame left margin
399    %identifierstyle=\sffamily,%                   % style for identifiers
400    keywordstyle=\sfssfontfamily\color{gsplum},%     % color for keywords
401    language=Python,%                            % select language
402    linewidth=\linewidth,%                       % width of listings
403    morekeywords={%                                % VPython/Web VPython specific keywords
404        __future__,abs,acos,align,ambient,angle,append,append_to_caption,%  

405        append_to_title,arange,arrow,asin,astuple,atan,atan2,attach_arrow,%  

406        attach_trail,autoscale,axis,background,billboard,bind,black,blue,border,%  

407        bounding_box,box,bumpaxis,bumpmap,bumpmaps,camera,canvas,caption,capture,%  

408        ceil,center,clear,clear_trail,click,clone,CoffeeScript,coils,color,combin,%  

409        comp,compound,cone,convex,cos,cross,curve,cyan,cylinder,data,degrees,del,%  

410        delete,depth,descender,diff_angle,digits,division,dot,draw_complete,%  

411        ellipsoid,emissive,end_face_color>equals,explod,extrusion,faces,factorial,%  

412        False,floor,follow,font,format,forward,fov,frame,gcurve,gdisplay,gdots,%  

413        get_library,get_selected,ghbars,global,GlowScript,graph,graphs,green,gvbars,%  

414        hat,headlength,headwidth,height,helix,hsv_to_rgb,index,interval,keydown,%  

415        keyup,label,length,lights,line,linecolor,linewidth,logx,logy,lower_left,%  

416        lower_right,mag,mag2,magenta,make_trail,marker_color,markers,material,%  

417        max,min,mousedown,mousemove,mouseup,newball,norm,normal,objects,%  

418        offset,one,opacity,orange,origin,path,pause,pi,pixel_to_world,pixels,plot,%  

419        points,pos,pow,pps,print,print_function,print_options,proj,purple,pyramid,%  

420        quad,radians,radius,random,rate,ray,read_local_file,readonly,red,redraw,%  

421        retain,rgb_to_hsv,ring,rotate,round,scene,scroll,shaftwidth,shape,shapes,%  

422        shininess,show_end_face,show_start_face,sign,sin,size,size_units,sleep,%  

423        smooth,space,sphere,sqrt,start,start_face_color,stop,tan,text,txtpos,%  

424        texture,textures,thickness,title,trail_color,trail_object,trail_radius,%  

425        trail_type,triangle,trigger,True,twist,unbind,up,upper_left,upper_right,%  

426        userpan,userspin,userzoom,vec,vector,vertex,vertical_spacing,visible,%  

427        visual,vpython,VPython,waitfor,Web,VPython,white,width,world,xtitle,%  

428        yellow,yoffset,ytitle%
429    }%,  

430    morekeywords={print,None,TypeError},%           % additional keywords
431    morestring=[b]{"""},%                          % treat triple quotes as strings
432    numbers=left,%                                % where to put line numbers
433    numbersep=10pt,%                             % how far line numbers are from code
434    numberstyle=\bfseries\tiny,%                  % set to 'none' for no line numbers
435    showstringspaces=false,%                     % show spaces in strings
436    showtabs=false,%                            % show tabs within strings
437    stringstyle=\sfssfontfamily\color{gsgreen},%    % color for strings
438    upquote=true,%                           % how to typeset quotes
439 }

```

Introduce a new, more intelligent [webvpythonblock](#)^{P.62} environment.

See <https://tex.stackexchange.com/a/232208/218142>.

```

440 \AtBeginEnvironment{webvpythonblock}{\catcode`\#=12}
441 \AtEndEnvironment{webvpythonblock}{\catcode`\#=6}
442 \NewTCBListing{auto counter,list inside=gsprogs}[webvpythonblock]{ 0{} D(){webvpython.org} m }%
443 {%
444     breakable,%
445     center,%
446     code = \newpage,%
447     %derivpeach,%
448     enhanced,%

```

```

449  hyperurl interior = https://#2,%
450  label = {gs:\thetcbcounter},%
451  left = 8mm,%
452  list entry = \thetcbcounter~~~~~#3,%
453  listing only,%
454  listing style = vpython,%
455  nameref = {#3},%
456  title = \begin{minipage}{1.5cm}%
457    \protect\qrcode*[https://#2]%
458  \end{minipage}\hspace{5mm}%
459  \begin{minipage}{0.8\textwidth}%
460    \texttt{Web VPython} Program \thetcbcounter: #3\\
461    \footnotesize{\color{white}\color{https://#2}}%
462  \end{minipage},%
463  width = 0.9\textwidth,%
464  {#1},%
465 }%

```

Here is a variant that omits the QR code.

```

466 \AtBeginEnvironment{webvpythonblock*}{\catcode`\#=12}
467 \AtEndEnvironment{webvpythonblock*}{\catcode`\#=6}
468 \NewTCBListing[use counter from=webvpythonblock,list inside=gsprogs]
469 {webvpythonblock*}{ 0{} D(){webvpython.org} m }%
470 {%
471   breakable,%
472   center,%
473   code = \newpage,%
474   %derivpeach,%
475   enhanced,%
476   hyperurl interior = https://#2,%
477   label = {gs:\thetcbcounter},%
478   left = 8mm,%
479   list entry = \thetcbcounter~~~~~#3,%
480   listing only,%
481   listing style = vpython,%
482   nameref = {#3},%
483   title = \texttt{Web VPython} Program \thetcbcounter: #3\\%
484   \footnotesize{\color{white}\color{https://#2}}%,%
485   width = 0.9\textwidth,%
486   {#1},%
487 }%

```

A new command for generating a list of Web VPython programs.

```

488 \NewDocumentCommand{\listofwebvpythonprograms}{}%
489 {%
490   \tcblistof[\section*]{gsprogs}{List of \texttt{Web VPython} Programs}%
491 }%

```

Introduce a new, more intelligent `\vpythonfile`^{P.68} command.

See <https://tex.stackexchange.com/q/616205/218142>.

```

492 \newcommand*\vpythonfile{\catcode`\#=12 \vpythonfile@auxA}%
493 \NewDocumentCommand{\vpythonfile@auxA}{ 0{} D(){vpython.org} m m }%
494 {%
495   \vpythonfile@auxB[#1](#2){#3}{#4}%
496   \catcode`\#=6
497 }%
498 \NewTCBInputListing[auto counter,list inside=vpprogs]
499 {\vpythonfile@auxB}{ 0{} D(){vpython.org} m m }%
500 {%

```

```

501     breakable,%
502     center,%
503     code = \newpage,%
504     %derivgray,%
505     enhanced,%
506     hyperurl interior = https://#2,%
507     label = {vp:\thetcbcounter},%
508     left = 8mm,%
509     list entry = \thetcbcounter~~~~~#4,%
510     listing file = {#3},%
511     listing only,%
512     listing style = vpython,%
513     nameref = {#4},%
514     title = \texttt{VPython} Program \thetcbcounter: #4,%
515     width = 0.9\textwidth,%
516     {#1},%
517 }%

```

A new command for generating a list of VPython programs.

```

518 \NewDocumentCommand{\listofvpythonprograms}{}{%
519   {%
520     \tcblistof[\section*]{vpprogs}{List of \texttt{VPython} Programs}%
521   }%

```

Introduce a new `\webvpythoninline`^{P. 70} command.

```

522 \DeclareTotalTCBox{\webvpythoninline}[ m ]{%
523   {%
524     bottom = Opt,%
525     bottomrule = 0.0mm,%
526     boxsep = 1.0mm,%
527     colback = gsbgray,%
528     colframe = gsbgray,%
529     left = Opt,%
530     leftrule = 0.0mm,%
531     nobeforeafter,%
532     right = Opt,%
533     rightrule = 0.0mm,%
534     sharp corners,%
535     tcbox raise base,%
536     top = Opt,%
537     toprule = 0.0mm,%
538   }%
539   {\lstinline[style = vpython]{#1}}%

```

Define `\vpythoninline`^{P. 70}, a semantic alias for VPython in-line listings.

```

540 \NewDocumentCommand{\vpythoninline}{}{\webvpythoninline}%

```

8 The `mandiexp` Package

`mandi` comes with an accessory package `mandiexp` which extends `mandi` with commands specific to *Matter & Interactions*.⁵ The commands are primarily for typesetting mathematical expressions used in that text. `mandiexp` requires, and loads, `mandi` but `mandi` doesn't require, and doesn't load, `mandiexp`. `mandiexp` requires the `\vec*` command and so loads `mandistudent` if it has not already been loaded.

Load `mandiexp` as you would any package in your preamble. There are no package options.

```
\usepackage{mandiexp}
```

`\mandiexpversion`

Typesets the current version and build date.

```
The version is \mandiexpversion{} and is a stable build.
```

```
The version is v3.2.2 dated 2024-02-27 and is a stable build.
```

8.1 The Fundamental Principles

<code>\lhsmomentumprinciple</code>	(LHS of delta form, bold vectors)
<code>\rhsmomentumprinciple</code>	(RHS of delta form, bold vectors)
<code>\lhsmomentumprincipleupdate</code>	(LHS of update form, bold vectors)
<code>\rhsmomentumprincipleupdate</code>	(RHS of update form, bold vectors)
<code>\momentumprinciple</code>	(delta form, bold vectors)
<code>\momentumprincipleupdate</code>	(update form, bold vectors)
<code>\lhsmomentumprinciple*</code>	(LHS of delta form, arrow vectors)
<code>\rhsmomentumprinciple*</code>	(RHS of delta form, arrow vectors)
<code>\lhsmomentumprincipleupdate*</code>	(LHS of update form, arrow vectors)
<code>\rhsmomentumprincipleupdate*</code>	(RHS of update form, arrow vectors)
<code>\momentumprinciple*</code>	(delta form, arrow vectors)
<code>\momentumprincipleupdate*</code>	(update form, arrow vectors)

Variants of command for typesetting the momentum principle. Use starred variants to get arrow notation for vectors.

⁵See *Matter & Interactions* and <https://matterandinteractions.org/> for details.

$\backslash(\backslash\text{lhsmomentumprinciple} \backslash) \quad \backslash\backslash$	Δp_{sys}
$\backslash(\backslash\text{rhsmomentumprinciple} \backslash) \quad \backslash\backslash$	$\mathbf{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{lhsmomentumprincipleupdate} \backslash) \quad \backslash\backslash$	$\mathbf{p}_{\text{sys,initial}} + \mathbf{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{rhsmomentumprincipleupdate} \backslash) \quad \backslash\backslash$	$\Delta p_{\text{sys}} = \mathbf{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{momentumprinciple} \backslash) \quad \backslash\backslash$	$\mathbf{p}_{\text{sys,final}} = \mathbf{p}_{\text{sys,initial}} + \mathbf{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{momentumprincipleupdate} \backslash) \quad \backslash\backslash$	$\Delta \vec{p}_{\text{sys}}$
$\backslash(\backslash\text{lhsmomentumprinciple*} \backslash) \quad \backslash\backslash$	$\vec{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{rhsmomentumprinciple*} \backslash) \quad \backslash\backslash$	$\vec{p}_{\text{sys,final}}$
$\backslash(\backslash\text{lhsmomentumprincipleupdate*} \backslash) \quad \backslash\backslash$	$\vec{p}_{\text{sys,initial}} + \vec{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{rhsmomentumprincipleupdate*} \backslash) \quad \backslash\backslash$	$\Delta \vec{p}_{\text{sys}} = \vec{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{momentumprinciple*} \backslash) \quad \backslash\backslash$	$\vec{p}_{\text{sys,final}} = \vec{p}_{\text{sys,initial}} + \vec{F}_{\text{sys,net}} \Delta t$
$\backslash(\backslash\text{momentumprincipleupdate*} \backslash)$	

$\backslash\text{lhsenergyprinciple}$	(LHS of delta form)
$\backslash\text{rhsenergyprinciple}[<+process...>]$	(RHS of delta form)
$\backslash\text{lhsenergyprincipleupdate}$	(LHS of update form)
$\backslash\text{rhsenergyprincipleupdate}[<+process...>]$	(RHS of update form)
$\backslash\text{energyprinciple}[<+process...>]$	(delta form)
$\backslash\text{energyprincipleupdate}[<+process...>]$	(update form)

Variants of command for typesetting the energy principle.

$\backslash(\backslash\text{lhsenergyprinciple} \backslash) \quad \backslash\backslash$	ΔE_{sys}
$\backslash(\backslash\text{rhsenergyprinciple} \backslash) \quad \backslash\backslash$	W_{ext}
$\backslash(\backslash\text{rhsenergyprinciple}[+Q] \backslash) \quad \backslash\backslash$	$W_{\text{ext}} + Q$
$\backslash(\backslash\text{energyprinciple} \backslash) \quad \backslash\backslash$	$\Delta E_{\text{sys}} = W_{\text{ext}}$
$\backslash(\backslash\text{energyprinciple}[+Q] \backslash) \quad \backslash\backslash$	$\Delta E_{\text{sys}} = W_{\text{ext}} + Q$
$\backslash(\backslash\text{lhsenergyprincipleupdate} \backslash) \quad \backslash\backslash$	$E_{\text{sys,final}}$
$\backslash(\backslash\text{rhsenergyprincipleupdate} \backslash) \quad \backslash\backslash$	$E_{\text{sys,initial}} + W_{\text{ext}}$
$\backslash(\backslash\text{rhsenergyprincipleupdate}[+Q] \backslash) \quad \backslash\backslash$	$E_{\text{sys,initial}} + W_{\text{ext}} + Q$
$\backslash(\backslash\text{energyprincipleupdate} \backslash) \quad \backslash\backslash$	$E_{\text{sys,final}} = E_{\text{sys,initial}} + W_{\text{ext}}$
$\backslash(\backslash\text{energyprincipleupdate}[+Q] \backslash)$	$E_{\text{sys,final}} = E_{\text{sys,initial}} + W_{\text{ext}} + Q$

$\backslash\text{lhsangularmomentumprinciple}$	(LHS of delta form, bold vectors)
$\backslash\text{rhsangularmomentumprinciple}$	(RHS of delta form, bold vectors)
$\backslash\text{lhsangularmomentumprincipleupdate}$	(LHS of update form, bold vectors)
$\backslash\text{rhsangularmomentumprincipleupdate}$	(RHS of update form, bold vectors)
$\backslash\text{angularmomentumprinciple}$	(delta form, bold vectors)
$\backslash\text{angularmomentumprincipleupdate}$	(update form, bold vectors)
$\backslash\text{lhsangularmomentumprinciple*}$	(LHS of delta form, arrow vectors)
$\backslash\text{rhsangularmomentumprinciple*}$	(RHS of delta form, arrow vectors)
$\backslash\text{lhsangularmomentumprincipleupdate*}$	(LHS of update form, arrow vectors)
$\backslash\text{rhsangularmomentumprincipleupdate*}$	(RHS of update form, arrow vectors)
$\backslash\text{angularmomentumprinciple*}$	(delta form, arrow vectors)
$\backslash\text{angularmomentumprincipleupdate*}$	(update form, arrow vectors)

Variants of command for typesetting the angular momentum principle. Use starred variants to get arrow notation for vectors.

```
\(\ lhsangularmomentumprinciple \)    \\
\(\ rhsangularmomentumprinciple \)    \\
\(\ lhsangularmomentumprincipleupdate \) \\
\(\ rhsangularmomentumprincipleupdate \) \\
\(\ angularmomentumprinciple \)        \\
\(\ angularmomentumprincipleupdate \)   \\
\(\ lhsangularmomentumprinciple* \)    \\
\(\ rhsangularmomentumprinciple* \)    \\
\(\ lhsangularmomentumprincipleupdate* \) \\
\(\ rhsangularmomentumprincipleupdate* \) \\
\(\ angularmomentumprinciple* \)       \\
\(\ angularmomentumprincipleupdate* \)
```

$$\begin{aligned} & \Delta \mathbf{L}_{A,\text{sys},\text{net}} \\ & \tau_{A,\text{sys},\text{net}} \Delta t \\ & \mathbf{L}_{A,\text{sys},\text{final}} \\ & \mathbf{L}_{A,\text{sys},\text{initial}} + \tau_{A,\text{sys},\text{net}} \Delta t \\ & \Delta \mathbf{L}_{A,\text{sys},\text{net}} = \tau_{A,\text{sys},\text{net}} \Delta t \\ & \mathbf{L}_{A,\text{sys},\text{final}} = \mathbf{L}_{A,\text{sys},\text{initial}} + \tau_{A,\text{sys},\text{net}} \Delta t \\ & \Delta \vec{\mathbf{L}}_{A,\text{sys},\text{net}} \\ & \vec{\tau}_{A,\text{sys},\text{net}} \Delta t \\ & \vec{\mathbf{L}}_{A,\text{sys},\text{final}} \\ & \vec{\mathbf{L}}_{A,\text{sys},\text{initial}} + \vec{\tau}_{A,\text{sys},\text{net}} \Delta t \\ & \Delta \vec{\mathbf{L}}_{A,\text{sys},\text{net}} = \vec{\tau}_{A,\text{sys},\text{net}} \Delta t \\ & \vec{\mathbf{L}}_{A,\text{sys},\text{final}} = \vec{\mathbf{L}}_{A,\text{sys},\text{initial}} + \vec{\tau}_{A,\text{sys},\text{net}} \Delta t \end{aligned}$$

8.2 Other Symbols

N 2021-02-13

\energyof{<label>}[<label>]

Generic symbol for the energy of some entity.

```
\(\ \energyof{\symup{electron}} \) \\
\(\ \energyof{\symup{electron}}[\symup{final}] \)
```

$$\begin{aligned} & E_{\text{electron}} \\ & E_{\text{electron},\text{final}} \end{aligned}$$

N 2021-02-13

\systemenergy[<label>]

Symbol for system energy.

```
\(\ \systemenergy \) \\
\(\ \systemenergy[\symup{final}] \)
```

$$\begin{aligned} & E_{\text{sys}} \\ & E_{\text{sys},\text{final}} \end{aligned}$$

N 2021-02-13

\particleenergy[<label>]

Symbol for particle energy.

```
\(\ \particleenergy \) \\
\(\ \particleenergy[\symup{final}] \)
```

$$\begin{aligned} & E_{\text{particle}} \\ & E_{\text{particle},\text{final}} \end{aligned}$$

N 2021-02-13

\restenergy[<label>]

Symbol for rest energy.

```
\(\ \restenergy \) \\
\(\ \restenergy[\symup{final}] \)
```

$$\begin{aligned} & E_{\text{rest}} \\ & E_{\text{rest},\text{final}} \end{aligned}$$

N 2021-02-13

\internalenergy[*<label>*]

Symbol for internal energy.

```
\(\internalenergy\)\  
\(\internalenergy[\symup{final}]\)\
```

E_{internal}
 $E_{\text{internal,final}}$

N 2021-02-13

\chemicalenergy[*<label>*]

Symbol for chemical energy.

```
\(\chemicalenergy\)\  
\(\chemicalenergy[\symup{final}]\)\
```

E_{chem}
 $E_{\text{chem,final}}$

N 2021-02-13

\thermalenergy[*<label>*]

Symbol for thermal energy.

```
\(\thermalenergy\)\  
\(\thermalenergy[\symup{final}]\)\
```

E_{therm}
 $E_{\text{therm,final}}$

N 2021-02-13

\photonenergy[*<label>*]

Symbol for photon energy.

```
\(\photonenergy\)\  
\(\photonenergy[\symup{final}]\)\
```

E_{photon}
 $E_{\text{photon,final}}$

N 2021-02-13

\translationalkineticenergy[*<label>*]

\translationalkineticenergy*[*<label>*]

Symbol for translational kinetic energy. The starred variant gives E notation.

```
\(\translationalkineticenergy\)\  
\(\translationalkineticenergy[\symup{initial}]\)\  
\(\translationalkineticenergy*\)\  
\(\translationalkineticenergy*[\symup{initial}]\)\
```

K_{trans}
 $K_{\text{trans,initial}}$
 E_K
 $E_{K,\text{initial}}$

N 2021-02-13

\rotationalkineticenergy[*<label>*]

\rotationalkineticenergy*[*<label>*]

Symbol for rotational kinetic energy. The starred variant gives E notation.

```
\(\rotationalkineticenergy\)\  
\(\rotationalkineticenergy[\symup{initial}]\)\  
\(\rotationalkineticenergy*\)\  
\(\rotationalkineticenergy*[\symup{initial}]\)\
```

K_{rot}
 $K_{\text{rot,initial}}$
 E_{rot}
 $E_{\text{rot,initial}}$

N 2021-02-13
N 2021-02-13

\vibrationalkineticenergy[*<label>*]
\vibrationalkineticenergy*[*<label>*]

Symbol for vibrational kinetic energy. The starred variant gives E notation.

```
\(\vibrationalkineticenergy\)\\"\\
\(\vibrationalkineticenergy[\symup{initial}]\)\\"\\
\(\vibrationalkineticenergy*\)\\"\\
\(\vibrationalkineticenergy*[\symup{initial}]\)\\"
```

K_{vib}
 $K_{\text{vib,initial}}$
 E_{vib}
 $E_{\text{vib,initial}}$

N 2021-02-13

\gravitationalpotentialenergy[*<label>*]

Symbol for gravitational potential energy.

```
\(\gravitationalpotentialenergy\)\\"\\
\(\gravitationalpotentialenergy[\symup{final}]\)\\"
```

U_g
 $U_{g,\text{final}}$

N 2021-02-13

\electricpotentialenergy[*<label>*]

Symbol for electric potential energy.

```
\(\electricpotentialenergy\)\\"\\
\(\electricpotentialenergy[\symup{final}]\)\\"
```

U_e
 $U_{e,\text{final}}$

N 2021-02-13

\springpotentialenergy[*<label>*]

Symbol for spring potential energy.

```
\(\springpotentialenergy\)\\"\\
\(\springpotentialenergy[\symup{final}]\)\\"
```

U_s
 $U_{s,\text{final}}$

8.3 **mandiexp** Source Code

Define the package version and date for global use, exploiting the fact that in a .sty file there is now no need for `\makeatletter` and `\makeatother`. This simplifies defining internal commands, with @ in the name, that are not for the user to know about.

```
1 \def\mandiexp@version{3.2.2}
2 \def\mandiexp@date{2024-02-27}
3 \NeedsTeXFormat{LaTeX2e}[2020-02-02]
4 \DeclareRelease{v3.2.2}{2024-02-27}{mandiexp.sty}
5 \DeclareCurrentRelease{v\mandiexp@version}{\mandiexp@date}
6 \ProvidesPackage{mandiexp}
7 [\mandiexp@date\space v\mandiexp@version\space Macros for Matter & Interactions]
```

Define a convenient package version command.

```
8 \newcommand*{\mandiexpversion}{v\mandiexp@version\space dated \mandiexp@date}
```

We need `mandi` to load `mathtools` and `unicode-math`.

```
9 \IfPackageLoadedTF{mandi}%
10  {}%
11  {}%
12  \RequirePackage{mandi}%
13 }%
```

We need `mandistudent` for the new `\vec*` command.

```
14 \IfPackageLoadedTF{mandistudent}%
15  {}%
16  {}%
17  \RequirePackage{mandistudent}%
18 }%
```

Load `xparse` if necessary.

```
19 \IfFormatAtLeastTF{2020-10-01}%
20  {}%
21  {\RequirePackage{xparse}}%
```

We require the `LuaLaTeX` engine.

```
22 \RequireLuaTeX
23 \typeout{}%
24 \typeout{mandiexp: You are using mandiexp \mandiexpversion.}%
25 \typeout{mandiexp: This package requires LuaLaTeX.}%
26 \typeout{}
```

The momentum principle's lefthand and righthand sides.

```
27 \NewDocumentCommand{\lhsmomentumprinciple}{ s }%
28  {}%
29  \Delta
30  \IfBooleanTF{#1}%
31  {}%
32  \vec*{p}%
33  {}%
34  {}%
35  \vec{p}%
36  {}%
37  \sb{\symup{sys}}%
38 }%
39 \NewDocumentCommand{\rhsmomentumprinciple}{ s }%
40  {}%
41  \IfBooleanTF{#1}%
42  {}%
```

```

43      \vec*{F}%
44  }%
45  {%
46      \vec{F}%
47  }%
48  \sb{\symup{sys,net}}\,,\Delta t%
49 }%

```

The momentum principle in update form, lefthand and righthand sides.

```

50 \NewDocumentCommand{\lhsmomentumprincipleupdate}{ s }%
51  {%
52      \IfBooleanTF{#1}%
53  {%
54      \vec*{p}%
55  }%
56  {%
57      \vec{p}%
58  }%
59  \sb{\symup{sys,final}}%
60 }%
61 \NewDocumentCommand{\rhsmomentumprincipleupdate}{ s }%
62  {%
63      \IfBooleanTF{#1}%
64  {%
65      \vec*{p}%
66  }%
67  {%
68      \vec{p}%
69  }%
70  \sb{\symup{sys,initial}}+%
71  \IfBooleanTF{#1}%
72  {%
73      \vec*{F}%
74  }%
75  {%
76      \vec{F}%
77  }%
78  \sb{\symup{sys,net}}\,,\Delta t%
79 }%

```

The full momentum principle as an expression.

```

80 \NewDocumentCommand{\momentumprinciple}{ s }%
81  {%
82      \IfBooleanTF{#1}%
83  {%
84      \lhsmomentumprinciple* = \rhsmomentumprinciple*%
85  }%
86  {%
87      \lhsmomentumprinciple = \rhsmomentumprinciple%
88  }%
89 }%

```

The full momentum principle in update form as an expression.

```

90 \NewDocumentCommand{\momentumprincipleupdate}{ s }%
91  {%
92      \IfBooleanTF{#1}%
93  {%
94      \lhsmomentumprincipleupdate* = \rhsmomentumprincipleupdate*%
95  }%

```

```

96      {%
97          \lhsmomentumprincipleupdate = \rhsmomentumprincipleupdate%
98      }%
99  }%

```

The energy principle's lefthand and righthand sides.

```

100 \NewDocumentCommand{\lhsenergyprinciple}{}{%
101     {%
102         \Delta E_{\symup{sys}}%
103     }%
104 \NewDocumentCommand{\rhsenergyprinciple}{ O{} }{%
105     {%
106         W_{\symup{ext}}#1%
107     }%

```

The energy principle in update form, lefthand and righthand sides.

```

108 \NewDocumentCommand{\lhsenergyprincipleupdate}{}{%
109     {%
110         E_{\symup{sys,final}}%
111     }%
112 \NewDocumentCommand{\rhsenergyprincipleupdate}{ O{} }{%
113     {%
114         E_{\symup{sys,initial}}+%
115         W_{\symup{ext}}#1%
116     }%

```

The full energy principle as an expression.

```

117 \NewDocumentCommand{\energyprinciple}{ O{} }{%
118     {%
119         \lhsenergyprinciple = \rhsenergyprinciple[#1]%
120     }%

```

The full energy principle in update form as an expression.

```

121 \NewDocumentCommand{\energyprincipleupdate}{ O{} }{%
122     {%
123         \lhsenergyprincipleupdate = \rhsenergyprincipleupdate[#1]%
124     }%

```

The angular momentum principle's lefthand and righthand sides.

```

125 \NewDocumentCommand{\lhsangularmomentumprinciple}{ s }{%
126     {%
127         \Delta%
128         \IfBooleanTF{#1}{%
129             {%
130                 \vec*{L}%
131             }%
132             {%
133                 \vec{L}%
134             }%
135             \sb{A}{\symup{,sys,net}}%
136         }%
137 \NewDocumentCommand{\rhsangularmomentumprinciple}{ s }{%
138     {%
139         \IfBooleanTF{#1}{%
140             {%
141                 \vec*{\tau}%
142             }%
143             {%
144                 \vec{\tau}%

```

```

145      }%
146      \sb{A\symup{,sys,net}}\,,\Delta t%
147 }%

```

The energy principle in update form, lefthand and righthand sides.

```

148 \NewDocumentCommand{\lhsangularmomentumprincipleupdate}{ s }%
149 {%
150     \IfBooleanTF{#1}%
151     {%
152         \vec*{L}%
153     }%
154     {%
155         \vec{L}%
156     }%
157     \sb{A,\symup{sys,final}}%
158 }%
159 \NewDocumentCommand{\rhsangularmomentumprincipleupdate}{ s }%
160 {%
161     \IfBooleanTF{#1}%
162     {%
163         \vec*{L}%
164     }%
165     {%
166         \vec{L}%
167     }%
168     \sb{A\symup{,sys,initial}}+%
169     \IfBooleanTF{#1}%
170     {%
171         \vec*{\tau}%
172     }%
173     {%
174         \vec{\tau}%
175     }%
176     \sb{A\symup{,sys,net}}\,,\Delta t%
177 }%

```

The full angular momentum principle as an expression.

```

178 \NewDocumentCommand{\angularmomentumprinciple}{ s }%
179 {%
180     \IfBooleanTF{#1}%
181     {%
182         \lhsangularmomentumprinciple* = \rhsangularmomentumprinciple*%
183     }%
184     {%
185         \lhsangularmomentumprinciple = \rhsangularmomentumprinciple%
186     }%
187 }%

```

The full angular momentum principle in update form as an expression.

```

188 \NewDocumentCommand{\angularmomentumprincipleupdate}{ s }%
189 {%
190     \IfBooleanTF{#1}%
191     {%
192         \lhsangularmomentumprincipleupdate* = \rhsangularmomentumprincipleupdate*%
193     }%
194     {%
195         \lhsangularmomentumprincipleupdate = \rhsangularmomentumprincipleupdate%
196     }%
197 }%

```

The symbol for an arbitrary entity.

```
198 \NewDocumentCommand{\energyof}{ m o }%
199   {%
200     E_{#1}%
201     \IfValueT{#2}{%
202       {, #2}%
203     }%
204   }%
```

The symbol for a system's energy.

```
205 \NewDocumentCommand{\systemenergy}{ o }%
206   {%
207     E_{\symup{sys}}%
208     \IfValueT{#1}{%
209       {, #1}%
210     }%
211   }%
212 \NewDocumentCommand{\particleenergy}{ o }%
213   {%
214     E_{\symup{particle}}%
215     \IfValueT{#1}{%
216       {, #1}%
217     }%
218   }%
```

The symbol for a particle's rest energy.

```
219 \NewDocumentCommand{\restenergy}{ o }%
220   {%
221     E_{\symup{rest}}%
222     \IfValueT{#1}{%
223       {, #1}%
224     }%
225   }%
```

The symbol for a system's internal energy.

```
226 \NewDocumentCommand{\internalenergy}{ o }%
227   {%
228     E_{\symup{internal}}%
229     \IfValueT{#1}{%
230       {, #1}%
231     }%
232   }%
```

The symbol for a system's chemical energy.

```
233 \NewDocumentCommand{\chemicalenergy}{ o }%
234   {%
235     E_{\symup{chem}}%
236     \IfValueT{#1}{%
237       {, #1}%
238     }%
239   }%
```

The symbol for a system's thermal energy.

```
240 \NewDocumentCommand{\thermalenergy}{ o }%
241   {%
242     E_{\symup{therm}}%
243     \IfValueT{#1}{%
244       {, #1}%
245     }%
246   }%
```

The symbol for a photon's energy.

```
247 \NewDocumentCommand{\photonenergy}{ o }%
248   {%
249     E_{\symup{photon}}%
250     \IfValueT{#1}%
251     {, #1}%
252   }%
253 }
```

The symbol for translational kinetic energy. `d[]` must be used because of the way consecutive optional arguments are handled. See `xparse` docs for details.

See <https://tex.stackexchange.com/a/569011/218142>.

```
254 \NewDocumentCommand{\translationalkineticenergy}{ s d[] }%
255   {%
256     \IfBooleanTF{#1}%
257     {%
258       E_{\bgroup \symup{K}}%
259     }%
260     {%
261       K_{\bgroup \symup{trans}}%
262     }%
263     \IfValueT{#2}{, #2}%
264     \egroup%
265   }%
```

The symbol for rotational kinetic energy.

```
266 \NewDocumentCommand{\rotationalkineticenergy}{ s d[] }%
267   {%
268     \IfBooleanTF{#1}%
269     {%
270       E_{\bgroup}%
271     }%
272     {%
273       K_{\bgroup}%
274     }%
275     \symup{rot}\IfValueT{#2}{, #2}%
276     \egroup%
277   }%
```

The symbol for vibrational kinetic energy.

```
278 \NewDocumentCommand{\vibrationalkineticenergy}{ s d[] }%
279   {%
280     \IfBooleanTF{#1}%
281     {%
282       E_{\bgroup}%
283     }%
284     {%
285       K_{\bgroup}%
286     }%
287     \symup{vib}\IfValueT{#2}{, #2}%
288     \egroup%
289   }%
```

The symbol for a system's gravitational potential energy.

```
290 \NewDocumentCommand{\gravitationalpotentialenergy}{ o }%
291   {%
292     U_{\symup{g}}%
293     \IfValueT{#1}%
294   }%
```

```
294      {,#1}%
295  }%
296 }%
```

The symbol for a system's electric potential energy.

```
297 \NewDocumentCommand{\electricpotentialenergy}{ o }%
298   {%
299     U_{\symup{e}}%
300     \IfValueT{#1}{%
301       {,#1}%
302     }%
303   }%
```

The symbol for a system's spring potential energy.

```
304 \NewDocumentCommand{\springpotentialenergy}{ o }%
305   {%
306     U_{\symup{s}}%
307     \IfValueT{#1}{%
308       {,#1}%
309     }%
310   }%
```

Index

Page numbers refer to page where the corresponding entry is documented and/or referenced.

A

\absolutevalue	55
\absolutevalue*	55
\acceleration	10
\accelerationvector	10
alternate value	8, 36
\alwaysusealternateunits	22
\alwaysuseapproximateconstants	31
\alwaysusebaseunits	22
\alwaysusederivedunits	22
\alwaysusepreciseconstants	31
\amount	10
\ampere	31
\anglebrackets	53
\anglebrackets*	53
\angularacceleration	10
\angularaccelerationvector	10
\angularfrequency	10
\angularimpulse	10
\angularimpulsevector	10
\angularmomentum	11
\angularmomentumprinciple	84
\angularmomentumprinciple*	84
\angularmomentumprincipleupdate	84
\angularmomentumprincipleupdate*	84
\angularmomentumvector	11
\angularvelocity	11
\angularvelocityvector	11
\area	11
\areachargedensity	11
\areamassdensity	11
\atomicmassunit	31
\avogadro	24

B

base value	8, 36
\biotsavartconstant	24
\bohradius	24
\boltzmann	25

C

\candela	31
\capacitance	11
\changein	53
\charge	11

\CheckConstant	24
\CheckQuantity	10
\chemicalenergy	86
\cmagneticfield	12
\cmagneticfieldvector	12
\colvec	60
\conductance	12
\conductivity	12
\contraction	61
\contraction*	61
\conventionalcurrent	12
\coulomb	32
\coulombconstant	25
\curlybraces	54
\curlybraces*	54
\current	12
\currentdensity	12
\currentdensityvector	12

D

\degree	32
derived value	8, 36
\df	62
\dielectricconstant	12
\direction	13
\directionvector	13
\dirvec	52
\dirvec*	53
\displacement	13
\displacementvector	13
\doublebars	53
\doublebars*	53
\duration	13

E

\earthmass	25
\earthmoondistance	25
\earthradius	25
\earthsundistance	25
\electricdipolemoment	13
\electricdipolemomentvector	13
\electricfield	13
\electricfieldvector	13
\electricflux	13
\electricpotential	13

\electricpotentialdifference	14
\electricpotentialenergy	87
\electronCharge	26
\electroncharge	26
\electroncurrent	14
\electronmass	26
\electronvolt	32
\elementarycharge	26
\emf	14
\emptyunit	31
\energy	14
\energydensity	14
\energyflux	15
\energyfluxvector	15
\energyinev	14
\energyinkev	14
\energyinmev	14
\energyof	85
\energyprinciple	84
\energyprincipleupdate	84
\entropy	15
Environments	
parts	56
physicsproblem	56
physicsproblem*	56
physicssolution	57
physicssolution*	57
usealternateunits	23
useapproximateconstants	31
usebaseunits	23
usederivedunits	23
usepreciseconstants	31
webpythonblock	62
webpythonblock*	62
\ev	32
F	
false value	8, 36
\farad	32
\finestructure	26
\force	15
\forcevector	15
\frequency	15
G	
\gravitationalfield	15
\gravitationalfieldvector	15
\gravitationalpotential	15
\gravitationalpotentialdifference	15
\gravitationalpotentialenergy	87
H	
\hbar	33
\henry	32
\hereusealternateunits	22
\hereuseapproximateconstants	31
\hereusebaseunits	22
\hereusederivedunits	22
\hereusepreciseconstants	31
\hertz	32
\hilite	58
\hydrogenmass	26
I	
\image	59
\impulse	16
\impulsevector	16
\indexofrefraction	16
\inductance	16
\internalenergy	86
\inverse	32
J	
\joule	32
K	
\kelvin	32
\kev	32
Keys	
preciseconstants	8
units	8
\kilolectronvolt	32
\kilogram	32
L	
\lhsangularmomentumprinciple	84
\lhsangularmomentumprinciple*	84
\lhsangularmomentumprincipleupdate	84
\lhsangularmomentumprincipleupdate*	84
\lhsenergyprinciple	84
\lhsenergyprincipleupdate	84
\lhsmomentumprinciple	83
\lhsmomentumprinciple*	83
\lhsmomentumprincipleupdate	83
\lhsmomentumprincipleupdate*	83
\lightspeed	32
\linearchargedensity	16
\linearmassdensity	16
\lorentzfactor	16
\luminousintensity	16

M	P
\magneticcharge	17
\magneticdipolemoment	17
\magneticdipolemomentvector	17
\magneticfield	17
\magneticfieldvector	17
\magneticflux	17
\magnitude	55
\magnitude*	55
\mandiexpversion	83
\mandisetup	8
\mandistudentversion	52
\mandiversion	8
\mass	17
\megaelectronvolt	32
\meter	32
\metre	32
\mev	32
\mivector	34
\mobility	17
\mole	32
\momentofinertia	17
\momentum	9, 18
\momentumflux	18
\momentumfluxvector	18
\momentumprinciple	83
\momentumprinciple*	83
\momentumprincipleupdate	83
\momentumprincipleupdate*	83
\momentumvector	9, 18
\moonearthdistance	27
\moonmass	27
\moonradius	27
\mzofp	27
N	R
\neutronmass	27
\NewPhysicalConstant	30
\NewScalarQuantity	22
\newton	32
\NewVectorQuantity	22
\norm	55
\norm*	55
\numberdensity	18
O	R
\ohm	32
\oofpez	23, 27
\oofpezcs	28
\parallelto	55
\parentheses	53
\parentheses*	53
\particleenergy	85
parts environment	56
\pascal	32
\per	31
\permeability	18
\permittivity	18
\perpendicularto	55
\photonenergy	86
physicsproblem environment	56
physicsproblem* environment	56
physicssolution environment	57
physicssolution* environment	57
\planck	28
\planckbar	28
\planckc	28
\planeangle	18
\polarizability	18
\power	18
\poynting	19
\poyntingvector	19
preciseconstants key	8
\pressure	19
\problempart	56
\protonCharge	28
\protoncharge	28
\protonmass	29

\rhsmomentumprincipleupdate	83
\rhsmomentumprincipleupdate*	83
\rotationalkineticenergy	86
\rotationalkineticenergy*	86
\rowvec	60
\rydberg	29
 S	
\second	32
\siemens	32
\singlebars	53
\singlebars*	53
\slot	61
\slot*	61
\solidangle	19
\specificheatcapacity	20
\speedoflight	29
\springpotentialenergy	87
\springstiffness	20
\springstretch	20
\squarebrackets	53
\squarebrackets*	53
\stefanboltzmann	29
\steradian	32
\strain	20
\stress	20
\sunearthdistance	29
\sunradius	29
\surfacegravfield	30
\systemenergy	85
 T	
\temperature	20
\tencomp	61
\tencomp*	61
\tento	34
\tesla	32
\thermalenergy	86
\timestento	34
\torque	20
\torquevector	20
\tothefour	32
\totheinversefour	32
\totheinversethree	32
\totheinversetwo	32
\tothethree	32
\tothetwo	32
\translationalkineticenergy	86
\translationalkineticenergy*	86
true value	8, 36
 U	
\units	31
units key	8
\universalgrav	30
usealternateunits environment	23
useapproximateconstants environment	31
usebaseunits environment	23
usederivedunits environment	23
usepreciseconstants environment	31
\usk	31
 V	
\vacuumpermeability	30
\vacuumpermittivity	30
\valence	61
\valence*	61
Values	
alternate	8, 36
base	8, 36
derived	8, 36
false	8, 36
true	8, 36
\vec	52
\vec*	52
\veccomp	61
\veccomp*	61
\vectoracceleration	10
\vectorangularacceleration	10
\vectorangularimpulse	10
\vectorangularmomentum	11
\vectorangularvelocity	11
\vectorcmagneticfield	12
\vectorcurrentdensity	12
\vectordirection	13
\vectordisplacement	13
\vectorelectricdipolemoment	13
\vectorelectricfield	13
\vectorenergyflux	15
\vectorforce	15
\vectorgravitationalfield	15
\vectorimpulse	16
\vectormagneticdipolemoment	17
\vectormagneticfield	17
\vectormomentum	9, 18
\vectormomentumflux	18
\vectorpoynting	19
\vectortorque	20
\vectorvelocity	20
\vectorvelocityc	21
\vectorwavenumber	21

\velocity	20
\velocityc	21
\velocitycvector	21
\velocityvector	20
\vibrationalkineticenergy	87
\vibrationalkineticenergy*	87
\volt	32
\volume	21
\volumechargedensity	21
\volumemassdensity	21
\vpythonfile	68
\vpythoninline	70

W

\watt	32
\wavelength	21
\wavenumber	21
\wavenumbervector	21
\weber	32
webpythonblock environment	62
webpythonblock* environment	62
\webpythoninline	70
\work	21

X

\xtento	34
---------	----

Y

\youngsmodulus	22
----------------	----

Z

\zerovec	53
\zerovec*	53